Version 2.2

Revision Date 04/21/2020

Print Date 02/11/2021

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name Material number	:	BOARDWALK AIR FRESHENER MANGO BWK 910 00000000001048770				
Manufacturer or supplier's	Manufacturer or supplier's details					
Company	:	Boardwalk / Essendant Co.				
Address	:	One Parkway North Deerfield, IL 60015				
Telephone	:	844-828-5617				

S
844-828-5617
Chemtel: 1(800)255-3924

Recommended use of the chemical and restrictions on use

Recommended use : Air Care

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	clear
Odour	characteristic

GHS Classification

Flammable aerosols	:	Category 1
Gases under pressure	:	Liquefied gas
Eye irritation	:	Category 2A
Specific target organ toxicity - single exposure	:	Category 3 (Central nervous system)

GHS label elements

Hazard pictograms	:	Flame Gas cylinder	Exclamation mark
Signal word	:	Danger	
Hazard statements	:	H222 Extremely flammal H280 Contains gas unde H319 Causes serious ey H336 May cause drowsin	r pressure; may explode if heated. e irritation.

Version 2.2	Revision Date 04/21/2020	Print Date 02/11/2021
Version 2.2 Precautionary statements	 Revision Date 04/21/2020 Prevention: P210 Keep away from heat, hot sur and other ignition sources. No smole P211 Do not spray on an open flam P251 Pressurized container: Do not use. P261 Avoid breathing dust/ fume/ g P264 Wash skin thoroughly after ha P271 Use only outdoors or in a well P280 Wear eye protection/ face pro Response: P304 + P340 + P312 IF INHALED: and keep comfortable for breathing. CENTER/doctor if you feel unwell. 	faces, sparks, open flames king. le or other ignition source. t pierce or burn, even after as/ mist/ vapours/ spray. andling. l-ventilated area. ttection. Remove person to fresh air
		Rinse cautiously with water ct lenses, if present and s: Get medical advice/ Do not expose to
	Disposal: P501 Dispose of contents/container regulation.	[,] in accordance with local

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 70 - < 90
propane	74-98-6	>= 10 - < 20
butane	106-97-8	>= 10 - < 20
diethyl phthalate	84-66-2	>= 1 - < 3

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice	 Show this safety data sheet to the doctor in attendance. Move out of dangerous area. Do not leave the victim unattended. Get medical attention.
If inhaled	 Remove to fresh air. Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	: Wash off immediately with soap and plenty of water.

Version 2.2	Revision Date 04/21/2020	Print Date 02/11/2021	
In case of eye contact	 Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. If skin irritation persists, call a physician. Rinse immediately with plenty of water for at least 15 minutes If eye irritation persists, consult a specialist. Remove contact lenses. Protect unharmed eye. 		
If swallowed	 Keep eye wide open while rinsing. Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. DO NOT induce vomiting unless directed to do so by a 		
Most important symptoms and effects, both acute and delayed	 physician or poison control center. Effects are dependent on exposure (dose, concentration, contact time). Effects are immediate and delayed. Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness. Symptoms may include irritation, redness, pain, and rash. Causes serious eye irritation. May cause drowsiness or dizziness. Review section 2 of SDS to see all potential hazards. 		
Notes to physician	: Treat symptomatically. Symptoms	•	

SECTION 5. FIREFIGHTING MEASURES

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions,	: Use personal protective equipment.
protective equipment and	Ensure adequate ventilation.
emergency procedures	Remove all sources of ignition.
	Evacuate personnel to safe areas.

Version 2.2	Revision Date 04/21/2020	Print Date 02/11/2021
Environmental precautions	 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal. 	
Methods and materials for containment and cleaning up		

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Do not puncture. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Do not breathe vapours or spray mist. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.
Conditions for safe storage	 BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	: Oxidizing agents
Storage temperature	: <49 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
		STEL	750 ppm 1,780 mg/m3	CAL PEL

Version 2.2

Revision Date 04/21/2020

Print Date 02/11/2021

		С	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
		STEL	1,000 ppm	ACGIH
diethyl phthalate	84-66-2	TWA	5 mg/m3	ACGIH
		TWA	5 mg/m3	NIOSH REL
		TWA	5 mg/m3	OSHA P0
		PEL	5 mg/m3	CAL PEL

Biological occupational exposure limits

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
2-PROPANONE	67-64-1	Acetone	Urine	End of	25 mg/l	ACGIH BEI
				shift (As		
				soon as		
				possible		
				after		
				exposure		
				ceases)		

Engineering measures Personal protective equipmen		effective ventilation in all processing areas
Respiratory protection		No personal respiratory protective equipment normally required.
Hand protection Remarks	:	The use of skin protection is not normally required; however, good industrial hygiene practice suggests the use of gloves or other appropriate skin protection whenever working with chemicals, and especially if prolonged or frequent contact is possible or likely.
Eye protection Skin and body protection Hygiene measures	:	Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded. No special protection is required. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Aerosol containing a liquefied gas
Colour	:	clear
Odour	:	characteristic
Odour Threshold	:	No data available
рН	:	Not applicable
Melting point/freezing point	:	No data available
Boiling point	:	Not applicable
Flash point	:	Not applicable
Evaporation rate	:	No data available
Flammability (solid, gas, liquid)	:	Extremely flammable aerosol.
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	4,826 hPa (21 °C)
Relative vapour density	:	No data available
Density	:	< 1 g/cm3
Solubility(ies)		
Water solubility	:	soluble
Partition coefficient: n- octanol/water	:	No data available
Auto-ignition temperature	:	not determined
Thermal decomposition	:	No data available
Viscosity		
Viscosity, kinematic	:	No data available
Heat of combustion	:	34.86 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.

Version 2.2	Revision Date 04/21/2020	Print Date 02/11/2021
Conditions to avoid	: Heat, flames and sparks.	et eurlicht
Incompatible materials	Extremes of temperature and dire : Oxidizing agents	ct suniight.
Hazardous decomposition products	 Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). 	

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	 Effects are dependent on exposure (dose, concentration, contact time). Effects are immediate and delayed. Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness. Symptoms may include irritation, redness, pain, and rash. Causes serious eye irritation. May cause drowsiness or dizziness. Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.
Carcinogenicity:	
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
Acute toxicity	
Components:	
acetone: Acute oral toxicity	: LD50 Rat: 5,800 mg/kg
Acute inhalation toxicity	: LC50 Rat: 132 mg/l Exposure time: 3 h
	LC50 Rat: 50.1 mg/l
Acute dermal toxicity	: LD50 Guinea pig: > 7,426 mg/kg

Version 2.2	Revision Date 04/21/2020	Print Date 02/11/2021
	LD50 Rabbit: > 7,426 mg/kg	
diethyl phthalate: Acute oral toxicity	: LD50 Oral Rat: 8,600 mg/kg	
,		
Acute inhalation toxicity	: LC50 Rat: > 4,640 mg/l	
	Exposure time: 6 h Test atmosphere: vapour	
Acute dermal toxicity	: LD50 Dermal Rat, male and female	e: > 10,000 mg/kg
Skin corrosion/irritation		
Product:		
Remarks: May irritate skin.		
Serious eye damage/eye irritation		
Product:		
Remarks: Eye irritation		
Respiratory or skin sensitisation		
No data available		
Germ cell mutagenicity		
No data available		
Carcinogenicity		
No data available		
Reproductive toxicity		
No data available		
STOT - single exposure		
No data available		
STOT - repeated exposure		
No data available		
Aspiration toxicity		
No data available		

Version 2.2

Revision Date 04/21/2020

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available Bioaccumulative potential

Product:	
Partition coefficient: n- octanol/water <u>Components:</u> butane :	: Remarks: No data available
Partition coefficient: n- octanol/water diethyl phthalate :	: Pow: 2.89
Partition coefficient: n- octanol/water	: log Pow: 2.2 (41 °C)
Mobility in soil	
No data available	
Other adverse effects	
No data available <u> Product:</u>	
Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological information	: Not applicable

SECTION 13. DISPOSAL CONSIDERATIONS

Version 2.2	Revision Date 04/21/2020	Print Date 02/11/2021
Disposal methods		
Masta from reaiduas	. Dianaga of in accordance with los	al regulations

: Dispose of in accordance with local regulations.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
The product should not be allowed to enter drains, water
courses or the soil.
: Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Version 2.2

Revision Date 04/21/2020

Print Date 02/11/2021

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
hydroquinone	123-31-9	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards	 Flammable (gases, aerosols, liquids, or solids) Gases under pressure Serious eye damage or eye irritation Specific target organ toxicity (single or repeated exposure)
SARA 302	: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 313	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
California Prop. 65	
	This product contains a chemical that is at or below California Propositions 65's "safe harbor level" for reproductive/developmental toxicity as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

The components of this product are reported in the following inventories:

DSL	All components of this product are on the Canadian DSL
TSCA	On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Version 2.2

Revision Date 04/21/2020

Print Date 02/11/2021

Further information

NFPA:

HEALTH	3
FLAMMABILITY	4
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme


HMIS III:

HEALTH	3
FLAMMABILITY	4
PHYSICAL HAZARD	3

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic



Version 2.2

Revision Date 04/21/2020

Print Date 02/11/2021

Version:	2.2
Revision Date:	04/21/2020
Print Date:	02/11/2021

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.