Safety Data Sheet

Classified in accordance 29 CFR 1910.1200

1. Product Identification

Product Information: 1000009834

Product Identifier: SW-676 CARPET SPOTTER PLUS

Recommended Use: Cleaner

Manufacturer/Importer/Distributor Information: PLZ CORP

2651 WARRENVILLE RD, STE 300 DOWNERS GROVE, IL 60515

US

800-332-9000

Emergency Telephone: 866-836-8855

2. Hazard(s) identification

Classification

Flammable Aerosol, category 1 Eye Irritation, category 2A

Label elements

HAZARD PICTOGRAMS



SIGNAL WORD
Danger

GHS HAZARD STATEMENTS

H222 Extremely flammable aerosol.
H319 Causes serious eye irritation.

GHS PRECAUTIONARY STATEMENTS

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P264+P265 Wash hands thoroughly after handling. Do not touch eyes.

P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P337+P317 If eye irritation persists: Get medical help.

4710 Page 1 / 7

Storage

P410+P412

Protect from sunlight. Do no expose to temperatures exceeding 50°C/ 122°F.

Disposal None

Other Information

None

3. Composition/Information on Ingredients

Mixtures

Chemical Identity	CAS Number	Content in Percent (%)*
Diethylene Glycol Monobutyl Ether	112-34-5	2.5-10
2-Butoxyethanol	111-76-2	2.5-10
Butane	106-97-8	2.5-10
Propane	74-98-6	1.0-2.5

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition Comments: Other components are not hazardous or are below required disclosure limits.

The exact concentration has been withheld as a trade secret.

4. First-aid Measures

SKIN CONTACT: Remove contaminated clothing and wash the skin thoroughly with soap and water after work.

EYE CONTACT: Rinse immediately with plenty of water.

INHALATION: Move to fresh air. **INGESTION:** Rinse mouth.

IMPORTANT SYMPTOMS: No data available

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED: Get medical attention if symptoms

occur.

5. Fire-fighting Measures

EXTINGUISHING MEDIA: Use fire-extinguishing media appropriate for surrounding materials.

UNSUITABLE EXTINGUISHING MEDIA: Do not use water jet as an extinguisher, as this will spread the fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: No data available

SPECIAL FIREFIGHTING PROCEDURES: No data available

6. Accidental Release Measures

PERSONAL PRECAUTIONS: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP: Stop the flow of material, if this is without risk. Absorb with sand or other inert absorbent.

ENVIRONMENTAL PRECAUTIONS: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer. Environmental manager must be informed of all major spillages.

7. Handling and Storage

HANDLING: Keep away from sources of ignition - No smoking. Keep away from open flames, hot surfaces and sources of ignition. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

SAFE HANDLING ADVICE: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

4710 Page 2 / 7

STORAGE: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

NFPA 30B: Aerosol Level 1

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

Chemical Name	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING
Diethylene Glycol Monobutyl Ether	10 ppm	N.E.	N.E.	N.E.
2-Butoxyethanol	20 ppm	N.E.	50 ppm	N.E.
Butane	N.E.	1000 ppm	N.E.	N.E.
Propane	N.E.	N.E.	1000 ppm	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

ENGINEERING CONTROLS: No data available.

Personal Protection

EYE/FACE PROTECTION: Wear goggles/face shield.

SKIN PROTECTION: No data available

RESPIRATORY PROTECTION: Seek advice from local supervisor. In case of inadequate ventilation use suitable respirator.

HYGIENIC PRACTICES: When using do not smoke. Observe good industrial hygiene practices.

4710 Page 3 / 7

9. Physical and Chemical Properties

Appearance:

Physical State: Liquid

Form: Spray Aerosol
Color: No data available
Odor: No data available
Odor Threshold: No data available
pH: No data available
Freeze Point, °C: No data available

Boiling Point, °C: 100
Flash Point, °C: -104

Flammability (solid, gas):

Evaporation Rate:

Combustibility:

No data available

No data available

Supports Combustion

Explosive Limits, %: 1.1 - 15.2 **Vapor Pressure @20°C, PSI:** 50 - 60

Vapor Density:

Relative Density:

No data available

No data available

No data available

No data available

Partition Coefficient, n-octanol/water:

No data available

No data available

No data available

Decomposition temperature, °C:

No data available

No data available

No data available

10. Stability and Reactivity

REACTIVITY: No data available.

STABILITY: Material is stable under normal conditions.

POSSIBILITY OF HAZARDOUS REACTIONS: No data available.

CONDITIONS TO AVOID: Avoid heat or contamination

INCOMPATIBILITY: No data available

HAZARDOUS DECOMPOSITION PRODUCTS: No data available.

11. Toxicological Information

Information on Likely Routes of Exposure

SKIN CONTACT EFFECTS: May cause irritation on prolonged or repeated contact.

EYE CONTACT EFFECTS: May cause slight irritation with tearing.

INHALATION EFFECTS: Inhalation of high concentrations of mists may cause irritation of the nose throat and upper respiratory tract.

INGESTION EFFECTS: Ingestion may cause irritation of the mucous membranes, esophagus and stomach.

Carcinogenicity: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible, or confirmed human carcinogen by IARC, ACGIH, NTP or OSHA.

4710 Page 4 / 7

The following values are calculated based on chapter 3.1 of the GHS document. The product itself has not been tested.

ATE ORAL 10,980 mg/kg

ATE DERMAL 8,491 mg/kg

ATE INHALATION 129 mg/kg

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

CAS-No.	<u>Chemical Name</u>	Oral LD50	Dermal LD50	Vapor LC50
112-34-5	Diethylene Glycol Monobutyl Ether	2,410 mg/kg	2,764 mg/kg	N.I.
111-76-2	2-Butoxyethanol	1,746 mg/kg	1,060 mg/kg	11 mg/l
106-97-8	Butane	N.I.	N.I.	658 mg/L Rat
74-98-6	Propane	5,000 mg/kg	5,000 mg/kg	100 mg/l

N.I. = No Information

Skin Corrosion & Irritation:

Product: No data available

Serious Eye Damage & Irritation:

Product: No data available

Components:

2-Butoxyethanol 111-76-2 Causes serious eye irritation.

Diethylene Glycol Monobutyl Ether 112-34-5 Causes serious eye irritation.

Respiratory or Skin Sensitization:

Product: No data available

STOT-Single Exposure:

Product: No data available

STOT-Repeated Exposure:

Product: No data available

Aspiration Hazard:

Product: No data available

Carcinogenicity:

Product: No data available

Reproductive Toxicity:

Product: No data available

Germ Cell Mutagenicity:

Product: No data available

12. Ecological Information

ECOLOGICAL INFORMATION: No data available

PERSISTENCE: No data available
BIOACCUMULATE: No data available
MOBILITY IN SOIL: No data available

4710 Page 5 / 7

OTHER ECOLOGICAL: No data available

13. Disposal Information

DISPOSAL INFORMATION: Consult with your local, regional and federal agencies for information on proper disposal.

CONTAMINATED PACKAGING: Consult with your local, regional and federal agencies for information on proper disposal.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No data available

DOT

UN Number: UN1950

Proper Shipping Name: AEROSOLS, FLAMMABLE

Technical Name: N/A

Hazard Class(es)

Class: 2.1
Subsidiary Risk N/A
Packing Group: N/A

IATA

UN Number: UN1950

Proper Shipping Name: AEROSOLS, FLAMMABLE

Technical Name: N/A

Hazard Class(es)

Class: 2.1
Subsidiary Risk: N/A
Packing Group: N/A

IMDG

UN Number: UN1950

Proper Shipping Name: AEROSOLS, FLAMMABLE

Technical Name: N/A

Hazard Class(es)

Class: 2.1
Subsidiary Risk: N/A
Packing Group: N/A

The classification shown In this section may be eligible for use of an exception, such as 'Limited Quantity', per the dangerous goods regulations. The shipper of this product should consult the applicable mode's regulation for the UN number displayed above to determine if any exceptions are available and may be utilized, at the shipper's discretion.

15. Regulatory Information

CHEMICAL INVENTORY STATUS:

TSCA On or in compliance with the inventory

DSL On or in compliance with the inventory

CALIFORNIA PROPOSITION 65 CARCINOGENS AND REPRODUCTIVE TOXINS:

4710 Page 6 / 7



WARNING

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

Chemical NameCAS-No.Ethylene Glycol107-21-1

16. Other Information

Revision Date: 6/8/2022

Datasheet produced by: Regulatory Department

Legend

N/A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

TLV - Threshold Limit Values (TLVs®), as established by the American Conference of Governmental Industrial Hygienists (ACGIH®)

PEL - Permissible Exposure Limit, as established by the U.S. Occupational Safety and Health Administration (OSHA), as amended

TSCA - U.S. Toxic Substance Control Act

DSL - Canada Environmental Protection Act: Domestic Substance List

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

4710 Page 7 / 7