

**Clorox Professional Products Company**

1221 Broadway
Oakland, CA 94612
Tel. (510) 271-7000

Material Safety Data Sheet

I Product: CLOROX COMMERCIAL SOLUTIONS® CLOROX® DISINFECTING SPRAY														
Description: FRAGRANCED AEROSOL														
Other Designations	Distributor	Emergency Telephone Nos.												
EPA Reg. No. 67619-3 Clorox Disinfecting Spray	Clorox Professional Products Company 1221 Broadway Oakland, CA 94612	For Medical Emergencies call: (800) 446-1014 For Transportation Emergencies Chemtrec (800) 424-9300												
II Health Hazard Data		III Hazardous Ingredients												
<u>EYES:</u> Will cause moderate, reversible eye irritation. <u>SKIN CONTACT:</u> Will cause minor irritation after prolonged contact. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. <u>INGESTION:</u> Low toxicity if ingested. May cause minor irritation of the mouth. Ingestion of large quantities may result in ethanol intoxication. <u>INHALATION:</u> Intentional misuse by concentrating and inhaling vapors may be harmful or fatal. Inhalation of high concentrations may cause irritation of the respiratory tract. Symptoms include headaches, dizziness, nausea, vomiting, and malaise. <u>MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:</u> None known. <u>EMERGENCY FIRST AID PROCEDURES:</u> <u>EYES:</u> Immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists, call a physician. <u>SKIN:</u> Wash with plenty of soap and water. IF SWALLOWED: Drink a glass of water. Call a physician.		<table border="1"><thead><tr><th>Ingredients</th><th>Concentration</th><th>Worker Exposure Limit</th></tr></thead><tbody><tr><td>Ethanol CAS #64-17-5</td><td>60-80%</td><td>1000ppm TLV - TWA</td></tr><tr><td>Propane CAS #7409806 (propellant)</td><td>1-5%</td><td>1000ppm PEL - TWA</td></tr><tr><td>Isobutane CAS #75-28-3</td><td>5-10%</td><td>Not Established</td></tr></tbody></table> None of the ingredients in this product are on the (ARC, NTP or OSHA carcinogen lists. TLV/TWA: Threshold Limit Value/Time Weighted Average. PEL: Permissible Exposure Limit. Source: OSHA	Ingredients	Concentration	Worker Exposure Limit	Ethanol CAS #64-17-5	60-80%	1000ppm TLV - TWA	Propane CAS #7409806 (propellant)	1-5%	1000ppm PEL - TWA	Isobutane CAS #75-28-3	5-10%	Not Established
Ingredients	Concentration	Worker Exposure Limit												
Ethanol CAS #64-17-5	60-80%	1000ppm TLV - TWA												
Propane CAS #7409806 (propellant)	1-5%	1000ppm PEL - TWA												
Isobutane CAS #75-28-3	5-10%	Not Established												
IV Special Protection and Precautions		V Transportation and Regulatory Data												
No special protection or precautions have been identified for using this product under directed consumer use conditions. The following recommendations are given for production facilities and for other conditions and situations where there is increased potential for accidental, large-scale, or prolonged exposure: <u>Hygienic Practices:</u> Wear safety glasses and protective gloves when handling product. <u>Engineering Controls:</u> Use explosion proof ventilation to minimize exposure to vapor or mist. <u>Work Practices:</u> Minimize skin contact and inhalation of vapor or mist.		U.S. DOT Hazard Class: ORM - D U.S. DOT Proper Shipping Name: Consumer Commodity. EPA - SARA Title III/CERCLA: Bulk product is regulated under sections 311/312. Packaged product is not reportable. TSCA Status: All components of this product are on the TSCA inventory.												
VI Spill Procedures/Waste Disposal		VII Reactivity Data												
<u>Steps to be taken in case material is released or spilled:</u> Eliminate all sources of ignition. Ventilate area. Mop up excess. Flush off any remaining material with soapy water. Flush again. <u>Respiratory Protection:</u> If handling large industrial or warehouse spills, people should use NIOSH approved respiratory protection. <u>Waste Disposal Method:</u> Do not puncture or incinerate (burn) empty or full cans. Dispose of in accordance with state and local regulations for consumer products. Empty cans may be landfilled. <u>Precautions to be taken in Handling and Storage:</u> Do not store above 120°F. Do not puncture or burn. Keep aerosols from fire or sparks. Store in accordance with NFPA 30B for Level 2 Aerosols. <u>Other Precautions:</u> N/A		Stability: Stable Conditions to Avoid: Temperatures over 120°F Incompatibility/Materials to Avoid: Alkalis and acids Hazardous Polymerization or Decomposition: None known												
VIII Fire and Explosion Data		IX Physical Data												
<u>Flashpoint:</u> Flashpoint of liquid is 66°F using a closed cup Herzog tester. Flame extension is between 16-18 inches with no flashback. <u>Fire Extinguishing Agents:</u> All types. <u>Special Fire Fighting Procedures:</u> N/A <u>Unusual Fire and Explosion Hazards:</u> Alcohol flames may not be readily visible. Exposure to temperatures over 120°F (49°C) may cause bursting or venting. Keep containers cool. Use equipment or shielding to protect personnel from bursting containers.		pH (no propellant) 9.2 Viscosity (no propellant) 3.2 cps at 20°C Density (no propellant) 0.86 g/ml at 25° Appearance and Odor Floral/Fruity odor												

©1963, 1991 THE CLOROX COMPANY

DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATIONAL SAFETY AND HEALTH DATE PREPARED 2/05