

(Material) Safety Data Sheet(M)SDS

IDENTITY (As Read on Label and Line)	Notice: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
LR44GH ALKALINE BUTTON CELL	

Section I

Manufacturer's Name Golden Power Corporation (HK) Ltd.	Telephone Number (852) 3125 2288
Address (Number, Sheet, City, State, and ZIP Code) Flat C, 20/F., Block 1, Tai Ping Industrial Centre, 57 Ting Kok Road, Tai Po, N.T., Hong Kong	Fax Number (852) 3125 2000 / 3125 2001
	Date Prepared 01-Jan-2018
	Signature of Preparer (optional)

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Names)	(contents, %/wt)	CAS No.
Manganese Dioxide (MnO ₂)	30.0 %	1313-13-9
Zinc (Zn)	11.0 %	7440-66-6
Potassium Hydroxide (KOH)	4.0 %	1310-58-3
Graphite (C)	3.0 %	7782-42-5
Cadmium (Cd)	<0.0005 %	7440-43-9
Mercury (Hg)	<0.0001 %	7439-97-6
Lead (Pb)	0.002%	7439-92-1

Section III – Physical/Chemical Characteristics

Boiling Point KOH aqua solution = 140 °C	Specific Gravity (H ₂ O=1) MnO ₂ = 4.4, Zn = 7.1, KOH = 2.0
Vapor Pressure (mmHg) KOH aqua solution = 3mmHg at 20 °C	Melting Point MnO ₂ decompose at 535°C Zn = 420 °C, KOH aqua = -35 °C
Vapor Density (Air = 1)	Evaporation Rate (Butyl Acetate = 1)

Solubility in Water KOH – complete

Appearance and Color

MnO₂ is a black powder, Graphite is also a black powder, Zinc is a silver metal.
KOH aqua is a colorless liquid with stimulative order.

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) Incombustible	Flammable Limits Not Available	LEL	UEL
--	-----------------------------------	-----	-----

Extinguishing Media: See Special Fire Fighting Procedure

Special Fire Fighting Procedure: In case of fire in an adjacent area, use water, CO₂ or dry chemical extinguishers if cells are packed in their original containers since the fuel of the fire is basically paper products. For bulk quantities of unpackaged cells use LITH-X (Graphite Base). In this case, do not use water.

As with any fire, wear self-contained breathing apparatus to avoid inhalation of hazardous decomposition products.

Unusual Fire and Explosion Hazards

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid			
	Stable	√	Do not short circuit, charge or dispose of in fire.			
Incompatibility (Materials to Avoid)		Hazardous polymerization will not occur.				
Hazardous Decomposition or Byproducts		Not Available				
Hazardous Polymerization	May Occur		Conditions to Avoid			
	Will Not Occur	√				
Section VI – Health Hazard Data						
Route(s) of Entry.	Inhalation?	Yes	Skin?	Yes	Ingestion?	Yes
Health Hazards (Acute and Chronic)		These chemicals are contained in a sealed can. Risk of exposure occurs, only if battery is mechanically or electrically abused. The most likely risk is acute exposure when a cell vents KOH is caustic alkali and attack the skin and eyes. Contact of electrolyte with skin and eyes should be avoided.				
Section VII – Ecological Information						
Cardnogenicity	NTP?	Not Available	IARC Monographs?	Not Available	OSHA Regulated?	Not Available
Signs and Symptoms of Exposure		KOH can cause chemical burn upon contact with skin.				
Medical Conditions Generally Aggravated by Exposure		An acute exposure will not generally aggravate any medical help.				
Section VIII –Emergency and First Aid Procedures						
In case of skin contact with content of battery, flush immediately with water. For eye contact, flush with copious amount of water for 10 minutes. If imitation persists, get medical help.						
Section IX - Precautions for Safe Handling and Use						
Steps to Be Taken in Case Material is Released or Spilled		Wipe out by wet duster.				
Section X - Waste Disposal Method						
General abandonment						
Section XI - Precautions to Be Taken in Handling and Storing						
Avoid mechanical or electrical abuse.						
Section XII - Other Precautions						
Do not short circuit, charge or dispose of in fire. Battery may explode or leak.						
Section XIII - Control Measures						
Respiratory Protection (Specify Type)		Not Available				
Ventilation	Local Exhaust	Not Available		Special	Not Available	
	Mechanical (General)	Not Available		Other	Not Available	
Protective Gloves	Butyl	Eye Protection		Safety Glasses		
Other Protective Clothing or Equipment		Not Available				
Work / Hygienic Practices		Not Available				
Section XIV – Regulatory Information						
Not Available						
Section XV – Other Information						

Not Available

Section XVI – Transportation Information

Golden Power **LR44GH** ALKALINE BUTTON CELL are considered to be “dry cell” batteries and are not listed as dangerous goods under below regulations:

1. Batteries, dry fulfills the requirement of U.S. Department of Transportation (DOT), Special Provision 130, i.e. they are offered for transportation in a manner that prevents the dangerous evolution of heat (for example, by the effective insulation of exposed terminals or batteries to be packed in such a way to prevent short circuits or generation of a dangerous quantity of heat.)”.
2. International Civil Aviation Administration (ICAO) and International Air Transport Association (IATA Dangerous Goods Regulation 59th Edition 2018), Special Provision A123, i.e. “An electrical battery or battery powered device having the potential of dangerous evolutions of heat that is not prepared so as to prevent a short-circuit (e.g. in the case of batteries, by the effective insulation of exposed terminals; or in the case of equipment, by disconnection of the battery and protection of exposed terminals or batteries to be packed in such a way to prevent short circuits or generation of a dangerous quantity of heat.) is forbidden from transportation.”
3. International Maritime Dangerous Goods Regulations (IMDG) **2016** edition does not regulate these batteries.

Examples of such batteries include alkali-manganese, silver oxide, zinc carbon, nickel metal hydride and nickel-cadmium batteries.

注：于 2018 年 1 月 1 日生效