



TECHNICAL DATA SHEET

During Business Hours: (800) 966-3458

Outside Business Hours: (800) 420-7186

Gorilla® Heavy Duty Mounting Tape

Product Description: Gorilla Heavy Duty Mounting Tape provides a quick and easy solution to mount and repair where traditional fasteners can't. This industrial strength tape conforms to smooth and rough surfaces, delivering an instant and weatherproof bond.

Product Construction: Black acrylic foam and adhesive, Clear removable liner

Standard Size: 60 inches long x 1 inch wide

Physical Properties:

Property	Standard	Metric	Test Method
Thickness	43 mils	1.09 mm	N/A
Initial Tack	10 lbf / in ²	44 N / 6.5 cm ²	PSTC 16
Adhesion to Steel, 90 deg, 72h	14 lbf / in	62 N / 25 mm	PSTC 101
Static Shear, 1" x 1", 1000g, SS	>10,000 minutes	>10,000 minutes	PSTC 107
Temperature Range - Application	Above 50°F	Above 10°C	N/A
	Best At Room Temperature		
Temperature Range - In Service	up to 194°F (long term) up to 302°F (short term)	up to 90°C (long term) up to 150°C (short term)	N/A

Note: The technical information and data found in this data sheet is intended only as representative and should not be used for specification purposes. The information is given in good faith, with tests recommended by PSTC and ASTM and conducted by Quality Assurance and Technical Service Departments. Individual rolls may vary slightly from these averages. Users should determine the suitability of the product for their own purposes by their own tests.