

1. Chemical Product and Company Identification

Material name C6602A

Use of the preparation Inkjet printing

Version #

Revision date 27-Mar-2008 CAS# Mixture

Manufacturer information Hewlett-Packard Company

1000 NE Circle Boulevard Corvallis, OR 97330-4239 US

Hewlett-Packard health effects line

(Toll-free within the US) 1-800-457-4209 1-503-494-7199 (Direct)

General information telephone number

HP Customer Care Line 1-800-474-6836 (Toll-free) 1-800-474-6836 1-208-323-2551 (Direct) **Date prepared** Mar 26, 2008 **MSDS** number 264631

2. Hazards Identification

Emergency overview Contact with skin and eyes may result in irritation.

Acute health effects Any potential hazards are presumed to be due to exposure to the components.

Skin contact

2-pyrrolidone

Contact with skin may result in irritation.

Alkyldiol

Contact with skin may result in irritation.

Food Black 2 acid salt # 3

This product may cause an allergic skin reaction.

Eye contact

2-pyrrolidone

Contact with eyes may result in irritation.

Alkyldiol

Contact with eyes may result in irritation.

Inhalation

2-pyrrolidone

Inhalation may result in respiratory irritation.

Inhalation may result in respiratory irritation.

Material name C6602A MSDS US Creation date Apr 30, 2003



Ingestion

2-pyrrolidone

Ingestion may result in nausea, vomiting and diarrhea.

Ethylene glycol

Harmful if swallowed. May cause kidney and liver damage. May depress the central nervous

system.

Food Black 2 acid salt # 3

Toxic if swallowed.

Potential health effects

Routes of exposure Potential routes of overexposure to this product are skin and eye contact

Inhalation of vapor and ingestion are not expected to be significant routes of exposure for this

product under normal use conditions.

Complete toxicity data are not available for this specific formulation

Chronic health effects Prolonged or repeated skin contact may cause skin irritation or allergic skin sensitization

reaction.

CarcinogenicityNone of the components present in this formulation at concentrations equal to or greater than

0.1% are listed by EU, MAK, IARC, NTP or OSHA.

3. Composition / Information on Ingredients

Component/substance	CAS number	% by weight		
Water	7732-18-5	> 30		
2-pyrrolidone	616-45-5	< 30		
Ethylene glycol	107-21-1	< 25		
Alkyldiol	Proprietary	< 7.5		
Food Black 2 acid salt # 3	Proprietary	< 5		
Composition comments	This ink supply contains an aqueous ink formulation.			

This product has been evaluated using criteria specified in 29 CFR 1910.1200 (Hazard

Communication Standard).

4. First Aid Measures

First aid procedures

Eye contact Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure)

for at least 15 minutes or until particles are removed. If irritation persists get medical attention.

Skin contact Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation

develops or persists.

Inhalation Remove to fresh air. If symptoms persist, get medical attention.

Ingestion If ingestion of a large amount does occur, seek medical attention.

5. Fire Fighting Measures

Flash point and method > 200 °F (> 93.3 °C); Pensky-Martens Closed Cup

Hazardous combustion

products

Refer to section 10.

Flammable properties None known.

Extinguishing media

Suitable extinguishing Dry chemical, CO2, water spray or regular foam.

media

Material name C6602A MSDS US
Creation date Apr 30, 2003 Version number 4 2 / 6



Unsuitable extinguishing

media

None known.

Unusual fire and explosion

hazard

None known.

Special firefighting

procedures

None established.

6. Accidental Release Measures

Personal precautions Wear appropriate personal protective equipment.

Environmental precautions Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

Methods for containment Dike the spilled material, where this is possible. Absorb with inert absorbent such as dry clay,

sand or diatomaceous earth, commercial sorbents, or recover using pumps.

Methods for cleaning up Soak up with inert absorbent material.

Other information Soak up with inert absorbent material. Slowly vacuum or sweep the material into a bag or

other sealed container. Dispose of in compliance with federal, state, and local regulations. See

also section 13 Disposal considerations.

7. Handling and Storage

Handling Avoid contact with skin, eyes and clothing.

Storage Keep out of the reach of children. Keep away from excessive heat or cold.

8. Exposure Controls/Personal Protection

Exposure limits

ACGIH

Components	CAS #	TWA	STEL	Ceiling
Ethylene glycol	107-21-1	Not established	Not established	100 mg/m3

Exposure guidelines Exposure limits have not been established for this product.

Personal protective equipment

General Use personal protective equipment to minimize exposure to skin and eye.

General hygeine

considerations

Handle in accordance with good industrial hygiene and safety practice.

9. Physical & Chemical Properties

Color Black

Odor threshold Not available Physical state Liauid.

7 - 7.4 рH

Melting point Not available Freezing point Not available **Boiling point** Not determined

Flash point > 200 °F (> 93.3 °C); Pensky-Martens Closed Cup

Evaporation rate Not determined **Flammability** Not available.

MSDS US Material name C6602A Creation date Apr 30, 2003 3 / 6



Flammability limits in air,

upper, % by volume

Not available

Flammability limits in air,

lower, % by volume

Not determined

Not determined Vapor pressure Vapor density > 1 (air = 1.0)

Specific gravity 1 - 1.2

Relative density Not available Solubility in water Soluble in water **Partition coefficient** Not available

(n-octanol/water)

Auto-ignition temperature Not available **Decomposition temperature** Not available

VOC < 3 % **Viscosity** > 2 cp

10. Chemical Stability & Reactivity Information

Chemical stability Stable under recommended storage conditions.

Incompatible materials Incompatible with strong bases and oxidizing agents.

Hazardous decomposition

products

Upon decomposition, this product may yield gaseous nitrogen oxides, carbon monoxide,

carbon dioxide and/or low molecular weight hydrocarbons.

Possibility of hazardous

reactions

Will not occur.

11. Toxicological Information

Oral toxicity LD50/oral/rat >2500 mg/kg (OECD 401)

Not classified for acute oral toxicity according to EU Directive 67/548/EEC and 1999/45/EC.

Eve irritation Non - irritant in rabbit (OECD 405) Sensitization Sensitizer in guinea pig (OECD 406)

Repeated contact may cause allergic reactions in very susceptible persons.

Symptoms and target organs

NIOSH - Pocket Guide - Target Organs

Ethylene glycol 107-21-1 respiratory system, skin, eyes, CNS

12. Ecological Information

Aquatic toxicity LC50/96h/Fathead minnows => 750 mg/L

Persistence and degradability Not available

13. Disposal Considerations

Disposal instructions Dispose of in compliance with federal, state, and local regulations.

14. Transportation Information

Department of Transportation (DOT) Requirements

Not regulated as hazardous goods.

MSDS US Material name C6602A Creation date Apr 30, 2003 Version number 4 4/6

IATA

Proper shipping name Not applicable **Hazard class** Not applicable

UN number None **Packing group** N/A **Packaging exceptions** None

15. Regulatory Information

US federal regulations US TSCA 12(b): Does not contain listed chemicals.

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Ethylene glycol 107-21-1 1.0 % de minimis concentration

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

107-21-1 5000 lb final RQ; 2270 kg final RQ Ethylene glycol

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Section 302 extremely hazardous substance

No

Section 311 hazardous

chemical

No

International regulations All chemical substances in this HP product have been notified or are exempt from notification

under chemical substances notification laws in the following countries: US (TSCA), EU

(EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea,

New Zealand, and China.

State regulations

U.S. - Pennsylvania - RTK (Right to Know) List

Ethylene glycol 107-21-1 Environmental hazard

U.S. - New Jersey - Right to Know Hazardous Substance List

107-21-1 sn 0878 Ethylene glycol

16. Other Information

HMIS® ratings Health: 1

> Flammability: 1 Physical hazard: 0

Health: 1 NFPA ratings

> Flammability: 1 Instability: 0

Issue date Mar 26 2008 9:09PM

Revision 3

Replaces sheet dated Jan 9 2006 10:58PM

Material name C6602A MSDS US 5 / 6

Creation date Apr 30, 2003 Version number 4



Disclaimer This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard

> Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as quaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in

Section 1 above and may not meet regulatory requirements in other countries.

MSDS sections updated

Explanation of abbreviations

11. Toxicological Information: Dermal irritation

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

CFR Code of Federal Regulations

COC Cleveland Open Cup

DOT Department of Transportation

EPCRA Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RCRA Resource Conservation and Recovery Act

REC Recommended

REL Recommended Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986

STEL Short-Term Exposure Limit

TCLP Toxicity Characteristics Leaching Procedure

TLV Threshold Limit Value

TSCA Toxic Substances Control Act VOC Volatile Organic Compounds

Material name C6602A MSDS US Creation date Apr 30, 2003 6/6