

Material Safety Data Sheet

•• • • •	ification
Material name	HP Color LaserJet C8552A Yellow Print Cartridge
Use of the preparation	This product is a yellow toner preparation that is used in HP Color LaserJet 9500/9500mfp series printers.
Version #	07
Revision date	04-08-2009
Company identification	Hewlett-Packard Company 3000 Hanover Street Palo Alto, CA 94304-1185 United States Telephone 650-857-1501
	Hewlett-Packard health effects line (Toll-free within the US) 1-800-457-4209 (Direct) 1-503-494-7199 HP Customer Care Line (Toll-free within the US) 1-800-474-6836 (Direct) 1-208-323-2551 Email: hpcustomerinquiries@hp.com
Date prepared	Apr 07, 2009
MSDS number	393296
Acute health effects	Liplikaly to source akin initiation
Skin contact	Unlikely to cause skin irritation.
Eye contact	May cause transient slight irritation
Inhalation	Minimal respiratory tract irritation may occur with exposure to large amounts of toner dust
Ingestion	Low acute toxicity. Ingestion is a minor route of entry for intended use of this product.
Potential health effects Routes of exposure	Potential routes of exposure under normal use conditions are skin and eye contact; and inhalation
	Ingestion is not expected to be a primary route of exposure for this product under normal conditions.
Chronic health effects	Prolonged inhalation of excessive amounts of any dust may cause lung damage. Use of the product as intended does not result in inhalation of excessive amounts of dust.
Carcinogenicity	None of the ingredients have been classified as carcinogens according to EU, IARC, MAK NTP, OSHA or ACGIH.
Other information	This product is not classified as hazardous according to OSHA CFR 1910.1200 or EU Directive 1999/45/EC, as amended.
	This preparation contains no component classified as Persistent, Bioaccumulative, and To (PBT) or very Persistent and very Bioaccumulative (vPvB) as defined under Regulation (E 1907/2006.

3. Composition / Information on Ingredients

Component/substance	CAS number	% by weight	
Styrene acrylate copolymer	Trade Secret	< 85	
Wax	Trade Secret	< 10	
Pigment	Trade Secret	< 4	

4. First Aid Measures

Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at least 15 minutes or until particles are removed. If irritation persists, consult a physician.
Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation develops or persists.
Move person to fresh air immediately. If irritation persists, consult a physician.
Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, consult a physician.
Not applicable
Carbon monoxide and carbon dioxide.
Like most organic material in powder form, toner can form explosive dust-air mixtures when finely dispersed in air.
CO2, water, or dry chemical
None known.
Like most organic material in powder form, toner can form explosive dust-air mixtures when finely dispersed in air.
If fire occurs in the printer, treat as an electrical fire.
None established.
Minimize dust generation and accumulation.
Do not flush into surface water or sanitary sewer system. See also section 13 Disposal considerations.
Slowly vacuum or sweep the material into a bag or other sealed container. Clean remainder with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated as dust
explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance with federal, state, and local regulations.
explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance
explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance with federal, state, and local regulations.
explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance with federal, state, and local regulations. Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Use
explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance with federal, state, and local regulations. Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Use with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry.
explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance with federal, state, and local regulations. Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Use with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Keep out of the reach of children. Store at room temperature. Store away from strong
explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance with federal, state, and local regulations. Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Use with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry. Protection
explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance with federal, state, and local regulations. Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Use with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry. Protection USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)
explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance with federal, state, and local regulations. Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Use with adequate ventilation. Keep away from excessive heat, sparks, and open flames. Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers. Keep tightly closed and dry. Protection USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)
-

Material Safety Data Sheet



invent	
Color	Black
Odor	Slight plastic odor
Odor threshold	Not available.
Physical state	Not available.
Form	solid
рН	Not applicable
Melting point	Not available.
Freezing point	Not available.
Boiling point	Not applicable
Flash point	Not applicable
Evaporation rate	Not applicable
Flammability	Not available.
Flammability limits in air, upper, % by volume	Not available.
Flammability limits in air, lower, % by volume	Not flammable
Vapor pressure	Not applicable
Vapor density	Not applicable
Specific gravity	1 - 1.2 (H2O = 1)
Relative density	Not available.
Solubility (water)	Negligible in water. Partiall soluble in toluene and xylene.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not applicable
Decomposition temperature	Not available.
Softening point	212 - 302 °F (100 - 150 °C)
Viscosity	Not applicable
Chemical Stability & Reactiv	-
Chemical stability	Stable under normal storage conditions.
Incompatible materials	Strong oxidizers
Hazardous decomposition products	Carbon monoxide and carbon dioxide.
Possibility of hazardous reactions	Will not occur.
Toxicological Information	
Oral toxicity	LD50/oral/rat >2000 mg/kg; (OECD 401); Not harmful.
Inhalation toxicity	No information available.
	Not classified for acute inhalation toxicity according to EU Directive 67/548/EEC and 1999/45/EC.
Eye irritation	Not classified as irritant, according to OSHA Hazard Communication Standard (HCS) and EL Directive 67/548/EEC and as amended.
Sensitization	Not classified as a sensitizer according to EU Directive 67/548/EEC and as amended, and OSHA HCS (US).
Chronic toxicity	No information available.
Chronic toxicity Carcinogenicity	No information available. Not a known or suspected carcinogen according to any IARC Monograph, NTP, OSHA Regulations (USA), EU Directive, or Proposition 65 (California).



Reproductive toxicity	Not classified as toxic according to EU Directive 67/548/EEC and as amended, California Prop. 65, and DFG (Germany).
12. Ecological Information	
Ecotoxicity	96.00 Hours, LL50 > 1000 mg/l, rainbow trout
Persistence and degradability	Not available.
13. Disposal Considerations	
Disposal instructions	Do not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state, and local regulations.
	HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkjet and LaserJet supplies. For more information and to determine if this service is available in your location, please visit http://www.hp.com/recycle.
14. Transport Information	
Not available.	
General	Not a regulated article under United States DOT, IATA, ADR, IMDG, or RID.
15. Regulatory Information	
US federal regulations	US EPA TSCA Inventory: All chemical substances in this product comply with all rules or orders under TSCA.
CERCLA (Superfund) reportab None	le quantity
Superfund Amendments and F	Reauthorization Act of 1986 (SARA)
Hazard categories	Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No
Section 302 extremely hazardous substance	Νο
Section 311 hazardous chemical	Νο
International regulations	All chemical substances in this HP product have been notified or are exempt from notification under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea, New Zealand, and China.
16. Other Information	
HMIS® ratings	Health: 1 Flammability: 1 Physical hazard: 0
NFPA ratings	Health: 1 Flammability: 1 Instability: 0
Issue date	Apr 7 2009 9:20PM
Revision	7
Replaces sheet dated	Mar 31 2009 4:47AM
Disclaimer	This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries.
Matarial name C8552A	Medell



Material Safety Data Sheet

MSDS sections updated Explanation of abbreviations Hazards Identification: Other information

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CFR	Code of Federal Regulations
COC	Cleveland Open Cup
DOT	Department of Transportation
EPCRA	Emergency Planning and Community Right-to-Know Act (aka SARA)
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation and Recovery Act
REC	Recommended
REL	Recommended Exposure Limit
SARA	Superfund Amendments and Reauthorization Act of 1986
STEL	Short-Term Exposure Limit
TCLP	Toxicity Characteristics Leaching Procedure
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
VOC	Volatile Organic Compounds
Manufacturer information	Hewlett-Packard Company 11311 Chinden Boulevard Boise, ID 83714 USA (Direct) 1-503-494-7199 (Toll-free within the US) 1-800-457-4209