MATERIAL SAFETY DATA SHEET

MAY BE USED TO COMPLY WITH OSHA'S HAZARD COMMUNICATION STANDARD 29CFR 1910.1200



Emergency telephone number 1-800-356-2728 telephone number 1-919-774-3808 6/5/2003 SIGNATURE OF PREPARER (OPTIONAL)

DATE PREPARED 6/5/2003 SECTION 1 CHEMICAL PRODUCT / NAME Product/Chemical Name: Lexmark E 210 Toner CAS Number: Mixture Other Designations: N/A

Other Designations: N/A General Use: Laser Printer

SECTION 2	COMPOSITION / INFORMATION ON INGREDIENTS	
		-

		CAS	%	OSHA	ACGIH	OTHER
ngredient Name:		NUMBER		PEL	TLV	LIMITS
				Toner is regulated under OSI otherwise regu		ot
Polyester		25038-59-9	88 - 92	otherwise regu	laleu.	
orycolor		20000 00 0	00 02			
Polypropylene		9003-07-0	2 - 4			
Carbon Black		1333-86-4	3 - 6			
Additive		31714-55-3	2			
NDA = NO DATA AVA	LABLE					
N/A = NOT APPLICAB						
SECTION 3 HAZAF	DOUS IDENTIFICA	TION				
Primary Entry Routes	Inhalati	on				HMIS
Target Organs:	N/A					H 1
Acute Effects:	N/A					F 1
nhalation:	Slight irritation of res	piratory tract.				R 0
Eye:	Dust may cause irrita	ation by mechanical	abrasion.			PPE
Skin:	Slight irritation.					Sec.8
Ingestion:	None known.					
Carcinogenicity:	N/A					
Medical Conditions A	gravated By Long-Tern	n Exposure:	Accumulation	of dust in the respiratory system		
		I	may cause co	ingestion.		
Chronic Effects:	If these materials are u	sed in a manner that c	ould generate	e airborne particles (dust), it is re	commended that	
	the dust be treated as a	A NUISANCE PARTIC	JLATE accor	ding to the American Conference	e of Government	
	Industrial Hygienists (A	CGIH)(TLV=10mg/m3).			
SECTION 4 FIRST	AID MEASURES					
Inhalation:	Remove to fresh air.	Treat any irritation	symptomati	cally. Call a physician if cond	ition persists.	
Eye Contact:	In case of contact in	mediately flush with	n plenty of lo	w pressure water for at least		
	15 minutes. Remove	e any contact lenses	to ensure t	horough flushing.		
Skin Contact:	Wash well with soap	and running water.				
Ingestion:	Give water to drink.					
After first a	id, get appropriate in-p	olant paramedic or c	ommunity n	nedical support		
if serious s	ign and symptoms per	sist.				
Note to Physicians:	N/A					
Special Precautions /	nrooduroo	N/A				

Section 5 FIRE FIGHT	TING MEASURES	
	N/A	
	N/A	
Burning Rate:	N/A	
Auto Ignition Temperatu	Jre: > 360 C	
LEL: N/A		
UEL: N/A		
Flammability Classificat	tion:	1 Slight (HMIS, NFPA)
Extinguishing Media:		Water spray, foam, carbon dioxide.
Unusual Fire or explosic	on hazards:	May form flammable dust-air mixture.
Hazardous combustion		Carbon monoxide, carbon dioxide, nitrogen oxide and smoke.
		Under certain conditions some aliphatic aldehydes and carboxylic acids
		may form.
Fire- Fighting Instruction	ns:	Do not release runoff from fire control methods to sewers or waterways.
Fire-Fighting Equipment:		Because fire may produce toxic thermal decomposition products, wear a
		self-contained breathing apparatus (SCBA) with full facepiece operated
		in pressure-demand or positive-pressure mode.
SECTION 6 ACCIDE	NTAL RELEASE ME	
Spill / Leak Procedures:		
•		r disposal, suction up remaining material with high efficiency
	vacuum cleaner.	
Large Spills:	Scoop into container for	r disposal, suction up remaining material with high efficiency
	vacuum cleaner.	
Containment:	For large spills, avoid	suspending particles, collect for later disposal. Do not release
	into sewers or waterw	
	No special requireme	•
REGULATORY REQUIREM		
SECTION 7 HANDLIN	NG AND STORAGE	
	Keep containers closed	at all times. Avoid creating dust. Keep away from ignition sources.
Handling Precautions:		at all times. Avoid creating dust. Keep away from ignition sources. tion. (Below 40 C / 100 F)
Handling Precautions: Storage Requirements:	Store in a cool, dry loca	at all times. Avoid creating dust. Keep away from ignition sources. tion. (Below 40 C / 100 F)
Handling Precautions: Storage Requirements: Regulatory Requirement	Store in a cool, dry loca ts: N/A	tion. (Below 40 C / 100 F)
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUR	Store in a cool, dry loca ts: N/A	
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUE Engineering Controls:	Store in a cool, dry loca ts: N/A RE CONTROLS / PE	tion. (Below 40 C / 100 F) RSONAL PROTECTION
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUE Engineering Controls: Ventilation:	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or loca	tion. (Below 40 C / 100 F) RSONAL PROTECTION exhaust ventilation systems to maintain airborne concentrations
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUE Engineering Controls: Ventilation:	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or loca below OSHA PELs (sec	tion. (Below 40 C / 100 F) RSONAL PROTECTION L exhaust ventilation systems to maintain airborne concentrations 2.2). Local exhaust ventilation is preferred because it prevents contaminant
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUE Engineering Controls: Ventilation:	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or loca below OSHA PELs (see dispersion into the work	tion. (Below 40 C / 100 F) RSONAL PROTECTION exhaust ventilation systems to maintain airborne concentrations
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUE Engineering Controls: Ventilation: Administrative Controls	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or local below OSHA PELs (see dispersion into the work :	tion. (Below 40 C / 100 F) RSONAL PROTECTION exhaust ventilation systems to maintain airborne concentrations c.2). Local exhaust ventilation is preferred because it prevents contaminant area by controlling it at its source.
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUE Engineering Controls: Ventilation:	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or loca below OSHA PELs (see dispersion into the work :: Seek profe	tion. (Below 40 C / 100 F) RSONAL PROTECTION exhaust ventilation systems to maintain airborne concentrations c.2). Local exhaust ventilation is preferred because it prevents contaminant area by controlling it at its source. essional advise prior to respirator selection and use.
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUE Engineering Controls: Ventilation: Administrative Controls	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or local below OSHA PELs (see dispersion into the work : Seek profe Follow OS	tion. (Below 40 C / 100 F) RSONAL PROTECTION I exhaust ventilation systems to maintain airborne concentrations c.2). Local exhaust ventilation is preferred because it prevents contaminant area by controlling it at its source. I essional advise prior to respirator selection and use. HA respirator regulations (29 CFR 1910.134) and, if necessary, wear
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUE Engineering Controls: Ventilation: Administrative Controls	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or local below OSHA PELs (see dispersion into the work : Seek profe Follow OS a MSHA/N	tion. (Below 40 C / 100 F) RSONAL PROTECTION I exhaust ventilation systems to maintain airborne concentrations c.2). Local exhaust ventilation is preferred because it prevents contaminant c area by controlling it at its source. Ressional advise prior to respirator selection and use. HA respirator regulations (29 CFR 1910.134) and, if necessary, wear IOSH-approved respirator. select respirator based on its suitability
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUE Engineering Controls: Ventilation: Administrative Controls	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or local below OSHA PELs (see dispersion into the work : Seek profe Follow OS a MSHA/N to provide	tion. (Below 40 C / 100 F) RSONAL PROTECTION I exhaust ventilation systems to maintain airborne concentrations c.2). Local exhaust ventilation is preferred because it prevents contaminant c area by controlling it at its source. Ressional advise prior to respirator selection and use. HA respirator regulations (29 CFR 1910.134) and, if necessary, wear IOSH-approved respirator. select respirator based on its suitability adequate worker protection for given working conditions, level of
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUE Engineering Controls: Ventilation: Administrative Controls	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or loca below OSHA PELs (see dispersion into the work : Seek profe Follow OS a MSHA/N to provide airborne co	tion. (Below 40 C / 100 F) RSONAL PROTECTION I exhaust ventilation systems to maintain airborne concentrations 2.2). Local exhaust ventilation is preferred because it prevents contaminant area by controlling it at its source. Inssional advise prior to respirator selection and use. HA respirator regulations (29 CFR 1910.134) and, if necessary, wear IOSH-approved respirator. select respirator based on its suitability adequate worker protection for given working conditions, level of contamination, and presence of sufficient oxygen. For emergency or
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUE Engineering Controls: Ventilation: Administrative Controls	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or local below OSHA PELs (see dispersion into the work : Seek profe Follow OS a MSHA/N to provide airborne co nonroutine	tion. (Below 40 C / 100 F) RSONAL PROTECTION I exhaust ventilation systems to maintain airborne concentrations 2.2). Local exhaust ventilation is preferred because it prevents contaminant area by controlling it at its source. Inssional advise prior to respirator selection and use. HA respirator regulations (29 CFR 1910.134) and, if necessary, wear IOSH-approved respirator. select respirator based on its suitability adequate worker protection for given working conditions, level of contamination, and presence of sufficient oxygen. For emergency or operation (cleaning spills, reactor vessels, or storage tanks), wear
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUE Engineering Controls: Ventilation: Administrative Controls	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or local below OSHA PELs (see dispersion into the work : Seek profe Follow OS a MSHA/N to provide airborne co nonroutine an SCBA.	tion. (Below 40 C / 100 F) RSONAL PROTECTION I exhaust ventilation systems to maintain airborne concentrations 2.2). Local exhaust ventilation is preferred because it prevents contaminant a area by controlling it at its source. Issional advise prior to respirator selection and use. HA respirator regulations (29 CFR 1910.134) and, if necessary, wear IOSH-approved respirator. select respirator based on its suitability adequate worker protection for given working conditions, level of ontamination, and presence of sufficient oxygen. For emergency or operation (cleaning spills, reactor vessels, or storage tanks), wear <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient</i>
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUE Engineering Controls: Ventilation: Administrative Controls Respiratory Protection:	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or local below OSHA PELs (see dispersion into the work : Seek profe Follow OS a MSHA/N to provide airborne co nonroutine an SCBA. atmospher	tion. (Below 40 C / 100 F) RSONAL PROTECTION I exhaust ventilation systems to maintain airborne concentrations 2.2). Local exhaust ventilation is preferred because it prevents contaminant a area by controlling it at its source. Assional advise prior to respirator selection and use. HA respirator regulations (29 CFR 1910.134) and, if necessary, wear IOSH-approved respirator. select respirator based on its suitability adequate worker protection for given working conditions, level of ontamination, and presence of sufficient oxygen. For emergency or operation (cleaning spills, reactor vessels, or storage tanks), wear <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient</i> res.
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUE Engineering Controls: Ventilation: Administrative Controls	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or local below OSHA PELs (see dispersion into the work : Seek profe Follow OS a MSHA/N to provide airborne co nonroutine an SCBA. atmospher ipment: Wear chem	tion. (Below 40 C / 100 F) RSONAL PROTECTION L exhaust ventilation systems to maintain airborne concentrations 2.2). Local exhaust ventilation is preferred because it prevents contaminant a area by controlling it at its source. RSSIN advise prior to respirator selection and use. HA respirator regulations (29 CFR 1910.134) and, if necessary, wear IOSH-approved respirator. select respirator based on its suitability adequate worker protection for given working conditions, level of contamination, and presence of sufficient oxygen. For emergency or operation (cleaning spills, reactor vessels, or storage tanks), wear Warning! Air-purified respirators do not protect workers in oxygen-deficient es. nically protective gloves, boots, aprons, and gauntlets to prevent
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUE Engineering Controls: Ventilation: Administrative Controls Respiratory Protection:	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or local below OSHA PELs (see dispersion into the work : Seek profe Follow OS a MSHA/N to provide airborne co nonroutine an SCBA. atmospher ipment: Wear chen prolonged	tion. (Below 40 C / 100 F) RSONAL PROTECTION I exhaust ventilation systems to maintain airborne concentrations 2.2). Local exhaust ventilation is preferred because it prevents contaminant area by controlling it at its source. Essional advise prior to respirator selection and use. HA respirator regulations (29 CFR 1910.134) and, if necessary, wear IOSH-approved respirator. select respirator based on its suitability adequate worker protection for given working conditions, level of contamination, and presence of sufficient oxygen. For emergency or operation (cleaning spills, reactor vessels, or storage tanks), wear <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient</i> res. nically protective gloves, boots, aprons, and gauntlets to prevent or repeated skin contact. Wear protective eyeglasses or
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUE Engineering Controls: Ventilation: Administrative Controls Respiratory Protection:	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or local below OSHA PELs (see dispersion into the work : Seek profe Follow OS a MSHA/N to provide airborne co nonroutine an SCBA. atmospher ipment: Wear chen prolonged chemical s	tion. (Below 40 C / 100 F) RSONAL PROTECTION I exhaust ventilation systems to maintain airborne concentrations 2.2). Local exhaust ventilation is preferred because it prevents contaminant area by controlling it at its source. Essional advise prior to respirator selection and use. HA respirator regulations (29 CFR 1910.134) and, if necessary, wear IOSH-approved respirator. select respirator based on its suitability adequate worker protection for given working conditions, level of contamination, and presence of sufficient oxygen. For emergency or operation (cleaning spills, reactor vessels, or storage tanks), wear <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient</i> res. nically protective gloves, boots, aprons, and gauntlets to prevent or repeated skin contact. Wear protective eyeglasses or afety goggles, per OSHA eye-and face-protection regulations
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUE Engineering Controls: Ventilation: Administrative Controls Respiratory Protection:	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or local below OSHA PELs (see dispersion into the work : Seek profe Follow OS a MSHA/N to provide airborne co nonroutine an SCBA. atmospher prolonged chemical s (29CFR 19	tion. (Below 40 C / 100 F) RSONAL PROTECTION I exhaust ventilation systems to maintain airborne concentrations 2.2). Local exhaust ventilation is preferred because it prevents contaminant area by controlling it at its source. Essional advise prior to respirator selection and use. HA respirator regulations (29 CFR 1910.134) and, if necessary, wear IOSH-approved respirator. select respirator based on its suitability adequate worker protection for given working conditions, level of contamination, and presence of sufficient oxygen. For emergency or operation (cleaning spills, reactor vessels, or storage tanks), wear <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient</i> res. nically protective gloves, boots, aprons, and gauntlets to prevent or repeated skin contact. Wear protective eyeglasses or afety goggles, per OSHA eye-and face-protection regulations 10.133). Contact lenses are not eye protective devices. appropriate
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUF Engineering Controls: Ventilation: Administrative Controls Respiratory Protection:	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or local below OSHA PELs (see dispersion into the work : Seek profe Follow OS a MSHA/N to provide airborne co nonroutine an SCBA. atmospher prolonged chemical s (29CFR 19 protection	tion. (Below 40 C / 100 F) RSONAL PROTECTION I exhaust ventilation systems to maintain airborne concentrations 2.2). Local exhaust ventilation is preferred because it prevents contaminant area by controlling it at its source. Assional advise prior to respirator selection and use. HA respirator regulations (29 CFR 1910.134) and, if necessary, wear IOSH-approved respirator. select respirator based on its suitability adequate worker protection for given working conditions, level of ontamination, and presence of sufficient oxygen. For emergency or operation (cleaning spills, reactor vessels, or storage tanks), wear <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient</i> es. nically protective gloves, boots, aprons, and gauntlets to prevent or repeated skin contact. Wear protective eyeglasses or afety goggles, per OSHA eye-and face-protection regulations 010.133). Contact lenses are not eye protective devices. appropriate must be worn instead of, or in conjunction with contact lenses.
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUE Engineering Controls: Ventilation: Administrative Controls Respiratory Protection: Protective Clothing/Equ Safety Stations:	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or local below OSHA PELs (see dispersion into the work : Seek profe Follow OS a MSHA/N to provide airborne co nonroutine an SCBA. atmospher prolonged chemical s (29CFR 19 protection Make eme	tion. (Below 40 C / 100 F) RSONAL PROTECTION I exhaust ventilation systems to maintain airborne concentrations 2.2). Local exhaust ventilation is preferred because it prevents contaminant 3. area by controlling it at its source. RSSIONAL advise prior to respirator selection and use. HA respirator regulations (29 CFR 1910.134) and, if necessary, wear IOSH-approved respirator. select respirator based on its suitability adequate worker protection for given working conditions, level of contamination, and presence of sufficient oxygen. For emergency or operation (cleaning spills, reactor vessels, or storage tanks), wear <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient</i> res. nically protective gloves, boots, aprons, and gauntlets to prevent or repeated skin contact. Wear protective eyeglasses or afety goggles, per OSHA eye-and face-protection regulations 10.133). Contact lenses are not eye protective devices. appropriate must be worn instead of, or in conjunction with contact lenses. rgency eyewash stations and washing facilities available in work area.
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUF Engineering Controls: Ventilation: Administrative Controls Respiratory Protection:	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or local below OSHA PELs (see dispersion into the work : Seek profe Follow OS a MSHA/N to provide airborne co nonroutine an SCBA. atmospher prolonged chemical s (29CFR 19 protection Make eme nt: Separate of	tion. (Below 40 C / 100 F) RSONAL PROTECTION I exhaust ventilation systems to maintain airborne concentrations 2.2). Local exhaust ventilation is preferred because it prevents contaminant 3. area by controlling it at its source. Ressional advise prior to respirator selection and use. HA respirator regulations (29 CFR 1910.134) and, if necessary, wear IOSH-approved respirator. select respirator based on its suitability adequate worker protection for given working conditions, level of ontamination, and presence of sufficient oxygen. For emergency or operation (cleaning spills, reactor vessels, or storage tanks), wear <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient</i> es. nically protective gloves, boots, aprons, and gauntlets to prevent or repeated skin contact. Wear protective eyeglasses or afety goggles, per OSHA eye-and face-protection regulations 10.133). Contact lenses are not eye protective devices. appropriate must be worn instead of, or in conjunction with contact lenses. rgency eyewash stations and washing facilities available in work area. contaminated work clothing from street clothes. Launder before
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUE Engineering Controls: Ventilation: Administrative Controls Respiratory Protection: Protective Clothing/Equ	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or local below OSHA PELs (see dispersion into the work : Seek profe Follow OS a MSHA/N to provide airborne co nonroutine an SCBA. atmospher prolonged chemical s (29CFR 19 protection Make eme nt: Separate o re-use. Re	tion. (Below 40 C / 100 F) RSONAL PROTECTION I exhaust ventilation systems to maintain airborne concentrations 2.2). Local exhaust ventilation is preferred because it prevents contaminant area by controlling it at its source. Ressional advise prior to respirator selection and use. HA respirator regulations (29 CFR 1910.134) and, if necessary, wear IOSH-approved respirator. select respirator based on its suitability adequate worker protection for given working conditions, level of contamination, and presence of sufficient oxygen. For emergency or operation (cleaning spills, reactor vessels, or storage tanks), wear <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient</i> tes. nically protective gloves, boots, aprons, and gauntlets to prevent or repeated skin contact. Wear protection regulations 10.133). Contact lenses are not eye protective devices. appropriate must be worn instead of, or in conjunction with contact lenses. rgency eyewash stations and washing facilities available in work area. contaminated work clothing from street clothes. Launder before move this material from your shoes and clean personal protective
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUF Engineering Controls: Ventilation: Administrative Controls Respiratory Protection: Protective Clothing/Equ Safety Stations: Contaminated Equipment	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or local below OSHA PELs (see dispersion into the work : Seek profe Follow OS a MSHA/N to provide airborne co nonroutine an SCBA. atmospher prolonged chemical s (29CFR 19 protection Make eme equipment	tion. (Below 40 C / 100 F) RSONAL PROTECTION I exhaust ventilation systems to maintain airborne concentrations 2.2). Local exhaust ventilation is preferred because it prevents contaminant area by controlling it at its source. Its solution is prior to respirator selection and use. HA respirator regulations (29 CFR 1910.134) and, if necessary, wear IOSH-approved respirator. select respirator based on its suitability adequate worker protection for given working conditions, level of ontamination, and presence of sufficient oxygen. For emergency or operation (cleaning spills, reactor vessels, or storage tanks), wear <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient</i> tes. nically protective gloves, boots, aprons, and gauntlets to prevent or repeated skin contact. Wear protective eyeglasses or afety goggles, per OSHA eye-and face-protection regulations 10.133). Contact lenses are not eye protective devices. appropriate must be worn instead of, or in conjunction with contact lenses. rgency eyewash stations and washing facilities available in work area. contaminated work clothing from street clothes. Launder before move this material from your shoes and clean personal protective
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUF Engineering Controls: Ventilation: Administrative Controls Respiratory Protection: Protective Clothing/Equ Safety Stations: Contaminated Equipment Comments:	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or local below OSHA PELs (see dispersion into the work : Seek profe Follow OS a MSHA/N to provide airborne co nonroutine an SCBA. atmospher ipment: Wear chem prolonged chemical s (29CFR 19 protection Make eme equipment Never eat, drink, or smo	tion. (Below 40 C / 100 F) RSONAL PROTECTION I exhaust ventilation systems to maintain airborne concentrations 2.). Local exhaust ventilation is preferred because it prevents contaminant area by controlling it at its source. Assional advise prior to respirator selection and use. HA respirator regulations (29 CFR 1910.134) and, if necessary, wear IOSH-approved respirator. select respirator based on its suitability adequate worker protection for given working conditions, level of ontamination, and presence of sufficient oxygen. For emergency or operation (cleaning spills, reactor vessels, or storage tanks), wear <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient</i> es. nically protective gloves, boots, aprons, and gauntlets to prevent or repeated skin contact. Wear protective eyeglasses or afety goggles, per OSHA eye-and face-protection regulations 10.133). Contact lenses are not eye protective devices. appropriate must be worn instead of, or in conjunction with contact lenses. rgency eyewash stations and washing facilities available in work area. contaminated work clothing from street clothes. Launder before move this material from your shoes and clean personal protective bek in work areas. Practice good personal hygiene after using this
Handling Precautions: Storage Requirements: Regulatory Requirement SECTION 8 EXPOSUF Engineering Controls: Ventilation: Administrative Controls Respiratory Protection: Protective Clothing/Equ Safety Stations: Contaminated Equipment Comments:	Store in a cool, dry loca ts: N/A RE CONTROLS / PEI Provide general or local below OSHA PELs (see dispersion into the work : Seek profe Follow OS a MSHA/N to provide airborne co nonroutine an SCBA. atmospher ipment: Wear chem prolonged chemical s (29CFR 19 protection Make eme equipment Never eat, drink, or smo	tion. (Below 40 C / 100 F) RSONAL PROTECTION I exhaust ventilation systems to maintain airborne concentrations 2.2). Local exhaust ventilation is preferred because it prevents contaminant area by controlling it at its source. Its soinal advise prior to respirator selection and use. HA respirator regulations (29 CFR 1910.134) and, if necessary, wear IOSH-approved respirator. select respirator based on its suitability adequate worker protection for given working conditions, level of ontamination, and presence of sufficient oxygen. For emergency or operation (cleaning spills, reactor vessels, or storage tanks), wear <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient</i> tes. nically protective gloves, boots, aprons, and gauntlets to prevent or repeated skin contact. Wear protective eyeglasses or afety goggles, per OSHA eye-and face-protection regulations 10.133). Contact lenses are not eye protective devices. appropriate must be worn instead of, or in conjunction with contact lenses. rgency eyewash stations and washing facilities available in work area. contaminated work clothing from street clothes. Launder before move this material from your shoes and clean personal protective

SECTION 9 PHYSIC						
Physical State:				Water Solubility:	Insoluble	
Appearance and Odo	r: Black, free f	lowing powder, slig	ght odor.	Other Solubilities:	N/A	
 Ddor Threshold:	N/A		-	Boiling Point:	N/A	
apor Pressure:	N/A			Freezing/Melting Poin	t: 120 C (Melting Point)	
/apor Density(Air=1)	: Heavier that	n air.		Viscosity:	N/A	
ormula Weight:	N/A			Refractive Index:	N/A	
Density:	N/A			Surface Tension:	N/A	
Specific Gravity:	(H ₂ O=1, at	t 4ºC): 1.1		%Volatile:	N/A	
bH:	N/A			Evaporation Rate:	N/A	
SECTION 10 STAB	ILITY AND	REACTIVITY				
STABILITY:		Stable product	t.			
POLYMERIZATION:		N/A				
CHEMICAL INCOMPA	ATIBILITIES:	N/A				
CONDITIONS TO AVO	DID:	N/A				
HAZARDOUS DECON	IPOSITION F	RODUCTS: N	lay include nitrogen and	carbon oxides.		
SECTION 11 TOXIC	OLOGICAL	INFORMATIO	N			
Eye Effects:	N/A		Toxicity D	ata: *		
-						
Skin Effects:	N/A			lation Effects:	N/A	
			Acute Oral	Effects:	N/A	
			Chronic Ef		N/A	
			Carcinoge	nicity:	N/A	
			Carcinoge Mutagenic	nicity: ity:	N/A N/A	
			Carcinoge	nicity: ity:	N/A	
*See NIOSH, RTECS SECTION 12 ECOL Ecotoxicity: Environmental Fate:		-	Carcinoge Mutagenic	nicity: ity:	N/A N/A	
SECTION 12 ECOL Ecotoxicity: Environmental Fate:	.OGICAL IN	FORMATION N/A	Carcinoge Mutagenic	nicity: ity:	N/A N/A	
SECTION 12 ECOL Ecotoxicity: Environmental Fate: Environmental Degra	OGICAL IN	FORMATION N/A N/A	Carcinoge Mutagenic	nicity: ity:	N/A N/A	
SECTION 12 ECOL Ecotoxicity: Environmental Fate: Environmental Degra Soil Absorption / Mol SECTION 13 DISP	OGICAL IN dation: pility: OSAL CON	FORMATION N/A N/A N/A N/A SIDERATIONS	Carcinoge Mutagenic Teratogen	nicity: ity: icity:	N/A N/A	
SECTION 12 ECOL Ecotoxicity: Environmental Fate: Environmental Degra Soil Absorption / Mol SECTION 13 DISP Disposal: Waste ma	OGICAL IN Idation: bility: OSAL CON Iterial may be	FORMATION N/A N/A N/A N/A SIDERATIONS incinerated under	Carcinoge Mutagenic Teratogen er conditions which mee	nicity: ity: icity:	N/A N/A	
SECTION 12 ECOL Ecotoxicity: Environmental Fate: Environmental Degra Soil Absorption / Mol SECTION 13 DISP Disposal: Waste ma all federal	OGICAL IN dation: bility: OSAL CON aterial may be , state and loo	FORMATION N/A N/A N/A N/A SIDERATIONS incinerated under cal environmenta	Carcinoge Mutagenic Teratogen er conditions which mee al regulations.	nicity: ity: icity:	N/A N/A	
SECTION 12 ECOL Ecotoxicity: Environmental Fate: Environmental Degra Soil Absorption / Mol SECTION 13 DISP Disposal: Waste ma	OGICAL IN dation: bility: OSAL CON aterial may be , state and loo Requirement	FORMATION N/A N/A N/A N/A SIDERATIONS incinerated under cal environmentations: N	Carcinoge Mutagenic Teratogen er conditions which mee	nicity: ity: icity:	N/A N/A	_
SECTION 12 ECOL Ecotoxicity: Environmental Fate: Environmental Degra Soil Absorption / Mol SECTION 13 DISP Disposal: Waste ma all federal Disposal Regulatory Container Cleaning a	OGICAL IN dation: bility: OSAL CON aterial may be , state and loo Requirement nd Disposal: NSPORT INI	FORMATION N/A N/A N/A SIDERATIONS incinerated under cal environmenta ts: N N FORMATION	Carcinoge Mutagenic Teratogen er conditions which mee al regulations. I/A I/A	nicity: ity: icity:	N/A N/A	
SECTION 12 ECOL Ecotoxicity: Environmental Fate: Environmental Degra Soil Absorption / Mol SECTION 13 DISP Disposal: Waste ma all federal Disposal Regulatory Container Cleaning a	OGICAL IN dation: bility: OSAL CON aterial may be , state and loo Requirement nd Disposal: NSPORT INI	FORMATION N/A N/A N/A SIDERATIONS incinerated under cal environmenta ts: N N FORMATION	Carcinoge Mutagenic Teratogen er conditions which mee al regulations.	nicity: ity: icity:	N/A N/A	
SECTION 12 ECOL Ecotoxicity: Environmental Fate: Environmental Degra Soil Absorption / Mol SECTION 13 DISP Disposal: Waste ma all federal Disposal Regulatory Container Cleaning a SECTION 14 TRAM DOT Transportation I Shipping Name:	OGICAL IN dation: oility: OSAL CON aterial may be , state and loo Requirement nd Disposal: NSPORT INI Data (49 CFF N/A	FORMATION N/A N/A N/A SIDERATIONS incinerated under cal environmenta is: N N FORMATION R 172.101): N	Carcinoge Mutagenic Teratogeni er conditions which meet al regulations. I/A I/A lot specifically listed vackaging Authorizatio	nicity: ity: icity:	N/A N/A N/A	
SECTION 12 ECOL Ecotoxicity: Environmental Fate: Environmental Degra Soil Absorption / Mol SECTION 13 DISP Disposal: Waste ma all federal Disposal Regulatory Container Cleaning a SECTION 14 TRAN DOT Transportation I Shipping Name: Shipping Symbol:	OGICAL IN dation: bility: OSAL CON aterial may be , state and loo Requirement nd Disposal: NSPORT INI Data (49 CFF N/A N/A	FORMATION N/A N/A N/A SIDERATIONS incinerated under cal environmenta is: N N FORMATION R 172.101): N P a	Carcinoge Mutagenic Teratogeni er conditions which meet al regulations. I/A I/A lot specifically listed Packaging Authorizatio) Exceptions:	nicity: ity: icity: t ns Quantity L N/A a) Passeng	N/A N/A N/A	
SECTION 12 ECOL Ecotoxicity: Environmental Fate: Environmental Degra Soil Absorption / Mol SECTION 13 DISP Disposal: Waste ma all federal Disposal Regulatory Container Cleaning a SECTION 14 TRAN DOT Transportation I Shipping Name: Shipping Symbol: Hazard Class:	OGICAL IN dation: bility: OSAL CON aterial may be , state and loo Requirement nd Disposal: NSPORT INI Data (49 CFF N/A N/A N/A	FORMATION N/A N/A N/A SIDERATIONS incinerated under cal environmenta ts: N FORMATION R 172.101): N P a b	Carcinoge Mutagenic Teratogeni er conditions which mee al regulations. I/A I/A lot specifically listed Packaging Authorizatio) Exceptions:)Non-bulk Packaging:	nicity: ity: icity: ns Quantity L N/A a) Passeng N/A Railcar:	N/A N/A N/A	N/A
SECTION 12 ECOL Ecotoxicity: Environmental Fate: Environmental Degra Soil Absorption / Mol SECTION 13 DISP Disposal: Waste ma all federal Disposal Regulatory Container Cleaning a SECTION 14 TRAN DOT Transportation I Shipping Name: Shipping Symbol: Hazard Class: D No.:	OGICAL IN dation: bility: OSAL CON aterial may be , state and loo Requirement nd Disposal: NSPORT INI Data (49 CFF N/A N/A N/A N/A N/A	FORMATION N/A N/A N/A SIDERATIONS incinerated under cal environmenta ts: N FORMATION R 172.101): N P a b	Carcinoge Mutagenic Teratogeni er conditions which meet al regulations. I/A I/A lot specifically listed Packaging Authorizatio) Exceptions:	nicity: ity: icity: N/A a) Passeng N/A Railcar: N/A	N/A N/A N/A	N/A
SECTION 12 ECOL Ecotoxicity: Environmental Fate: Environmental Degra Soil Absorption / Mol SECTION 13 DISP Disposal: Waste ma all federal Disposal Regulatory Container Cleaning a SECTION 14 TRAN DOT Transportation I Shipping Name: Shipping Symbol: Hazard Class: D No.: Packing Group:	OGICAL IN dation: bility: OSAL CON aterial may be , state and loo Requirement nd Disposal: NSPORT INI Data (49 CFF N/A N/A N/A N/A N/A N/A N/A N/A	FORMATION N/A N/A N/A SIDERATIONS incinerated under cal environmenta ts: N FORMATION R 172.101): N P a b	Carcinoge Mutagenic Teratogeni er conditions which mee al regulations. I/A I/A lot specifically listed Packaging Authorizatio) Exceptions:)Non-bulk Packaging:	nicity: ity: icity: N/A a) Passeng N/A Railcar: N/A Vessel Sto	N/A N/A N/A	
SECTION 12 ECOL Ecotoxicity: Environmental Fate: Environmental Degra Soil Absorption / Mol SECTION 13 DISP Disposal: Waste ma all federal Disposal Regulatory Container Cleaning a SECTION 14 TRAM DOT Transportation I	OGICAL IN dation: bility: OSAL CON aterial may be , state and loo Requirement nd Disposal: NSPORT INI Data (49 CFF N/A N/A N/A N/A N/A	FORMATION N/A N/A N/A SIDERATIONS incinerated under cal environmenta ts: N FORMATION R 172.101): N P a b	Carcinoge Mutagenic Teratogeni er conditions which mee al regulations. I/A I/A lot specifically listed Packaging Authorizatio) Exceptions:)Non-bulk Packaging:	nicity: ity: icity: N/A a) Passeng N/A Railcar: N/A	N/A N/A N/A	N/A N/A

EPA Regulations: RCRA Hazardous Waste No		FION	
CRA Hazardouis Waste Ni			
	,	R 261.33)	Not Listed
CRA Hazardous Waste Cl		(40 CFR 261):	Not classified
ERCLA Hazardous Substance		I/unlisted specific per RCR	A, sec. 3001;
CWA sec.311 (b)			
WA, Sec. 307(a),CAA,Sec			
ERCLA Reportable Quant	ity(RQ):	Not listed	
ARA 311/312 Codes:		N/A	
ARA Toxic Chemical (40		Not listed	
ARA EHS (Extremely Haz	ardous Substance)	(40 CFR 355):	Not listed, Threshold Planning Quantity (TPQ)
SHA Regulations:			
Air Contaminant (29 CFR			Particulates not otherwise regulated.
tate Regulations: Ch	neck your states reg	ulations that may speci	fically list copy machine toner.
ECTION 16 OTHER IN	FORMATION		
epared By:	N/A		
evision Notes:	N/A		
dditional Hazard Rating S	ystem: N/A		
-	-		
			OURCES WHICH WE BELIEVE
ARE RELIABLE.	HOWEVER, THE INF	ORMATION IS PROVIDE	D WITHOUT ANY WARRANTY
EXPRESS OR IN	IPLIED, REGARDING	IT'S CORRECTNESS.	
THE CONDITION	NS OR METHODS OF	HANDLING, STORAGE, U	JSE AND DISPOSAL OF THE
PRODUCT ARE	BEYOND OUR CONT	ROL AND MAY BE BEYO	ND OUR KNOWLEDGE.
FOR THIS AND	OTHER REASONS, W	E DO NOT ASSUME RES	PONSIBILITY AND EXPRESSLY
DISCLAIM LIABI	LITY FOR LOSS, DAM	AGE OR EXPENSE ARIS	SING OUT OF OR IN ANY WAY
CONNECTED W	ITH THE HANDLING,	STORAGE, USE OR DISF	POSAL OF THE PRODUCT.