Document Number: MNAB005	Revision:08	Page 1 of 4
IDENTITY (As Used on Label and List)	Note : Blank spaces are not permitted if any item is	
Alkaline batteries	information is available, the space must be marked	l to indicate that.
Section 1- Identification		
Manufacturer's Name	Emergency Telephone Number	
GPI International Ltd.		
Address (Number, Street, City State, and	Telephone Number for information	
ZIP Code)	852-2484-3333	
8/F GP Building, 30 Kwai Wing Road,		
	Date of prepared and revision	
Kwai Chung, N.T. H.K.	Jan 2, 2014	
	Signature of Prepare (optional)	

Section 2 – Hazards Identification

Classification

N.A.

Section 3 – Composition/Information On Ingredients

Hazardous Components:		
Description:	Approx	imate % of total weight
Lead (Pb)	: <25	ppm
Mercury (Hg)	: <1	ppm
Cadmium (Cd)	: <3	ppm
Hexavalent Chromium (Cr ⁶⁺)	: <3	ppm
Polybrominated Biphenyls (PBBs)	: N/A	
Polybrominated Diphenyl Ethers (PBDEs)	: N/A	A
MnO2	: 29-3	0 Wt%
Zn	10	Wt%

Section 4 – First Aid Measures

First Aid Procedures

If electrolyte leakage occurs and makes contact with skin, wash with plenty of water immediately.

If electrolyte comes into contact with eyes, wash with copious amounts of water for fifteen (15) minutes, and contact a physician.

If electrolyte vapors are inhaled, provide fresh air and seek medical attention if respiratory irritation develops. Ventilate the contaminated area.

Document Number: MNAB005		Revision:08	Revision:08		
Section 5 – Fire-Figh	nting Measures	6			
Flash Point (Method Used)	Ignition Temp.	Flammable Limits	LEL	UEL	
N.A.	N.A.	N.A.	N.A.	N./	A.
Extinguishing Media	L				
Carbon Dioxide, Dry	Chemical or Foam e	xtinguishers			
Special Fire Fighting Proced	ures				
N.A.					
Unusual Fire and Explosion	Hazards				
Do not dispose of batt	tery in fire - may exp	lode.			
Do not short-circuit b	attery - may cause bu	ırns.			
Section 6 – Accident	al Release Mea	asures			
Steps to Be Taken in Case M	aterial is Released or	Spilled			
Batteries that are leal	kage should be hand	led with rubber gloves.			
Avoid direct contact	with electrolyte.				
Wear protective cloth	hing and a positive p	ressure Self-Contained B	reathing Apparatus (S	CBA).	
Section 7 – Handling	and Storage				
Safe handling and storage adv	vice				
		carefully to avoid short ci			
	•	low metal objects to be m	ixed with stored batter	ries.	
Never disassemble	•				
Do not breathe cell	vapors or touch inte	rnal material with bare ha	unds.		
The cells and batter	ries shall not be store	ed in high temperature, the	e maximum temperatu	re allowed is 60	for a shore

period during the shipment, Otherwise the cells maybe leakage and can result in shortened service life..

Document Number: MNAB005			Revision:08 Page 3 of 4			
Section 8	B– Exposure Cor	ntrols /	Person P	rotection		
		LTEP		STEP		
N.A.			N.A.			
Respiratory I	Protection (Specify Ty	pe)				
	Ν	N.A.				
Ventilation	Local Exhausts			Special		
		N.A.			N.A.	
	Mechanical (Gener	al)		Other		
		N.A.			N.A.	
Protective G				Eye Protection		
	N.A.			-	N.A.	
Other Protec	tive Clothing or Equip	ment				
Other Flottee	N.A.	ment				
Work / Hygi	enic Practices					
work / rrygr	N.A.					
<u> </u>			-			
	- Physical / Che	mical				
Boiling Point	N.A.		specific Gra	vity ($H_2O=1$)	N.A.	
Vapor Pressu	-		Melting Poir	nt		
N.A. Vapor Dopoity (AIP-1) Evaporatio		Evaporation	Rate (Butyl Acetate)	N.A.		
Vapor Density (AIR=1) Evaporation N.A.		Rate (Buty) //cetate)	N.A.			
Solubility in						
Appearance a	N.A. and Odor					
				ular Shape, odorless		
	0 – Stability and	React				
Stability	Unstable		Conditions	to Avoid		
	Stable					
Incompatibili	ty (Materials to Avoid					
Ĩ	•	, 				
Hazardous D	ecomposition or Bypro	oducts				
Hazardous Polymerizati on	May Occur		Conditions	to Avoid		
	Will Not Occur	X				

Member Gold Peak Group

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

Document Number: MNAB005		Revisio	Page 4 of 4	
Section 11 – T	oxicological Informa	tion		
Route(s) of	Inhalation?	Skin?	Ingestion?	
Entry	Ν	I.A.	N.A.	N.A.
Health Haza	ard (Acute and Chronic) / Tox	kiclogical information	n	
In case of ele	ctrolyte leakage, skin will be	itchy when contamir	ated with electrolyte.	
In contact wi	th electrolyte can cause sever	e irritation and chem	ical burns.	
Inhalation of	electrolyte vapors may cause	irritation of the uppe	er respiratory tract and lungs.	
Section 12 - F	cological Information	า		

Section 12 – Ecological Information

N.A.

Section 13 – Disposal Considerations

Dispose of batteries according to government regulations.

Section 14 – Transportation Information

In general, all batteries in all forms of transportation (ground, air, or ocean) must be packaged in a safe and responsible manner. Regulatory concerns from all agencies for safe packaging require that batteries be packaged in a manner that prevents short circuits and be contained in "strong outer packaging" that prevents spillage of contents. All original packaging for GP alkaline batteries has been designed to be compliant with these regulatory concerns.

Alkaline batteries (sometimes referred to as "Dry cell" batteries) are not listed as dangerous goods under the ADR European Agreement Concerning the International Carriage of Dangerous Goods by Road, the IMDG International Maritime Dangerous Goods Code, UN Dangerous Good Regulations, IATA Dangerous Goods Regulations 55th edition, ICAO Technical Instructions and the U.S. hazardous materials regulations (49 CFR). These batteries are not subject to the dangerous goods regulations provided they meet the requirements contained in the following special provisions

. Regulatory Body	Special Provisions
ADR	Not regulated
IMDG	Not regulated
UN	Not regulated
US DOT	49 CFR 172.102 Provision 130
IATA	A123
ICAO	Not regulated

All GP alkaline batteries are packed in such a way to prevent short circuits or the generation dangerous quantities of heat and meet the special provisions listed above. In addition, the IATA Dangerous Goods Regulations and ICAO Technical Instructions require the words "not restricted" and the Special Provision number A123 be provided on the air waybill, when an air waybill is issued.

Section 15 – Regulatory Information

Special requirement be according to the local regulatories.

Section 16 – Other Information

The data in this Material Safety Data Sheet relates only to the specific material designated herein.

Section 17 – Measures for fire extinction

In case of fire, it is permissible to use any class of extinguishing medium on these batteries or their packing material. Cool exterior of batteries if exposed to fire to prevent rupture.

Fire fighters should wear self-contained breathing apparatus.



Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.