# **Material Safety Data Sheet**

### 1. Product and Company Information

Product: Thermal Transfer Ribbon

Manufacturer's Name: Clover Technologies Group

Telephone: 815-431-8100

Address: 4200 Columbus St., Ottawa, IL 61350

### 2. Hazardous Ingredients/ Composition

Risks for human health: This product is a relatively innocuous substance and is

not expected to cause harm. Mechanical irritation of

the eyes, nose, and throat may occur in slitting.

Environmental Risk: No data available.

Chemical Characteristics: ET Carrier

Carbon Black

Wax Resin

# 3. Physical/Chemical Characteristics

Form Ink Coated Film

Color Black

Odor Little or no odor

Value/Range

Change in physical N/A

Melting point/melting range Ink: 70 +/- 5 degrees C. Film 256-265 degrees C.

Boiling point/boiling range N/A

Flash points > 150 degrees C.

Ignition temperature

Danger of explosion

Explosion limit

N/A

Lower limit

Vapor Pressure

N/A

N/A

N/A

N/A

Density 5.8g/m2
Solubility N/A
Viscosity N/A

## 4. Firefighting Measures

Suitable extinguishing media: Foam, dry-chemical, carbon dioxide and water.

Particular risk arising from the

products/products of

combustion/generated gases: Carbon monoxide, carbon dioxide.

Protective Equipment: Use of self-contained breathing apparatus in close

proximity of fire.

Further Information: Film may pick up surface static charges during its

movement over metal or other rollers. They may cause flash fire or explosion if discharged into dust or solvent laden air.

## 5. Stability and Reactivity

Stability: Stable

Hazardous decomposition

Products: Terephthalic acid. CO and aldehyde above 300

degrees C.

#### 6. First-Aid Measures

Skin: Wash effected areas with soap and water. Eye: Flush copiously with water for 15 minutes.

Ingestion: Obtain immediate medical attention.

## 7. Handling and Storage

Storage:

Handling: Wash hands thoroughly after handling and before

eating or smoking. Eye protection is recommended

if ribbon is being slit or cut. Use adequate

ventilation if nuisance particles are being generated. Store in air atmosphere, sheltered from light and at

temperature below 40 degrees C. Avoid proximity of flame and heat sources. Store 24 hours in room

temperature before slitting.

# 8. Exposure Controls/Personal Protection

Technical protection measures: This product will slowly photo degrade with UV

light exposure, shelter from light.

Personal protection equipment: Goggles for eye protection and particle mask for

nose and throat protection during slitting process.

## 9. Ecological Information

No data available

## 10. Regulatory Information

Nothing special

#### ADDITIONAL INFORMATION

No liability is accepted for any injury, loss damage, or cost arising directly or indirectly from the use of any information contained within this MSDS, since the customer's treatment of the product is beyond our control. The data given above is based upon current knowledge and experience. This safety data sheet is intended to describe product in terms of its safety requirement. It does not guarantee the properties of the product described.