

5700/ 5710/ 5730/

401 Professional Drive Gaithersburg, MD 20879 Tel 301.590.9781

Page I of 4

MATERIAL SAFETY DATA SHEET

name: Liquid Paper Coi Casno: Na	RRECTION F.	LUID (COL	ORS, LPC Effective		12/10/98	Rev:	4	
				_				
A IDENTIFICATION								
Composition*	1 -	% Formula:		Mixture				
Methylcyclohexane (108-87-2)		Molecular	Weight: 1	ĪA.				
Titanium Dioxide (13463-67-7)	}	Synonyme	B:		•			
Mineral Spirits (64742-48-9)							ŀ	
Resin, Dispersant, Colorant(s)	1	1	(Colored	Correction	i Fluid	ļ	
Mustard Oil (57-06-7)							ļ	
Masking Fragrance	İ	1					ļ	
B. — PHYSICAL DATA		fl						
Boiling Point	N	letting Point			Freezing	Point		
~212 °F ~100 °C		F NA	°c	NA		<u>NA</u>	°c	
Specific Gravity (H ₂ O=1)	Vapor Density (air=1)			Vapor	Pressure @	100	°F	
~1.3		3.4			83	mm H	g	
Evaporation					Autoignition 1	emperatur		
(Butyl Acctate =1)	}	^F)		°F	. ———	_ °c		
>1		NA			N.	A		
l l		Solubility in Water		ml.i		NA		
~40 Negli		Vegligible				NA		
Appearance/Odor Colored fluid wi	th a pungent so	olvent odor						
Flash Point and Test Method(s) 25°F (Closed Cu	p) for product							
Flammable Limits in Air					_		% '	
(% by volume)	Lower	1.2	%	Upr	er <u>6.</u>		70	
C REACTIVITY								
Stability Stable	unstable	Polyn	nerization		nay occur	Will Will	not occur	
Conditions to Avoid				Condition	ns to Avoid			
Product is flammable. Avoid conta	ct with open fl	ame NA						
or other ignition sources.		ł						
incompatible Materia	\$		Hazan	dous Dec	omposition Pr	oducts		
Strong oxidizers			Thermal degradation may produce oxides of carbon					
			and nitrogen and various hydrocarbons.					
1								
* IF MULTIPLE INGREDIENTS, IN	CLUDE CAS	NUMBERS I	OR EAC	4	NA=NO	TAVAIL	ABLE	
Footnotes								
Physical data, except Specific Grav	ity and % Vola	atiles, refers t	o Methylc	yclohex	ane.			
	<u> </u>	· · · · · · · · · · · · · · · · · · ·						
					Gi	MEL#	1391	

Page 2 of 4

D. -- HEALTH HAZARD DATA

Occupational Exposure Limits PEL's, TLV's, etc.)

8-Hour TWA's: Methylcyclohexane - 400 ppm (ACGIH)

Titanium Dioxide - 10 mg/cu m (OSHA/ACGIH)

Mineral Spirits - 300 ppm (Manufacturer recommendation)

These levels are not anticipated under foreseeable use conditions.

Warning Signals

NA

Routes/Effects of Exposure

No adverse effects anticipated from normal use. If vapors are deliberately concentrated and 1. Inhalation

inhaled (abuse), the following symptoms may occur: respiratory irritation, dizziness,

drowsiness, headache, nausea, unconsciousness, convulsions, cardiac sensitization, coma and

death. (Mustard oil is added to the product as an abuse deterrent.)

2. Ingestion No adverse effects anticipated from normal use. Depending on amount ingested, most of the

symptoms described above may occur. Estimated LD₅₀ in rats is greater than 5 ml/kg or between 1 pint and 1 quart in humans (ref. Gosselin, Smith and Hodge, Clinical Toxicology of

Commercial Products, 5th Ed., 1984). Aspiration may result in chemical pneumonitis.

3. Skin a. Contact

No adverse effects anticipated from normal use. Irritation may occur if contact is

prolonged/repeated.

b. Absorption

No adverse effects anticipated from normal use. Solvent can be absorbed through skin

(prolonged contact), but not likely in acutely toxic amounts.

4. Eye Contact If splashed into eye, irritation can occur.

5. Other

NA

E. — ENVIRONMENTAL IMPACT

1. Applicable Regulations

2. DOT Hazard Class -

ORM-D

3. DOT Shipping Name -

Consumer Commodity

Environmental Effects

All components of this product comply with the U.S. Toxic Substances Control Act (TSCA).

Page 3 of 4

F. EXPOSURE CONTROL METHODS
Engineering Controls
None under normal use conditions.
Eye Protection
None under normal use conditions.
Skin Protection
None under normal use conditions.
Respiratory Protection
None under normal use conditions.
140mp mon and an animate and animate a
Other
Product is non-hazardous when used as directed in an office/room with normal air circulation.
1100mat in Hall Washington Millian and Mil
G WORK PRACTICES
Handling and Storage
Product is flammable. No unusual handling or storage when used as directed; when stored in large quantities
(as in warehouse), it should be in a well-ventilated, cool area, away from ignition sources.
Normal Clean Up
Pick up spills with towels, tissues, etc.
Waste Disposal Methods
Dispose in accordance with applicable federal, state and local laws.
ł

Page 4 of 4

H. — EMERGENCY PROCEDURES

Steps to be taken if material is released to the environment or spilled in the work area Not applicable

Fire and Explosion Hazard

Product is flammable. May produce hazardous decomposition products.

Extinguishing Media

Dry chemical, foam, carbon

dioxide.

Firefighting Procedures

In fires involving large quantities of product, use self-contained breathing apparatus. Cool fire-exposed containers with water fog/spray.

I. — FIRST AID AND MEDICAL EMERGENCY PROCEDURES

Eyes

Flush with plenty of water. If irritation persists, obtain medical attention.

Skin

Wash with soap and water.

Inhalation

No adverse effects anticipated from normal use. In an abuse situation, remove from source of exposure. Treat symptomatically. Oxygen may be administered. Seek medical attention immediately and refer to "Notes to Physician" below.

Ingestion

Consult physician.

Notes to Physician

Contains methylcyclohexane and mineral spirits which, if aspirated, may cause chemical pneumonitis. The inhalation of concentrated vapors may produce cardiac sensitization, contraindicating the use of sympathomimetic agents.

Replaces #1197, Sections A, D revised.

The information contained in the Material Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.

GMEL#

1391