

NAME:

PAP 74701

401 Professional Drive Gaithersburg, MD 20879 Tel 301.590.9781

Page 1 of 4

GMEL#

1394

# MATERIAL SAFETY DATA SHEET

NAME: LIQUID PAPER PEN AN CAS NO: NA	ND INK CO		. ·	_	
	<u>-</u>	Effect	ive Date: 12/10/98	Rev: 3	
A. — IDENTIFICATION					
Composition*	<u>%</u>	Formula:	Mixture	. <u>.                                   </u>	
Titanium Dioxide (13463-67-7)		Molecular Weight:	NA		
Solvent Naphtha (64742-89-8)		Synonyms:			
Mineral Spirits (64742-48-9)					
Resin, Dispersant, Colorant(s) Mustard Oil (57-06-7)	1		Correction Fluid		
Masking Fragrance	 				
B. — PHYSICAL DATA					
Bolling Point 209-230 °F 98-110 °C		Point	Freezing		
	NA °F	NA °C	NA °F	NA °c	;
Specific Gravity (H <sub>2</sub> O=1)		sity (alr=1)	Vapor Pressure @		F
1.29		.3	124mm Hg		
Evaporation ( Butyl Acetate =1) (b	Saturation in Air (by volume@ °F) NA		Autoignition T	Autoignition Temperature  °F  °C	
3.6			NA NA		
% Volatiles	Solubility in Water				
~40	Negligible		ρН	NA	
Appearance/Odor White fluid with a pur	agent solvent	odor	<del></del>	<del></del>	
Flash Point and Test Method(s) 25.5°F (Closed Cup) f	<del></del>				
Flammable Limits in Air					
(% by volume)	Lower1	<u></u> %	Upper 8	%	
C REACTIVITY					
Stability Stable	unstable	Polymerization	may occur	will not occ	ur
Conditions to Avoid		37.	Conditions to Avoid		
Product is flammable. Avoid contact with or other ignition sources.	n open Hame	NA			
Incompatible Materials			dous Decomposition Pro		
Strong oxidizers			tion may produce ox		
	}	and muogen and	various hydrocarbor	15.	
* 15 MM TIDLE INCORPORATE MANAGEMENT					
* IF MULTIPLE INGREDIENTS, INCLUE Footnotes	DE CAS NUM	BERS FOR EAC	H NA=NO1	AVAILABLE	
Physical data, except Specific Gravity and	1 % Volatiles	refers to Solvent	Nanhtha a complex	mixture of	
predominantly C7 and C8 hydrocarbons.		TOTALO TO DOLACTI	respirately a complex	HIALING OL	

Page 2 of 4

## D. — HEALTH HAZARD DATA

Occupational Exposure Limits PEL's, TLY's, etc.)

8-Hour TWA's: Rubber Solvent (Naphtha) - 400 ppm (ACGIH) recommended.

Titanium Dioxide - 10 mg/cu m (OSHA/ACGIH)

Mineral Spirits - 300 ppm (Manufacturer recommendation)

These levels are not anticipated under foreseeable use conditions.

Warning Signals

NA

#### Routes/Effects of Exposure

1. Inhalation No adverse effects anticipated from normal use. If vapors are deliberately concentrated and

inhaled (abuse), the following symptoms may occur: respiratory irritation, dizziness,

drowsiness, headache, nausea, unconsciousness, convulsions, cardiac sensitization, coma and

death. (Mustard oil is added to the product as an abuse deterrent.)

2. Ingestion No adverse effects anticipated from normal use. Depending on amount ingested, most of the

symptoms described above may occur. Estimated LD<sub>50</sub> in rats is greater than 5 ml/kg or

between 1 pint and 1 quart in humans (ref. Gosselin, Smith and Hodge, Clinical Toxicology of

Commercial Products, 5th Ed., 1984). Aspiration may result in chemical pneumonitis.

3. Skin a. Contact

No adverse effects anticipated from normal use. Irritation may occur if contact is

prolonged/repeated.

b. Absorption

No adverse effects anticipated from normal use. Solvent can be absorbed through skin

(prolonged contact), but not likely in acutely toxic amounts.

4. Eye Contact If splashed into eye, irritation can occur.

5. Other NA

#### E. — ENVIRONMENTAL IMPACT

### 1. Applicable Regulations

2. DOT Hazard Class - ORM-D

3. DOT Shipping Name - Consumer Commodity

#### Environmental Effects

All components of this product comply with the U.S. Toxic Substances Control Act (TSCA).

Page 3 of 4

F EXPOSURE CONTROL METHODS
Engineering Controls
None under normal use conditions.
Eye Protection
None under normal use conditions.
Skin Protection  None under normal use conditions.
None under normal use conditions.
Respiratory Protection
None under normal use conditions.
Other
Product is non-hazardous when used as directed in an office/room with normal air circulation.
G WORK PRACTICES
Handling and Storage
Product is flammable. No unusual handling or storage when used as directed; when stored in large quantities
(as in warehouse), it should be in a well-ventilated, cool area, away from ignition sources.
(as in wateriously, it should be in a west verification, every more) from the same of the
$\cdot$
Normal Clean Up
Pick up spills with towels, tissues, etc.
Waste Disposal Methods
Dispose in accordance with applicable federal, state and local laws.

Page 4 of 4

#### H. — FMERGENCY PROCEDURES

Steps to be taken if material is released to the environment or spilled in the work area Not applicable

Fire and Explosion Hazard

Product is flammable. May produce hazardous decomposition products.

Extinguishing Media

Dry chemical, foam, carbon

dioxide.

Firefighting Procedures

In fires involving large quantities of product, use self-contained breathing apparatus. Cool fire-exposed containers with water fog/spray.

## - FIRST AID AND MEDICAL EMERGENCY PROCEDURES

Eves

Flush with plenty of water. If irritation persists, obtain medical attention.

Skin

Wash with soap and water.

Inhalation

No adverse effects anticipated from normal use. In an abuse situation, remove from source of exposure. Treat symptomatically. Oxygen may be administered. Seek medical attention immediately and refer to "Notes to Physician" below.

Ingestion

Consult physician.

Notes to Physician

Contains solvent naphtha and mineral spirits which, if aspirated, may cause chemical pneumonitis. The inhalation of concentrated vapors may produce cardiac sensitization, contraindicating the use of sympathomimetic agents.

Replaces #1196, Sections A, D revised.

The information contained in the Material Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.

MSDS-4 (8/95)

GMEL#

1394