

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Type: Ribbon Ink
Supplier: Pyramid Time Systems
Address: 45 Gracey Ave.
Meriden, CT 06451
Phone: 203-238-0550
Fax: 203-634-1696

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS#	Content (%)
C.I.Solvent black 7	8005-02-5	10 - 15 %
Carbon black	1333-86-4	4 - 5 %
Fatty acid	112-80-1	35 - 40 %
Fatty acid ester	68956-08-1	1 - 5%
Mineral oil	64742-52-5	30 - 35 %
Surface active agent	8007-43-0	10 - 15 %

3. HAZARDS IDENTIFICATION

Inhalation: N.A.
Eye Contact: May cause an irritation.
Skin Contact: Prolonged or repeated skin contact can cause irritation.
Ingestion: May cause diarrhea if significant quantities are ingested.

4. FIRST AID MEASURE

ThresholdLimit Value 3 mg/M3 (oil mist)
Effect Of Overexposure Possible transient irritation to eyes; essentially non-irritating to skin. Mist generated by heat or violent agitation may irritate eyes, nose and throat
Emergency and First Aid Procedures Flush eyes with water for at least 15 minutes, get medical attention. For prolonged skin contact, wash the affected skin areas thoroughly with soap and water. Remove and launder contaminated clothing before reuse. If swallowed, DO NOT induce vomiting. Get medical attention. Remove to fresh air.

5. FIRE FIGHTING MEASURES

Flash Point: DEG C 200
Flammable Limits: N.A.
Extinguish Media: Use water, foam, CO2, or dry chemical to extinguish fires
Special Fire Fighting Procedures: Treat as oil fire. Water spray may cool closed containers to prevent pressure buildup and possible autoignition on exposure to extreme heat.
Unusual fire and explosion hazards: Keep containers tightly closed. Isolate from heat, sparks and flame.

6. ACCIDENTAL RELEASE MEASURES

Steps to be taken if spilled: This is not a regulated product. Spills should be contained, absorbed, and placed in

