according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - CASHMERE WOODS®

Version 2.0 Print Date 05/22/2018

Revision Date 09/15/2017 SDS Number 350000017052

1. PRODUCT AND COMPANY IDENTIFICATION

Product information

Product name : GLADE® AUTOMATIC SPRAY REFILL - CASHMERE

WOODS®

Recommended use : Air Freshener

Restrictions on use : Use only as directed on label

Manufacturer, importer,

supplier

: S.C. Johnson & Son, Inc.

1525 Howe Street

Racine WI 53403-2236

Telephone : +1-800-558-5252

Emergency telephone

number

: 24 Hour Medical Emergency Phone: (866)231-5406 24 Hour International Emergency Phone: (703)527-3887

24 Hour Transport Emergency Phone: (800)424-9300

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Globally Harmonized System (GHS) Classification

Hazard classification	Hazard category	Hazards identification
Aerosol	Category 1	Extremely flammable aerosol.
Eye irritation	Category 2B	Causes eye irritation.
Skin sensitisation	Category 1	May cause an allergic skin reaction.
Specific target organ toxicity - single exposure	Category 3	May cause drowsiness or dizziness.
Gases under pressure	Liquefied gas	Contains gas under pressure; may explode if heated.

Labelling

Hazard symbols

Flame
Gas cylinder
Exclamation mark

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - CASHMERE WOODS®

Version 2.0 Print Date 05/22/2018

Revision Date 09/15/2017 SDS Number 350000017052

Signal word

Danger

Hazard statements

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Call a POISON CENTER/doctor if you feel unwell.

Specific treatment (see supplemental first aid instructions on this label).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/ attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Protect from sunlight. Store in a well-ventilated place.

Dispose of contents/ container to an approved incineration plant.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Wear protective gloves.

Avoid breathing spray.

Wash hands thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace.

Other hazards : Intentional misuse by deliberately concentrating and inhaling

contents can be harmful or fatal.

Excessive exposure to spray mist, fog or vapour may cause

respiratory irritation.

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - CASHMERE WOODS®

Version 2.0 Print Date 05/22/2018

Revision Date 09/15/2017 SDS Number 350000017052

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS-No.	Weight percent
Acetone	67-64-1	30.00 - 60.00
Isobutane	75-28-5	30.00 - 60.00
Propane	74-98-6	5.00 - 10.00
Fragrance - Trade Secret	Mixture	0.10 - 1.00

The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

For additional information on product ingredients, see www.whatsinsidescjohnson.com.

4. FIRST AID MEASURES

Description of first aid measures

Eye contact : IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.

Skin contact : Wash off with plenty of water. If skin irritation or rash occurs:

Get medical advice/ attention.

Inhalation : IF INHALED: Remove person to fresh air and keep comfortable

for breathing. Call a POISON CENTER or doctor/physician if

you feel unwell.

Ingestion : No special requirements

Most important symptoms and effects, both acute and delayed

Eyes : May irritate eyes.

Skin effect : May cause allergic skin reaction.

No adverse effects expected when used as directed.

Inhalation : Intentional misuse by deliberately concentrating and inhaling

contents can be harmful or fatal.

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - CASHMERE WOODS®

Version 2.0 Print Date 05/22/2018

Revision Date 09/15/2017 SDS Number 350000017052

May cause allergic respiratory reaction.

Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Ingestion : May cause irritation to mouth, throat and stomach.

May cause abdominal discomfort.

No adverse effects expected when used as directed.

Indication of any immediate medical attention and special treatment needed

See Description of first aid measures unless otherwise stated.

5. FIREFIGHTING MEASURES

Suitable extinguishing

media

: Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Specific hazards during

firefighting

: Aerosol Product - Containers may rocket or explode in heat of

fire.

Further information : Fight fire from maximum distance or protected area. Cool and

use caution when approaching or handling fire-exposed containers. Wear full protective clothing and positive pressure self-contained breathing apparatus. In case of fire and/or

explosion do not breathe fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Remove all sources of ignition.

Wear personal protective equipment. Wash thoroughly after handling.

Environmental precautions

: Outside of normal use, avoid release to the environment.

Methods and materials for containment and

cleaning up

: If damage occurs to aerosol can:

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local /

national regulations (see section 13).

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - CASHMERE WOODS®

Version 2.0 Print Date 05/22/2018

Revision Date 09/15/2017 SDS Number 350000017052

Use only non-sparking equipment.

Dike large spills.

Clean residue from spill site.

7. HANDLING AND STORAGE

Handling

Precautions for safe

handling

: Avoid contact with skin, eyes and clothing. For personal protection see section 8.

Note: Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. For more

information visit www.inhalant.org.

Use only as directed.

KEEP OUT OF REACH OF CHILDREN AND PETS.

Pressurized container.

Do not pierce or burn, even after use.

Contaminated work clothing should not be allowed out of the

workplace.

Avoid breathing vapours, mist or gas. Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Do not spray on an open flame or other ignition source.

Storage

Requirements for storage areas and containers

Protect from sunlight. Do not expose to temperatures

exceeding 50 °C/ 122 °F.

Keep in a dry, cool and well-ventilated place.

Store locked up. Protect from sunlight.

Store in a well-ventilated place. Keep container tightly closed.

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - CASHMERE WOODS®

Version 2.0 Print Date 05/22/2018

Revision Date 09/15/2017 SDS Number 350000017052

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

Components	CAS-No.	mg/m3	ppm	Non- standard units	Basis
Acetone	67-64-1	2,400 mg/m3	1,000 ppm	-	OSHA TWA
Acetone	67-64-1	-	500 ppm	-	ACGIH STEL
Acetone	67-64-1	-	250 ppm	-	ACGIH TWA
Isobutane	75-28-5	-	1,000 ppm	-	ACGIH STEL
Propane	74-98-6	1,800 mg/m3	1,000 ppm	-	OSHA TWA
Propane	74-98-6	-	-	-	ACGIH TWA

Personal protective equipment

Respiratory protection : No special requirements.

Hand protection : Wear suitable gloves.

Eye protection : No special requirements.

Skin and body protection : No special requirements.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form : aerosol

compressed liquefied gas

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - CASHMERE WOODS®

Version 2.0 Print Date 05/22/2018

Revision Date 09/15/2017 SDS Number 350000017052

Color : colourless

Odour : characteristic

Odour Threshold : No data available

pН : No data available

Melting point/freezing point : No data available

Initial boiling point and

boiling range

: No data available

Flash point : < -7 °C

> < 19.4 °F Propellant

Evaporation rate : No data available

Flammability (solid, gas) : Sustains combustion

Upper/lower flammability or : No data available

explosive limits

Vapour pressure : No data available

Vapour density : No data available

Relative density : 0.65 g/cm3 at 20 C

Solubility(ies) : No data available

Partition coefficient: n-

octanol/water

: No data available

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - CASHMERE WOODS®

Version 2.0 Print Date 05/22/2018

Revision Date 09/15/2017 SDS Number 350000017052

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

Volatile Organic Compounds Total VOC (wt. %)* 50.6 % - additional exemptions may apply
*as defined by US Federal and State Consumer Product

Regulations

Other information : None identified

10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Stable under recommended storage conditions.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

: Thermal decomposition can lead to release of irritating gases

and vapours.

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - CASHMERE WOODS®

Version 2.0 Print Date 05/22/2018

Revision Date 09/15/2017 SDS Number 350000017052

11. TOXICOLOGICAL INFORMATION

Acute dermal toxicity : LD50 > 5000 mg/kg

GHS Properties	Classification	Routes of entry
Acute toxicity	No classification proposed	Oral
Acute toxicity	No classification proposed	Dermal
Acute toxicity	No classification proposed	Inhalation - Dust and Mist
Acute toxicity	No classification proposed	Inhalation - Vapour
Acute toxicity	No classification proposed	Inhalation - Gas
Skin corrosion/irritation	No classification proposed	-
Eye irritation	Category 2B	-
Skin sensitisation	Category 1	-
Respiratory sensitisation	No classification proposed	-
Germ cell mutagenicity	No classification proposed	-
Carcinogenicity	No classification proposed	-
Reproductive toxicity	No classification proposed	-
Specific target organ toxicity - single exposure	Category 3	-
Specific target organ toxicity - repeated exposure	No classification proposed	-
Aspiration hazard	No classification proposed	-

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - CASHMERE WOODS®

Version 2.0 Print Date 05/22/2018

Revision Date 09/15/2017 SDS Number 350000017052

Aggravated Medical

Condition

: None known.

12. ECOLOGICAL INFORMATION

Product: The product itself has not been tested.

Toxicity

The ingredients in this formula have been reviewed and no adverse impact to the environment is expected when used according to label directions.

Toxicity to fish

Components	End point	Species	Value	Exposure time
Acetone	static test LC50	Oncorhynchus mykiss (rainbow trout)	6,210 mg/l	96 h
Isobutane	LC50 QSAR	Fish	27.98 mg/l	96 h
Propane	LC50	Fish	27.98 mg/l	96 h
Fragrance - Trade Secret	No data available			

Toxicity to aquatic invertebrates

Components	End point	Species	Value	Exposure time
Acetone	static test LC50	Daphnia pulex (Water flea)	8,800 mg/l	48 h
	NOEC	Daphnia magna	2,212 mg/l	28 d
Isobutane	LC50 QSAR	Daphnid	16.33 mg/l	48 h

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - CASHMERE WOODS®

Version 2.0 Print Date 05/22/2018

Revision Date 09/15/2017 SDS Number 350000017052

Propane	LC50	Daphnid	14.22 mg/l	48 h
Fragrance - Trade Secret	No data available			

Toxicity to aquatic plants

Components	End point	Species	Value	Exposure time
Acetone	NOEC	Microcystis aeruginosa (blue-green algae)	530 mg/l	8 d
Isobutane	EC50 QSAR	Green algae	8.57 mg/l	96 h
Propane	No data available			
Fragrance - Trade Secret	No data available			

Persistence and degradability

Component	Biodegradation	Exposure time	Summary
Acetone	90.9 %	28 d	Readily biodegradable.
Isobutane	70 %	< 10 d	Readily biodegradable.
Propane	70 %	< 10 d	Readily biodegradable.
Fragrance - Trade Secret	No data available		

Bioaccumulative potential

Component	Bioconcentration factor (BCF)	Partition Coefficient n- Octanol/water (log)
Acetone	0.69	-0.23

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - CASHMERE WOODS®

Version 2.0 Print Date 05/22/2018

Revision Date 09/15/2017 SDS Number 350000017052

Isobutane	1.57 - 1.97	2.8
Propane	No data available	2.36
Fragrance - Trade Secret	No data available	No data available

Mobility

Component	End point	Value
Acetone	No data available	+
Isobutane	No data available	
Propane	No data available	
Fragrance - Trade Secret	No data available	

PBT and vPvB assessment

Component	Results
Acetone	Not fulfilling PBT and vPvB criteria
Isobutane	Not fulfilling PBT and vPvB criteria
Propane	Not fulfilling PBT and vPvB criteria
Fragrance - Trade Secret	Not fulfilling PBT and vPvB criteria

Other adverse effects : None known.

13. DISPOSAL CONSIDERATIONS

Consumer may discard empty container in trash, or recycle where facilities exist.

14. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up-to-date shipping information.

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - CASHMERE WOODS®

Version 2.0 Print Date 05/22/2018

Revision Date 09/15/2017 SDS Number 350000017052

	Land transport	Sea transport	Air transport
UN number	1950	1950	1950
UN proper	AEROSOLS,	AEROSOLS,	AEROSOLS,
shipping name	Flammable	Flammable	Flammable
Transport hazard	2.1	2	2.1
class(es)			
Packing group	-	-	-
Environmental hazards	-	-	-
Special precautions for user	Limited quantities derogation may be applicable to this product, please check transport documents.	Limited quantities derogation may be applicable to this product, please check transport documents.	Limited quantities derogation may be applicable to this product, please check transport documents.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Product not transported as bulk.	Product not transported as bulk.	Product not transported as bulk.

15. REGULATORY INFORMATION

Notification status : All ingredients of this product are listed or are excluded from

listing on the U.S. Toxic Substances Control Act (TSCA)

Chemical Substance Inventory.

Notification status : All ingredients of this product comply with the New Substances

Notification requirements under the Canadian Environmental

Protection Act (CEPA).

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® AUTOMATIC SPRAY REFILL - CASHMERE WOODS®

Version 2.0 Print Date 05/22/2018

Revision Date 09/15/2017 SDS Number 350000017052

16. OTHER INFORMATION

HMIS R	Ratings
--------	---------

TIVIIO Kaliliys		
Health	2	
Flammability	4	
Reactivity	0	

NFPA Ratings

iti i A italings		
Health	2	
Fire	4	
Reactivity	0	
Special	-	

This information is being provided in accordance with the Occupational Safety and Health Administration (OSHA) regulation (29 CFR 1910.1200). The information supplied is designed for workplaces where product use and frequency of exposure exceeds that established for the labeled consumer use.

Further information

This document has been prepared using data from sources considered to be technically reliable. It does not constitute a warranty, expressed or implied, as to the accuracy of the information contained herein. Actual conditions of use are beyond the seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.

Prepared by	SC Johnson Global Safety Assessment &
	Regulatory Affairs (GSARA)