

XEROX

Material Safety Data Sheet

MSDS No: A-02095

Date: 2/13/96

Revision: 11/13/02

Distributor:

Xerox Corporation
Rochester, NY 14644

Telephone #(s): *Safety Information:* (800) 828-6571

Health Emergency: (585) 422-2177

Transportation Emergency (Chemtrec): (800) 424 - 9300

Section I - Product Identification

Trade Names/Synonyms: Document FaxCentre PRO 735, Document WorkCentre PRO 745/745 DL/ 745 SX Toner

Part No.: 6R851, 106R373

Chemical Name: None

WHMIS Status: This is not a WHMIS controlled product.

<u>Ingredients (% by wt.)</u>	<u>CAS No.</u>
Polyester resin (80-90%)	Trade Secret ¹
Wax (<10%)	9003-07-0
Carbon black (2-3%)	1333-86-4
Pigment (<2%)	104815-18-1

Section II - Emergency and First Aid

Primary Route of Entry:

Inhalation

Eyes:

Flush with water.

Skin:

Wash with soap and water.

Inhalation:

Remove from exposure.

Ingestion:

Dilute stomach contents with several glasses of water.

Symptoms of Overexposure:

Minimal respiratory tract irritation may occur as with exposure to large amounts of any non-toxic dust.

Medical Conditions Generally Aggravated by Exposure:

None when used as described by product literature.

Additional Information:

None.

Section III - Toxicology and Health Information

This material has been evaluated by Xerox Corporation.

Oral LD₅₀:	N.D.	TLV:	10 mg/m ³ (total dust)
Dermal LD₅₀:	>2 g/kg (rabbits) practically non-toxic.	PEL:	15 mg/m ³ (total dust)
Inhalation LC₅₀:	>9.36 mg/l		5 mg/m ³ (respirable dust)
Eye Irritation:	Not an irritant.	STEL:	N.E.
Skin Sensitization:	Not a sensitizer.	Ceiling:	N.E.
Skin Irritation:	Not an irritant.	XEL²:	2.5 mg/m ³ (total dust)
Human Patch:	N.D.		0.4 mg/m ³ (respirable dust)
Mutagenicity:	No mutagenicity detected in Ames Assays.		
Carcinogens:	None present		
Aquatic LC₅₀:	N.D.		

Additional Information: The results obtained from a Xerox sponsored, Chronic Toner Inhalation Study, demonstrated no lung change in rats for the lowest (1mg/m³) exposure level (i.e. the level most relevant to potential human exposure). A very slight degree of fibrosis was noted in 25% of the animals at the middle (4mg/m³) exposure level, while a slight degree of fibrosis was noted in all the animals at the highest (16 mg/m³) exposure level. These findings are attributed to "lung overloading", a generic response to excessive amounts of any dust retained in the lungs for a prolonged period. This study was conducted using a special test toner to comply with EPA testing protocol. The test toner was ten times more respirable than commercially available Xerox toner, and would not be functionally suitable for Xerox equipment.

¹This ingredient is considered a Trade Secret and registered under the New Jersey TSRN 80100252-5001-P. ²XEL - Xerox Exposure Limits.

Section IV - Physical Data

Appearance/Odor:	Black powder /odorless	Softening Range:	N.A.
Boiling Point:	N.A.	Melting Point:	N.A.
Solubility in Water:	Insoluble	Specific Gravity (H₂O=1):	1.2
Evaporation Rate:	N.A.	Vapor Pressure (mm Hg):	N.A.
Vapor Density (Air=1):	N.A.	pH:	N.A.
Volatile:	N.A. % (Wt.) N.A. % (Vol.)		

Section V - Fire and Explosion Data

Flash Point (Method Used):	N.A.
Flammable Limits:	LEL: 31.6 g/m ³ , UEL: N.A.
NFPA 704:	Health - 0, Fire - 3, Reactivity - 0
Extinguishing Media:	Water spray, foam, CO ₂ , dry powder
Special Fire Fighting Procedures:	Avoid inhalation of smoke.
Fire and Explosion Hazards:	Toner is a combustible powder. Like most organic materials in powder form, it can form explosive mixtures when dispersed in air.

Section VI -Reactivity Data

Stability:	Stable
Hazardous Polymerization:	Will Not Occur
Hazardous Decomposition Products:	Phenol derivatives, carbon monoxide when heated at high temperatures. (>300°C)
Incompatibility (Materials to Avoid):	Strong acid or alkaline

Section VII - Special Protection Information

Respiratory Protection:	None required when used as intended in Xerox equipment. Inhalation should be avoided.
Eye Protection:	None required when used as intended in Xerox equipment.
Protective Gloves:	None required when used as intended in Xerox equipment.
Other:	None

Section VIII - Special Precautions

Handling and Storage:	None
Conditions to Avoid:	Avoid prolonged inhalation of excessive dust.

Section IX- Spill, Leak, and Disposal Procedures

For Spills or Leakage:	Sweep up and place into a sealable waste container or vacuum spilled toner. Sweep slowly to minimize generation of dust during clean-up. If a vacuum is used, the motor must be rated as dust tight. A conductive hose bonded to the machine should be used to reduce static buildup (See Section V). Residue can be removed with soap and cold water. Garments may be washed or dry cleaned, after removal of loose toner.
Waste Disposal Method:	This material is not a hazardous waste according to Federal Regulation 40 CFR 261 when disposed. State and Local requirements may however be more restrictive. Consult with the appropriate State and Local waste disposal authorities for detailed information. Incinerate only in a closed container.

Section X - Transportation Information

DOT Proper Shipping Name:	N.A. (Not Regulated)	ID Number:	N.A.
Hazard Classification:	N.A.	Packing Group:	N.A.