## MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number

955-003

Product name Effective date Static Eliminator 22-Feb-2012

Company information

Martin Yale Industries, Inc

251 Wedcor

Wabash, Indiana 46992 United States

Company phone

219-563-0641

Emergency telephone US

866-836-8855

Emergency telephone outside US

1-952-852-4646

Version #

01

Product use

Antistatic agent

#### 2. Hazards Identification

Emergency overview

Aerosol, FLAMMABLE

CONTENTS UNDER PRESSURE.

Will be easily ignited by heat, spark or flames. Harmful in contact with eyes. Prolonged

exposure may cause chronic effects.

Potential health effects

Routes of exposure

Eye contact. Inhalation. Skin contact. Ingestion.

Eyes

Contact with eyes may cause irritation.

Skin

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and

dermatitis.

Inhalation

Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

Prolonged inhalation may be harmful.

Ingestion

Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage.

Components of the product may be absorbed into the body by ingestion.

Target organs

Central nervous system. Lungs.

Chronic effects

May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and

dermatitis. May cause delayed lung injury.

Signs and symptoms

Discomfort in the chest. Narcosis. Coughing. Defatting of the skin. Skin irritation.

3. Composition / Information on Ingredients					
Components	CAS#	Percent			
Ethyl Alcohol	64-17-5	70 - 80			
1,1-Difluoroethane	75-37-6	15 - 20			

#### 4. First Aid Measures

First aid procedures

Skin contact

Inhalation

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. Get medical attention immediately. Remove and isolate contaminated clothing and shoes. Wash off with warm water and

soap. Get medical attention if irritation develops and persists.

Move to fresh air. Do not use mouth-to-mouth method if victim inhaled the substance.

Call a physician if symptoms develop or persist.

Ingestion If material is ingested, immediately contact a poison control center. Do not induce

vomiting without advice from poison control center. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask

equipped with a one-way valve or other proper respiratory medical device.

Product name: Static Eliminator

MSDS US

0.1 - 1

Non-hazardous and other components below reportable levels

<b>*</b>				
Notes	to	nhvs	SIC	ะเลก

Keep victim warm. Keep victim under observation. Symptoms may be delayed.

#### 5. Fire Fighting Measures

Flammable properties

Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may

cause fire or explosion hazard.

Extinguishing media

Suitable extinguishing media

Protection of firefighters

Protective equipment and precautions for firefighters Water, Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up. Cool containers with flooding quantities of water until well after fire is out.

#### 6. Accidental Release Measures

Methods for containment

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk.

Methods for cleaning up

Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. After removal flush contaminated area thoroughly with water.

## 7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Do not get this material in contact with eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin. Avoid prolonged exposure.

Storage

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs. Level 2 Aerosol.

## 8. Exposure Controls / Personal Protection

#### **Exposure limits**

**ACGIH** 

Components	CAS#	TWA	STEL	Ceiling
Ethyl Alcohol	64-17-5	1000 ppm	1000 ppm	Not established
OSHA				
Components	CAS#	TWA	STEL	Ceiling
Ethyl Alcohol	64-17-5	1000 ppm	Not established	Not established

#### Personal protective equipment

Eye / face protection Skin protection

Do not get in eyes. Chemical goggles are recommended.

Wear appropriate chemical resistant clothing. Chemical resistant gloves.

Respiratory protection

Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

### 9. Physical & Chemical Properties

**Appearance Boiling point** Color

Compressed liquefied gas. 136.4 °F (57.8 °C) estimated

clear colorless

Density 0.8114 g/cm3 estimated

Product name: Static Eliminator

MSDS US

Product #: 955-003 Revision date: 22-FEB-2012 Print date: 22-FEB-2012 Flammability (HOC)

21.0417 kJ/g estimated

Flash back

Yes

Flash point

-58 °F (-50 °C) Propellant

Form Freezing point Aerosol.

Odor

Not available Characteristic.

рΗ

Not applicable

Physical state

Liquid.

Pressure

27 - 37 psig @70F

Solubility

Negligible

Specific gravity

0.8115

# 10. Chemical Stability & Reactivity Information

Chemical stability

Material is stable under normal conditions. Risk of ignition.

Conditions to avoid

Heat, flames and sparks.

Hazardous decomposition products

No hazardous decomposition products are known.

## 11. Toxicological Information

Acute effects

Acute LC50: 157 mg/l/4h estimated, Rat, Inhalation

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

1,1-Difluoroethane

75-37-6

Inhalation LC50 Mouse 977 g/m3 2 h

Ethyl Alcohol

64-17-5

Oral LD50 Rat 7060 mg/kg; Inhalation LC50 Rat 124.7 mg/L 4 h

Sensitization

Not expected to be hazardous by OSHA criteria.

Carcinogenicity

IARC - Group 1 (Carcinogenic to Humans)

Ethyl Alcohol

64-17-5

Monograph 100E [in preparation] (in alcoholic beverages); Monograph 96 [2010] (in

alcoholic beverages)

Teratogenicity

Not expected to be hazardous by OSHA criteria.

#### 12. Ecological Information

**Ecotoxicity** 

Components of this product have been identified as having potential environmental

concerns.

LC50 16191 mg/L, Fish, 96.00 Hours, EC50 14503 mg/L, Daphnia, 48.00 Hours,

IC50, Algae, 72.00 Hours,

#### 13. Disposal Considerations

Waste codes

D001: Waste Flammable material with a flash point <140 F

Disposal instructions

Contents under pressure. Dispose of this material and its container to hazardous or special waste collection point. Do not incinerate sealed containers. If discarded, this

product is considered a RCRA ignitable waste, D001.

## 14. Transport Information

#### Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name

Aerosols

Hazard class UN number 2.1

UN1950

Additional information:

Special provisions

153, N82

Packaging exceptions


LTD QTY

Packaging non bulk

None

Packaging bulk

None



Further information

Until 12/31/2013, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/13 and may be used now in place of the "Consumer Commodity ORM-D" marking but not concurrently.

#### IMDG

Basic shipping requirements:

Proper shipping name

**AEROSOLS** 

Hazard class

2.1

**UN number** 

1950

Additional information:

**Packaging exceptions** 

LTD QTY

Item

5F

Labels required

None

**Transport Category** 

#### IATA

Basic shipping requirements:

Proper shipping name

Aerosols, flammable

Hazard class

1950

**UN** number Additional information:

Packaging exceptions

LTD QTY

Labels required

2.1





# 15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

CERCLA/SARA Hazardous Substances - Not applicable.

## Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous

chemical

# CERCLA (Superfund) reportable quantity

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely

Nο

hazardous substance

Section 311 hazardous chemical Yes

Hazard categories (311/312)

Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

## Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

#### State regulations

U.S. - Pennsylvania - RTK (Right to Know) List

Ethyl Alcohol

64-17-5

Present

Product name: Static Eliminator

MSDS US

Product #: 955-003 Revision date: 22-FEB-2012 Print date: 22-FEB-2012 4/5

# 16. Other Information

HMIS® is a registered trade and service mark of the NPCA. **Further information** 

HMIS® ratings

Health: 1\* Flammability: 3 Physical hazard: 0

The information provided in this Safety Data Sheet is correct to the best of our Disclaimer

knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and

experience currently available.

Regulatory Compliance Prepared by

Product name: Static Eliminator

MSDS US Product #: 955-003 Revision date: 22-FEB-2012 Print date: 22-FEB-2012 5/5