

# A00175 MST SOLVENT SPOT RMVR 20net20

Version 1.1 Revision Date 07/14/2016 Print Date 04/27/2017

#### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : A00175 MST SOLVENT SPOT RMVR 20net20

Material number : 00000000001001620

Manufacturer or supplier's details

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW

Atlanta, GA 30318

Telephone : 404-352-1680

For SDS Information : Compliance Services 1-877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

#### Recommended use of the chemical and restrictions on use

Recommended use : Cleaner

### **SECTION 2. HAZARDS IDENTIFICATION**

### **Emergency Overview**

| Appearance | Aerosol containing a compressed gas |
|------------|-------------------------------------|
| Colour     | clear, colourless                   |
| Odour      | characteristic                      |

#### **GHS Classification**

Gases under pressure : Compressed gas
Skin irritation : Category 2
Eye irritation : Category 2A
Carcinogenicity : Category 1B

**GHS** label elements

Hazard pictograms :







Signal word : Danger

Hazard statements : H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation. H319 Causes serious eve irritation.

H350 May cause cancer.

Precautionary statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read



# A00175 MST SOLVENT SPOT RMVR 20net20

Version 1.1 Revision Date 07/14/2016 Print Date 04/27/2017

and understood.

P264 Wash skin thoroughly after handling. P280 Wear eye protection/ face protection.

P280 Wear protective gloves.

P281 Use personal protective equipment as required.

P251 Pressurized container: Do not pierce or burn, even after use.

#### Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

P332 + P313 If skin irritation occurs: Get medical advice/

attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P362 Take off contaminated clothing and wash before reuse.

### Storage:

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F. P403 Store in a well-ventilated place.

#### Disposal:

Dispose of contents/container in accordance with local regulation.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

## **Hazardous components**

| Chemical name       | CAS-No.  | Concentration [%] |
|---------------------|----------|-------------------|
| tetrachloroethylene | 127-18-4 | >= 90 - <= 100    |
| acetone             | 67-64-1  | >= 1 - < 5        |
| carbon dioxide      | 124-38-9 | >= 1 - < 5        |

The exact percentages of disclosed substances are withheld as trade secrets.

# **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Remove person to fresh air. If signs/symptoms continue, get

medical attention.

In case of skin contact : In case of contact, immediately flush eyes or skin with plenty

of water for at least 15 minutes while removing contaminated

clothing and shoes.

Wash contaminated clothing before reuse. Call a physician if irritation develops or persists.



# A00175 MST SOLVENT SPOT RMVR 20net20

Version 1.1 Revision Date 07/14/2016 Print Date 04/27/2017

In case of eye contact : Remove contact lenses.

In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If eye irritation persists, consult a specialist.

Protect unharmed eye.

Keep eye wide open while rinsing.

If swallowed : DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Dry chemical

Alcohol-resistant foam Carbon dioxide (CO2) Water spray jet

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

Carbon dioxide (CO2)

Carbon monoxide

Smoke

Chlorine compounds

Specific extinguishing

methods

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition.

Immediately evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.



# A00175 MST SOLVENT SPOT RMVR 20net20

Version 1.1 Revision Date 07/14/2016 Print Date 04/27/2017

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Container may be opened only under exhaust ventilation

hood.

Always replace cap after use.

Dispose of rinse water in accordance with local and national

regulations.

Do not breathe vapours or spray mist.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Keep in a dry, cool and well-ventilated place.

No smoking.

Materials to avoid : Strong oxidizing agents

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Components with workplace control parameters

| Components          | CAS-No.  | Value type<br>(Form of<br>exposure) | Control parameters / Permissible concentration | Basis     |
|---------------------|----------|-------------------------------------|--|-----------|
| tetrachloroethylene | 127-18-4 | TWA                                 | 25 ppm   | ACGIH     |
|                     |          | STEL                                | 100 ppm  | ACGIH     |
|                     |          | TWA                                 | 100 ppm  | OSHA Z-2  |
|                     |          | CEIL                                | 200 ppm  | OSHA Z-2  |
|                     |          | Peak                                | 300 ppm  | OSHA Z-2  |
|                     |          | TWA                                 | 25 ppm<br>170 mg/m3                            | OSHA P0   |
| acetone             | 67-64-1  | TWA                                 | 500 ppm  | ACGIH     |
|                     |          | STEL                                | 750 ppm  | ACGIH     |
|                     |          | TWA                                 | 250 ppm  | NIOSH REL |
|                     |          |                                     | 590 mg/m3                                      |           |
|                     |          | TWA                                 | 1,000 ppm                                      | OSHA Z-1  |



# A00175 MST SOLVENT SPOT RMVR 20net20

Version 1.1 Revision Date 07/14/2016 Print Date 04/27/2017

|                |          |      | 2,400 mg/m3                |           |
|----------------|----------|------|----------------------------|-----------|
|                |          | TWA  | 750 ppm<br>1,800 mg/m3     | OSHA P0   |
|                |          | STEL | 1,000 ppm<br>2,400 mg/m3   | OSHA P0   |
| carbon dioxide | 124-38-9 | TWA  | 5,000 ppm                  | ACGIH     |
|                |          | STEL | 30,000 ppm                 | ACGIH     |
|                |          | TWA  | 5,000 ppm<br>9,000 mg/m3   | NIOSH REL |
|                |          | ST   | 30,000 ppm<br>54,000 mg/m3 | NIOSH REL |
|                |          | TWA  | 5,000 ppm<br>9,000 mg/m3   | OSHA Z-1  |
|                |          | TWA  | 10,000 ppm<br>18,000 mg/m3 | OSHA P0   |
|                |          | STEL | 30,000 ppm<br>54,000 mg/m3 | OSHA P0   |

## Biological occupational exposure limits

| Component             | CAS-No.  | Control parameters      | Biological specimen    | Sampling time  | Permissible concentration | Basis     |
|-----------------------|----------|-------------------------|------------------------|--|---------------------------|-----------|
| TETRACHLOROETHEN<br>E | 127-18-4 | Tetrachloroe<br>thylene | In blood               | Prior to<br>shift (16<br>hours<br>after<br>exposure<br>ceases)             | 0.5 mg/l                  | ACGIH BEI |
| TETRACHLOROETHEN<br>E |          | Tetrachloroe<br>thylene | In end-<br>exhaled air | Prior to<br>shift (16<br>hours<br>after<br>exposure<br>ceases)             | 3.ppm                     | ACGIH BEI |
| 2-PROPANONE           | 67-64-1  | Acetone                 | Urine                  | End of<br>shift (As<br>soon as<br>possible<br>after<br>exposure<br>ceases) | 50 mg/l                   | ACGIH BEI |

**Engineering measures** : effective ventilation in all processing areas

## Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Safety glasses

Ensure that eyewash stations and safety showers are close to

the workstation location.



# A00175 MST SOLVENT SPOT RMVR 20net20

Version 1.1 Revision Date 07/14/2016 Print Date 04/27/2017

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a compressed gas

Colour : clear, colourless
Odour : characteristic
Odour Threshold : No data available
pH : No data available
Melting point/freezing point : No data available
Boiling point : No data available

Flash point :

does not flash

Evaporation rate : not determined

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : 5,860 - 6,894 hPa

Relative vapour density : No data available

Density : 1.60 g/cm3

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

Heat of combustion : 6.12 kJ/g

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Stable

Chemical stability : Stable under normal conditions.



# A00175 MST SOLVENT SPOT RMVR 20net20

Version 1.1 Revision Date 07/14/2016 Print Date 04/27/2017

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Aluminium

Strong oxidizing agents

Hazardous decomposition

products

: Carbon monoxide Carbon dioxide (CO2)

Gaseous hydrogen chloride (HCI).

Phosgene Chlorine

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

### **Potential Health Effects**

Carcinogenicity:

IARC Group 2A: Probably carcinogenic to humans

tetrachloroethylene 127-18-4

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

tetrachloroethylene 127-18-4

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP Reasonably anticipated to be a human carcinogen

tetrachloroethylene 127-18-4

Acute toxicity

**Product:** 

Acute oral toxicity : Acute toxicity estimate : 2,837 mg/kg

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Components:

tetrachloroethylene:

Acute oral toxicity : LD50 Oral Rat: 2,629 mg/kg

Acute inhalation toxicity : LC50 Rat: 34,200 mg/l

Exposure time: 8 h

Acute dermal toxicity : LD50 Dermal Rabbit: 5,000 mg/kg



# A00175 MST SOLVENT SPOT RMVR 20net20

Version 1.1 Revision Date 07/14/2016 Print Date 04/27/2017

acetone:

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l

Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

#### Skin corrosion/irritation

**Product:** 

Remarks: May cause skin irritation in susceptible persons.

### Serious eye damage/eye irritation

**Product:** 

Remarks: Irritating to eyes.

#### Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

### Reproductive toxicity

No data available

tetrachloroethylene:

acetone:

carbon dioxide:

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

# **Further information**

**Product:** 

Remarks: No data available



# A00175 MST SOLVENT SPOT RMVR 20net20

Revision Date 07/14/2016 Version 1.1 Print Date 04/27/2017

#### **SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity** 

No data available

Persistence and degradability

No data available

Bioaccumulative potential

**Product:** 

Partition coefficient: n-

octanol/water

**Components:** tetrachloroethylene:

Partition coefficient: n-

octanol/water

: Remarks: No data available

: log Pow: 3.40

Mobility in soil

No data available

Other adverse effects

No data available

**Product:** 

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

> with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: An environmental hazard cannot be excluded in the

event of unprofessional handling or disposal., Toxic to

aquatic life.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.



## A00175 MST SOLVENT SPOT RMVR 20net20

Version 1.1 Revision Date 07/14/2016 Print Date 04/27/2017

Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

### **SECTION 15. REGULATORY INFORMATION**

## **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

| Components          | CAS-No.  | Component RQ | Calculated product RQ |
|---------------------|----------|--------------|-----------------------|
|                     |          | (lbs)        | (lbs)                 |
| tetrachloroethylene | 127-18-4 | 100          | 108                   |

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Sudden Release of Pressure Hazard

Acute Health Hazard Chronic Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

tetrachloroethylene 127-18-4 92.6534 %



# A00175 MST SOLVENT SPOT RMVR 20net20

Version 1.1 Revision Date 07/14/2016 Print Date 04/27/2017

California Prop 65 WARNING! This product contains a chemical known to the

State of California to cause cancer.

tetrachloroethylene 127-18-4

#### The components of this product are reported in the following inventories:

TSCA On TSCA Inventory

DSL All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.


#### **Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

NFPA:



Special hazard.

#### HMIS III:

| HEALTH          | 2 |
|-----------------|---|
| FLAMMABILITY    | 0 |
| PHYSICAL HAZARD | 2 |

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, \* = Chronic

### **OSHA - GHS Label Information:**

Hazard pictograms







Signal word

Hazard statements

: Danger:

Contains gas under pressure; may explode if heated. Causes skin irritation. Causes

serious eye irritation. May cause cancer.

Precautionary statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash skin thoroughly after handling. Wear eye protection/face protection. Wear protective gloves. Use personal protective equipment as required. Pressurized container: Do not pierce or burn, even after use. Response: IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage: Store locked up. Protect from sunlight. Do not expose to temperatures

exceeding 50 °C/ 122 °F. Store in a well-ventilated place.

**Disposal**: Dispose of contents/container in accordance with local regulation.



# A00175 MST SOLVENT SPOT RMVR 20net20

Version 1.1 Revision Date 07/14/2016 Print Date 04/27/2017

| Version:       | 1.1        |
|----------------|------------|
| Revision Date: | 07/14/2016 |
| Print Date:    | 04/27/2017 |

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®,Rexodan®, Mykal™, and a number of private labeled brands.