

# MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFACTURER'S INFORMATION						
<b>NFPA Rating:</b> Health-2; Flammability-3; Reactivity-0; Special-0 Manufacturer's Name: <b>AMREP, INC.</b> Address: 990 Industrial Park Drive Marietta, GA 30062		<b>HMIS Rating:</b> Health-2; Flammability-3; Reactivity-0; Personal Protection-B <b>DOT Hazard Classification:</b> ORM-D <b>Identity</b> (trade name as used on label): <b>MISTY HEAVY DUTY ADHESIVE SPRAY</b>				
Date Prepared: 12/06/01      Prepared By: IB/TR Information Calls: (770) 422-2071 <b>EMERGENCY RESPONSE NUMBER: 1(800)255-3924</b>		<b>MSDS Number:</b> A00315      Revision- 10 NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA				
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
ACETONE		67-64-1	No	1000	750	d
HEXANE		110-54-3	Yes	*50	50	d
ISOBUTANE / PROPANE BLEND		75-28-5	No	800	800	d
		74-98-6	No	1000	1000	d
* Per Manufacturer's Recommendation						
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS						
Boiling Point: N/A		Specific Gravity (H2O=1): Concentrate Only = 0.853				
Vapor Pressure: PSIG @ 70°F (Aerosols): Max.80		Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A				
Vapor Density (Air = 1): N/E		Evaporation Rate ( = 1): N/E				
Solubility in Water: Partial		Water Reactive: No				
Appearance and Odor: Straw colored liquid with ketone solvent odor.						
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA						
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) <b>EXTREMELY FLAMMABLE</b>		Auto Ignition Temperature N/E		Flammability Limits in Air by % in Volume: % LEL: N/E      % UEL: N/E		
FLASH POINT AND METHOD USED (non-aerosols): N/A		SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus. Use water fog to cool containers to prevent rupturing & exploding containers. Provide shielding for personnel.				
EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water.						
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.						
SECTION 4 - REACTIVITY HAZARD DATA						
STABILITY [ X ] STABLE [ ] UNSTABLE		HAZARDOUS POLYMERIZATION [ ] WILL [ X ] WILL NOT OCCUR				
Incompatibility (Mat. to avoid): Strong oxidizing agents.		Conditions to Avoid: Open flame, welding arcs, heat, sparks.				
Hazardous Decomposition Products: Carbon dioxide, carbon monoxide.						
SECTION 5 - HEALTH HAZARD DATA						
PRIMARY ROUTES OF ENTRY: [ X ] INHALATION [ ] INGESTION [ X ] SKIN ABSORPTION [ ] EYE [ ] NOT HAZARDOUS						
ACUTE EFFECTS						
Inhalation: Excessive inhalation of vapors can cause nasal & respiratory irritation, dizziness, weakness, nausea, headache, possible unconsciousness or asphyxiation.						
Eye Contact: Irritation.		Skin Contact: Irritation due to defatting of skin.				
Ingestion: Possible chemical pneumonitis if aspirated into lungs.						
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) Excessive inhalation of hexane may cause nerve damage.						
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.						
EMERGENCY FIRST AID PROCEDURES						
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.						
Skin Contact: Wash with soap and water. If irritated, seek medical attention.						
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.						
Ingestion: <b>DO NOT INDUCE VOMITING.</b> Drink two large glasses of water. Get immediate medical attention.						
SECTION 6 - CONTROL AND PROTECTIVE MEASURES						
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH in positive pressure mode.						
Protective Gloves: Neoprene.		Eye Protection: Safety glasses recommended.				
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.						
Other Protective Clothing & Equipment: None						
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.						
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE						
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. DO NOT FLUSH TO SEWER.						
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.						
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.						
Other Precautions &/or Special Hazards: <b>KEEP OUT OF REACH OF CHILDREN.</b> Avoid food contamination. Avoid breathing vapors. Remove ignition sources.						

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

\*\* Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only