

Version 1.1 SDS Number: 400000000157 Revision Date: 07/08/2019

SECTION 1. IDENTIFICATION

Product name : GOJO® E2 Foam Sanitizing Soap

Manufacturer or supplier's details

Company name of supplier : GOJO Industries, Inc.

Address : One GOJO Plaza, Suite 500

Akron, Ohio 44311

Telephone : 1 (330) 255-6000

Emergency telephone : CHEMTREC 1-800-424-9300

number CHEMTREC +1-703-527-3887: Outside USA & CANADA

Recommended use of the chemical and restrictions on use

Recommended use : Antibacterial Soap

Restrictions on use : This is a personal care or cosmetic product that is safe for

consumers and other users under normal and reasonably foreseeable use. Cosmetics and consumer products, specifically defined by regulations around the world, are exempt from the requirement of an SDS for the consumer. While this material is not considered hazardous, this SDS contains valuable information critical to the safe handling and proper use of the product for industrial workplace conditions as well as unusual and unintended exposures such as large spills. This SDS should be retained and available for employees and other users of this product. For specific intended-use guidance, please refer to the information

provided on the package or instruction sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Serious eye damage : Category 1

GHS label elements

Hazard pictograms





Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H318 Causes serious eye damage.

Precautionary statements : **Prevention:**

P210 Keep away from heat/sparks/open flames/hot surfaces. -

No smoking.

P233 Keep container tightly closed.



SDS Number: 40000000157 Version 1.1 Revision Date: 07/08/2019

> P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P280 Wear eye protection/ face protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER or doctor/ physician.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical name	CAS-No.	Concentration (%)
Ethyl Alcohol	64-17-5	>= 10 - < 20
Lauric Acid	143-07-7	>= 5 - < 10
Propylene Glycol	57-55-6	>= 5 - < 10
Ethanolamine	141-43-5	>= 1 - < 5
Disodium Cocoamphodiacetate	68650-39-5	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

If symptoms persist, call a physician.

In case of skin contact : Wash with water and soap as a precaution.

Get medical attention if irritation develops and persists.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Seek medical advice.

: Do NOT induce vomiting. If swallowed

> Rinse mouth with water. Obtain medical attention. : Causes serious eye damage.

Most important symptoms and effects, both acute and

delayed

Protection of first-aiders : First Aid responders should pay attention to self-protection



Version 1.1 SDS Number: 400000000157 Revision Date: 07/08/2019

and use the recommended protective clothing

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

High volume water jet

Specific hazards during

firefighting

: Do not use a solid water stream as it may scatter and spread

fire

Cool closed containers exposed to fire with water spray.

Flash back possible over considerable distance.

May form explosive mixtures in air.

Exposure to decomposition products may be a hazard to

health.

Carbon oxides

Nitrogen oxides (NOx)

Metal oxides

Hazardous combustion

products

: Carbon oxides

Nitrogen oxides (NOx)

Metal oxides

Specific extinguishing

methods

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Use water spray to cool unopened containers.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Keep people away from and upwind of spill/leak.

Material can create slippery conditions.

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

: Non-sparking tools should be used.

Soak up with inert absorbent material.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

Keep in suitable, closed containers for disposal.

Clean contaminated floors and objects thoroughly while

observing environmental regulations.



Version 1.1 SDS Number: 400000000157 Revision Date: 07/08/2019

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : For personal protection see section 8.

Keep away from heat.

Use with local exhaust ventilation.

Avoid contact with eyes.

Conditions for safe storage : Take measures to prevent the build up of electrostatic charge.

Keep in properly labelled containers.

Keep containers tightly closed in a dry, cool and well-

ventilated place.

Store in accordance with the particular national regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethyl Alcohol	64-17-5	TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		STEL	1,000 ppm	ACGIH
Propylene Glycol	57-55-6	TWA	10 mg/m3	US WEEL
Ethanolamine	141-43-5	TWA	3 ppm	ACGIH
		STEL	6 ppm	ACGIH
		TWA	3 ppm 8 mg/m3	NIOSH REL
		ST	6 ppm 15 mg/m3	NIOSH REL
		TWA	3 ppm 6 mg/m3	OSHA Z-1
		STEL	6 ppm 15 mg/m3	OSHA P0
		TWA	3 ppm 8 mg/m3	OSHA P0

Hazardous components without workplace control parameters

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

Hand protection

Remarks : No special protective equipment required.

Eye protection : Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : No special measures necessary provided product is used

correctly.

Protective measures : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Ensure that eye flushing systems and safety showers are

located close to the working place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety



Version 1.1 SDS Number: 400000000157 Revision Date: 07/08/2019

practice.

Avoid contact with eyes.

: No data available

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : clear, light yellow, yellow

Odour : slight, alcohol-like Odour Threshold : No data available

pH : 7.8 - 9.8, (20 °C)

Melting point/freezing point

Initial boiling point and boiling : 77.00 °C

range

Flash point : 40.00 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Does not sustain combustion.

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Density : 0.9869 g/cm3

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

: Not applicable

Auto-ignition temperature :

: No data available

Thermal decomposition : The substance or mixture is not classified self-reactive.

Viscosity

Viscosity, kinematic : 10 - 20 mm2/s (20 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard. Chemical stability : Stable under normal conditions.

Possibility of hazardous : Vapours may form explosive mixture with air.



Version 1.1 SDS Number: 400000000157 Revision Date: 07/08/2019

reactions

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Eye contact Skin contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 200 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Components:

Ethyl Alcohol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 124.7 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Lauric Acid:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 0.162 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Propylene Glycol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rabbit): > 159 mg/l, > 51091 ppm

Exposure time: 4 h



Version 1.1 SDS Number: 400000000157 Revision Date: 07/08/2019

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Ethanolamine:

Acute oral toxicity : LD50 (Rat): 1,515 mg/kg

Acute inhalation toxicity : Acute toxicity estimate : 11 mg/l

Test atmosphere: vapour Method: Expert judgement

Remarks: Based on harmonised classification in EU regulati

on 1272/2008, Annex VI

Acute dermal toxicity : LD50 (Rabbit): 1,025 mg/kg

Disodium Cocoamphodiacetate:

Acute oral toxicity : LD50 (Rat, male): > 5,000 mg/kg

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Product:

Assessment: Not irritating when applied to human skin.

Result: No skin irritation

Components:

Ethyl Alcohol:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Lauric Acid: Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Propylene Glycol: Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Ethanolamine: Species: Rabbit

Result: Corrosive after 3 minutes to 1 hour of exposure



Version 1.1 SDS Number: 400000000157 Revision Date: 07/08/2019

Disodium Cocoamphodiacetate:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Remarks: Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Ethyl Alcohol: Species: Rabbit

Result: Irritation to eyes, reversing within 21 days

Method: OECD Test Guideline 405

Lauric Acid: Species: Rabbit

Result: Irreversible effects on the eye Method: OECD Test Guideline 405

Propylene Glycol:

Species: Rabbit Result: No eve irritation

Method: OECD Test Guideline 405

Ethanolamine:

Species: Rabbit

Result: Irreversible effects on the eye

Disodium Cocoamphodiacetate:

Species: Rabbit

Result: Irreversible effects on the eye Method: OECD Test Guideline 405

Remarks: Based on data from similar materials

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Components: Ethyl Alcohol:

Test Type: Local lymph node assay (LLNA)

Exposure routes: Skin contact

Species: Mouse Result: negative

Lauric Acid:

Test Type: Maximisation Test (GPMT)

Exposure routes: Skin contact

Species: Guinea pig Result: negative

Propylene Glycol:

Test Type: Maximisation Test (GPMT)

Exposure routes: Skin contact



Version 1.1 SDS Number: 400000000157 Revision Date: 07/08/2019

Species: Guinea pig Result: negative

Ethanolamine:

Test Type: Maximisation Test (GPMT)

Exposure routes: Skin contact

Species: Guinea pig Result: negative

Disodium Cocoamphodiacetate:

Test Type: Maximisation Test (GPMT)

Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

Remarks: Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Ethyl Alcohol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)

Test species: Mouse Application Route: Ingestion

Result: negative

Lauric Acid:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Propylene Glycol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Test species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Ethanolamine:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Test species: Mouse

Application Route: Ingestion

Method: OECD Test Guideline 474

Result: negative



Version 1.1 SDS Number: 400000000157 Revision Date: 07/08/2019

Disodium Cocoamphodiacetate:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Remarks: Based on data from similar materials

: Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

: Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Propylene Glycol:

Species: Rat

Application Route: Ingestion Exposure time: 2 Years

Result: negative

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Ethyl Alcohol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Mouse

Application Route: Ingestion Method: OECD Test Guideline 416

Result: negative

Lauric Acid:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the re

production/developmental toxicity screening test

Species: Rat

Application Route: Ingestion



Version 1.1 SDS Number: 400000000157 Revision Date: 07/08/2019

Method: OECD Test Guideline 422

Result: negative

Remarks: Based on data from similar materials

Effects on foetal

development

: Test Type: Combined repeated dose toxicity study with the re

production/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Remarks: Based on data from similar materials

Propylene Glycol:

Effects on fertility

: Species: Mouse

Application Route: Ingestion

Result: negative

Effects on foetal

development

Test Type: Embryo-foetal development

Species: Mouse

Application Route: Ingestion

Result: negative

Ethanolamine:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on foetal

development

: Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

STOT - single exposure

Not classified based on available information.

Components:

Ethanolamine:

Assessment: May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:

Ethanolamine:

Exposure routes: inhalation (dust/mist/fume)

Assessment: No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d

or less.

Repeated dose toxicity

Components:

Ethyl Alcohol:

Species: Rat



Version 1.1 SDS Number: 400000000157 Revision Date: 07/08/2019

NOAEL: 2,400 mg/kg Application Route: Ingestion

Exposure time: 2 y

Lauric Acid: Species: Rat

NOAEL: 10,000 mg/kg Application Route: Ingestion

Exposure time: 18 w

Propylene Glycol:

Species: Rat

NOAEL: 1,700 mg/kg Application Route: Ingestion

Exposure time: 2 y

Ethanolamine:

Species: Rat

NOAEL: 150 mg/m3

Application Route: inhalation (dust/mist/fume)

Exposure time: 28 d

Disodium Cocoamphodiacetate:

Species: Rat, female NOAEL: 250 mg/kg LOAEL: 500 mg/kg

Application Route: Ingestion

Exposure time: 28 d

Remarks: Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Ethyl Alcohol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

Exposure time: 48 h

Toxicity to algae : EC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

: NOEC (Daphnia magna (Water flea)): 9.6 mg/l

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

Exposure time: 9 d

Toxicity to bacteria : EC50 (Photobacterium phosphoreum): 32.1 mg/l

Exposure time: 0.25 h



Version 1.1 SDS Number: 400000000157 Revision Date: 07/08/2019

Lauric Acid:

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): 5 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 3.6 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): > 7.6 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility

NOEC (Selenastrum capricornutum (green algae)): > 7.6 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility

Toxicity to fish (Chronic

toxicity)

: NOEC (Danio rerio (zebra fish)): 2 mg/l

Exposure time: 28 d

Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 0.47 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Toxicity to bacteria : EC10 (Pseudomonas putida): > 1,000 mg/l

Exposure time: 30 min

Method: OECD Test Guideline 209

Propylene Glycol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 40,613 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Ceriodaphnia Dubia (water flea)): 18,340 mg/l

Exposure time: 48 h

Toxicity to algae : EC50 (Skeletonema costatum (marine diatom)): 19,000 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic

toxicity)

: Chronic Toxicity Value: 2,500 mg/l

Exposure time: 30 d

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Ceriodaphnia Dubia (water flea)): 29,000 mg/l

Exposure time: 7 d

Toxicity to bacteria : NOEC (Pseudomonas putida): > 20,000 mg/l

Exposure time: 18 h

Ethanolamine:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 349 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 65 mg/l

Exposure time: 48 h



Version 1.1 SDS Number: 400000000157 Revision Date: 07/08/2019

Toxicity to algae : ErC50 (Selenastrum capricornutum (green algae)): 2.8 mg/l

Exposure time: 72 h

NOEC (Scenedesmus capricornutum (fresh water algae)): 1

mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

: NOEC (Oryzias latipes (Orange-red killifish)): 1.24 mg/l

Exposure time: 41 d

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 0.85 mg/l

Exposure time: 21 d

Toxicity to bacteria : EC50 (Pseudomonas putida): 110 mg/l

Exposure time: 17 h

Disodium Cocoamphodiacetate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 17.9 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 10

mg/l

Exposure time: 72 h

Method: Directive 67/548/EEC, Annex V, C.3. Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 3.2

mg/l

Exposure time: 72 h

Method: Directive 67/548/EEC, Annex V, C.3. Remarks: Based on data from similar materials

Persistence and degradability

Components:

Ethyl Alcohol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 84 % Exposure time: 20 d

Lauric Acid:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 86 % Exposure time: 30 d

Method: OECD Test Guideline 301D

Propylene Glycol:

Biodegradability : Result: Readily biodegradable.



Version 1.1 SDS Number: 400000000157 Revision Date: 07/08/2019

Biodegradation: 98.3 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Ethanolamine:

Biodegradability : Result: Readily biodegradable.

Biodegradation: > 90 % Exposure time: 21 d

Disodium Cocoamphodiacetate:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 79 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

Bioaccumulative potential

Components:

Ethyl Alcohol:

Partition coefficient: n-

: log Pow: -0.35

octanol/water Lauric Acid:

Bioaccumulation : Species: Fish

Bioconcentration factor (BCF): 234 - 288 Remarks: Based on data from similar materials

Partition coefficient: n-

octanol/water

: Pow: 4.6

Propylene Glycol:

Partition coefficient: n-

: log Pow: -1.07

octanol/water
Ethanolamine:

Partition coefficient: n-

: log Pow: -1.91

octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a

Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Dispose of as unused product.



Version 1.1 SDS Number: 400000000157 Revision Date: 07/08/2019

Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulation

IATA-DGR

UN/ID No. : UN 1170

Proper shipping name : Ethanol solution

Class : 3
Packing group : III
Packing instruction (cargo : 366

aircraft)

Packing instruction : 355

(passenger aircraft)

IMDG-Code

UN number : UN 1170

Proper shipping name : ETHANOL SOLUTION

(Triclosan)

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-D

Marine pollutant : yes

National Regulations

49 CFR

UN/ID/NA number : UN 1170

Proper shipping name : Ethanol solutions

Class : 3
Packing group : III
ERG Code : 127

Marine pollutant : yes(Triclosan)

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.



Version 1.1 SDS Number: 400000000157 Revision Date: 07/08/2019

SARA 313

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

 Ethyl Alcohol
 64-17-5
 13.215 %

 Propylene Glycol
 57-55-6
 5 %

 Ethanolamine
 141-43-5
 1.9 %

This product does not contain any VOC exemptions listed under the U.S. Clean Air Act Section 450.

Clean Water Act

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

US State Regulations

Massachusetts Right To Know

Ethyl Alcohol	64-17-5	10 - 20 %	
Ethanolamine	141-43-5	1 - 5 %	
Sodium Metabisulfite	7681-57-4	0 - 0.1 %	

Pennsylvania Right To Know

Water (Aqua)	7/32-18-5	70 - 90 %
Ethyl Alcohol	64-17-5	10 - 20 %
Lauric Acid	143-07-7	5 - 10 %
Propylene Glycol	57-55-6	5 - 10 %
Ethanolamine	141-43-5	1 - 5 %
Isopropyl Alcohol	67-63-0	0.1 - 1 %
Sodium Metabisulfite	7681-57-4	0 - 0.1 %
Sodium Hydroxide	1310-73-2	0 - 0.1 %

New Jersey Right To Know

Water (Aqua)	7732-18-5	70 - 90 %
Ethyl Alcohol	64-17-5	10 - 20 %
Lauric Acid	143-07-7	5 - 10 %
Propylene Glycol	57-55-6	5 - 10 %
Ethanolamine	141-43-5	1 - 5 %

California Prop 65 This product does not require a warning label under California

Proposition 65.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

AICS : On the inventory, or in compliance with the inventory

DSL : On the inventory, or in compliance with the inventory



SDS Number: 40000000157 Version 1.1 Revision Date: 07/08/2019

ENCS : On the inventory, or in compliance with the inventory

ISHL : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

HMIS III:

HEALTH	3
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, * = Chronic

Revision Date : 07/08/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.