

ACCORDING TO US CFR 1910.1200

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Gorilla Contact Adhesive Ultimate (Web Spray) Product Name 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) Glue from spray Uses Advised Against Not known. 1.3 Details of the supplier of the safety data sheet

Manufacturer

Company Identification The Gorilla Glue Company Address of Manufacturer 2101 East Kemper Road

> Cincinnati, Ohio 45241

Zip code Telephone 513-271-3300 Info@gorillaglue.com F-mail

Supplier

Company Identification The Gorilla Glue Company Address of Supplier 2101 East Kemper Road

Cincinnati, Ohio

45241 Zip code Telephone 513-271-3300 Info@gorillaglue.com F-mail

1.4 Emergency telephone number

Emergency Phone No. 1-800-420-7186

Contact Prosar

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

US CFR 1910.1200 Flammable aerosol 1: Extremely flammable aerosol.

Skin Sens. 1B: May cause an allergic skin reaction. Eye Irrit. 2A: Causes serious eye irritation. STOT SE 3: May cause drowsiness or dizziness.

2.2 Label elements

According to US CFR 1910.1200

Product Name Gorilla Contact Adhesive Ultimate (Web Spray) Hazard Pictogram(s)







Signal Word(s) Danger

Hazard Statement(s) H222: Extremely flammable aerosol.

H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Precautionary

P261: Avoid breathing mist/vapors/spray. Statement(s)

P302+P352: IF ON SKIN: Wash with plenty of water. P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501: Dispose of contents in accordance with local, state or national legislation.

Additional Information If medical advice is needed, have product container or label at hand. Keep out of the reach of children. Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F. Do not pierce or burn,

even after use. Do not spray on an open flame or other ignition source.

2.3 Other hazards

None known.

2.4 Additional Information

Page: 1 - 9 Revision: 1



For full text of H/P Statements see section 16.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Product as supplied: Aerosol

3.1 Substances

Not applicable.

3.2 Mixtures

HAZARDOUS INGREDIENT(S)	CAS No.	%W/W	Hazard Statement(s)	Hazard Pictogram(s)
Methyl acetate	79-20-9	50-60	Flam. Liq. 2 H225	GHS02
			Eye Irrit. 2A H319	GHS07
			STOT SE 3 H336	
Petroleum gases, liquefied, sweetened	68476-86-8	20-40	Flam. Gas 1 H220	GHS02
			Press. Gas H280	GHS04
			Note K*	
Cyclohexane	110-82-7	5-10	Flam. Liq. 2 H225	GHS02
			Asp. Tox. 1 H304	GHS08
			Skin Irrit. 2 H315	GHS07
			STOT SE 3 H336	
4-chloro-α,α,α-trifluorotoluene	98-56-6	5-10	Flam. Liq. 3 H226	GHS02
			Skin Sens. 1B H317	GHS07
Pentane	109-66-0	1-5	Flam. Liq. 2 H225	GHS02
			Asp. Tox. 1 H304	GHS08
			STOT SE 3 H336	GHS07
Propyl acetate	109-60-4	1-5	Flam. Liq. 2 H225	GHS02
			Eye Irrit. 2A H319	GHS07
			STOT SE 3 H336	
Bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	0.1-1	Skin Irrit. 2 H315	GHS07
			Skin Sens. 1 H317	
			Eye Irrit. 2A H319	
Cyclopentane	287-92-3	0.1-1	Flam. Liq. 2 H225	GHS02
Isopentane	78-78-4	0.1-1	Flam. Liq. 1 H224	GHS02
			Asp. Tox. 1 H304	GHS08
			STOT SE 3 H336	GHS07

Note K: The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0.1 % w/w 1,3-butadiene (Einecs No 203-450-8). For full text of H/P Statements see section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

Inhalation Remove person to fresh air and keep comfortable for breathing. Call a POISON

CENTER/doctor if you feel unwell.

Skin Contact Wash with plenty of water. Take off immediately all contaminated clothing and wash

it before reuse. If skin irritation or rash occurs: Get medical advice/attention. Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Ingestion Wash out mouth with water.
4.2 Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction. Causes serious eye irritation. May cause

drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Unlikely to be required but if necessary treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Pressurised container: May burst if heated.

5.1 Extinguishing media

Eye Contact

Suitable Extinguishing media As appropriate for surrounding fire.

Unsuitable extinguishing media None known.

5.2 Special hazards arising from the substance or mixture

May decompose in a fire, giving off toxic and irritant vapors.

5.3 Advice for firefighters

Fire fighters should wear complete protective clothing including self-contained

breathing apparatus. Dike fire control water for later disposal.

Page: 2 - 9 Revision: 1



SECTION 6: ACCIDENTAL RELEASE MEASURES

The product is an aerosol. It is unlikely to present spillage or leakage hazard. In case of rupture, released content should be contained as any other solvent spill.

6.1 Personal precautions, protective equipment and emergency procedures

Stop leak if safe to do so. Provide adequate ventilation. Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems.

6.2 Environmental precautions

Do not release large quantities into the surface water or into drains.

6.3 Methods and material for containment and cleaning up

Collect mechanically and dispose of according to Section 13. Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a lidded container for disposal or recovery. Containers must not be punctured or destroyed by burning, even when empty.

6.4 Reference to other sections

See Also Section 8, 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurised container - Do not pierce or burn, even after use. Avoid breathing mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Avoid contact with skin and eyes.

7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight.

Do not expose to temperatures exceeding 50°C/ 122°F. Storage temperature

Storage life Stable under normal conditions. None known.

Incompatible materials

7.3 Specific end use(s)

Glue from spray

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 Occupational Exposure Limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA	LTEL (8 hr TWA	STEL	STEL	Note
		ppm)	mg/m³)	(ppm)	(mg/m³)	
Methyl acetate	79-20-9	200	606	250	757	ACGIH TLV
Methyl acetate	79-20-9	200		250		OSHA PEL
Methyl acetate	79-20-9	200	610	250	760	NIOSH REL Z-1
Methyl acetate	79-20-9	200	610			OSHA PEL Z-1
Cyclohexane	110-82-7	100	344			ACGIH TLV
Cyclohexane	110-82-7	300				OSHA PEL
Cyclohexane	110-82-7	300	1050			NIOSH REL Z-1
Cyclohexane	110-82-7	300	1050			OSHA PEL Z-1
Pentane, all isomers	109-66-0	1000	2950			ACGIH TLV
Pentane	109-66-0	600				OSHA PEL
Pentane	109-66-0	120	350	610	1800	NIOSH REL Z-1, C1, ST [15min]
Pentane, all isomers	109-66-0	1000	2950			OSHA PEL Z-1
Propyl acetate isomers	109-60-4	100	417	150	626	ACGIH TLV
n-Propyl acetate	109-60-4	200		250		OSHA PEL
n-Propyl acetate	109-60-4	200	840	250	1050	NIOSH REL Z-1
n-Propyl acetate	109-60-4	200	840			OSHA PEL Z-1
Cyclopentane	287-92-3	1000				ACGIH TLV, EX
Cyclopentane	287-92-3	600	1720			NIOSH REL Z-1

Page: 3 - 9 Revision: 1



Pentane, all isomers	78-78-4	1000	2950		ACGIH TLV
Pentane, all isomers	78-78-4	1000	2950		OSHA PEL Z-1

ACGIH TLV

OSHA PEL NIOSH REL Z-1

The American Conference of Governmental Industrial Hygienists (ACGIH®) Threshold Limit Values (TLVs®), 2022
Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs), 2019
National Institute for Occupational Safety and Health (NIOSH) Recommended Exposure Limits (RELs) from the NIOSH Pocket Guide to Chemical Hazards table Z-1: Up to 10-hour time weighted average (TWA) during a 40-hour work week, 2022
Occupational Safety and Health Administration (OSHA) Permissible Exposure Limit (PEL) from 29 CFR 1910.1000 Z-1 Table, 2022
Calling limit of Short temp Exposure Limit

OSHA PEL Z-1

Ceiling limit of Short-term Exposure Limit
Short Term Exposure Limit with 15min duration ST [15min] EX

Explosion hazard: the substance is a flammable asphyxiant or exursions above the TLV could approach 10% of the lower explosive limit.

Biological Exposure Indices							
Substances	CAS Number	Sampling	Tissues		Biological monitoring guidance value	Comments	
Cyclohexane		End of shift, end of workweek	urine	1,2-Cyclohexanediol	50 mg/g creatinine	Ns, *	

Remark Notes with hydrolysis Ns Nonspecific

8.2 Exposure controls

8.2.1. Appropriate engineering controls Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems.

8.2.2. Personal protection equipment

Eye Protection Wear goggles giving complete eye protection.



Skin protection Wear protective clothing and gloves: Impervious gloves.

Breakthrough time of the glove material: refer to the information provided by the

gloves' producer.



Respiratory protection Normally no personal respiratory protection is necessary. Wear suitable respiratory

protective equipment if exposure to high levels of material are likely.



Thermal hazards Not applicable.

8.2.3. Environmental Exposure Controls Do not release large quantities into the surface water or into drains.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance Aerosol Color: Clear. Odor Characteristic. Odor threshold Not known. Not known. Melting point/freezing point Not known. Initial boiling point and boiling range Not applicable. Flash Point Not applicable. Evaporation rate Not known. Not applicable. Flammability (solid, gas) Upper/lower flammability or explosive Not known.

limits

Vapor pressure Not known. Vapor density Not known. Density (g/ml) Not applicable. Relative density Not applicable.

> Page: 4 - 9 Revision: 1



Solubility(ies) Solubility (Water): Insoluble. Solubility (Other): Not known.

Partition coefficient: n-octanol/water
Auto-ignition temperature
Decomposition Temperature (°C)
Viscosity
Not known.
Not oxidising.

9.2 Other information

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

Stable under normal conditions.

10.2 Chemical Stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose.

10.4 Conditions to avoid

Keep away from heat and direct sunlight.

10.5 Incompatible materials

Not known.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity - Ingestion Calculation method : Low oral toxicity.

Calculation method: Calculated acute toxicity estimate (ATE) Calc ATE -

1000000.00000

Acute toxicity - Skin Contact Calculation method : Low acute toxicity.

Calculation method : Calculated acute toxicity estimate (ATE) Calc ATE -

1000000.00000

Acute toxicity - Inhalation Calculation method : Low acute toxicity.

Calculation method : Calculated acute toxicity estimate (ATE) Calc ATE -

2521.01000

Skin corrosion/irritation Calculation method : Non-irritant.

Serious eye damage/irritation

Calculation method : Causes serious eye irritation. No data.

Skin sensitization data

Calculation method : May cause an allergic skin reaction. No data.

Germ cell mutagenicity

Calculation method : May cause genetic defects. No data.

Calculation method : May cause cancer. No data.

Calculation method : No evidence of reproductive effects.

Lactation Calculation method : Not classified.

STOT - single exposure Calculation method : May cause drowsiness or dizziness. No data.

STOT - repeated exposure Calculation method : None anticipated.
Aspiration hazard Calculation method : Not classified.

11.2 Other information

Not known.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Toxicity - Aquatic invertebrates Not known.

Toxicity - Fish Not known.

Toxicity - Algae Not known.

Toxicity - Sediment Compartment Not classified.

Toxicity - Terrestrial Compartment Not classified.

12.2 Persistence and degradability

No information on this formulation.

12.3 Bioaccumulative potential

No information on this formulation.

12.4 Mobility in soil

Page: 5 - 9 Revision: 1



Mixture: Insoluble in water. The product is predicted to have low mobility in soil.

12.5 Other adverse effects

Not known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Recycle only completely emptied packaging. Containers must not be punctured or destroyed by burning, even when empty. Non-emptied aerosol: Dispose of wastes in

an approved waste disposal facility.

13.2 Additional Information

Disposal should be in accordance with local, state or national legislation.

SECTION 14: TRANSPORT INFORMATION

14.1 UN number

UN No. 1950

14.2 UN proper shipping name

UN proper shipping name AEROSOLS

14.3 Transport hazard class(es)

ADR/RID

ADR/RID Class 2
ADR Classification Code 5F

Special Provisions 190, 327, 344, 625

Limited Quantities 1 L
Excepted Quantities E0

Emergency Action Code

Mixed Packing Instructions for Packages P207 LP200 Special Packing Provisions for Packages PP87 RR6 L2 Mixed Packing Instructions for Packages MP9

Packing Instructions for Portable Tanks

Special Provisions for Portable Tanks

Tank Code for Tanks

Special Provisions for Tanks Vehicle for Tank Carriage

ADR Transport Category 2
Tunnel Restriction Code D
Special Provisions for Carriage - V1

Packages

Special Provisions for Carriage - Bulk

Special Provisions for Carriage - Loading, CV9 CV12

Unloading and Handling

Special Provisions for Carriage - S2

Operation ADR HIN IMDG

IMDG Class

Special Provisions 190, 327, 344, 625

Limited Quantities 1 L
Excepted Quantities E0

Mixed Packing Instructions for Packages P207 LP200 Special Packing Provisions for Packages PP87 RR6 L2

Packing Instructions for Portable Tanks

Special Provisions for Portable Tanks

IMDG EMS F-D, S-U Stowage and Handling SW1 SW22 Segregation SG69

Marine Pollutant

IATA Proper Shipping Name AEROSOLS

Excepted Quantities E0

Passenger and Cargo Aircraft Limited

Quantities Packing Instructions

Y203

Page: 6 - 9 Revision: 1



Passenger and Cargo Aircraft Limited 30Kg

Quantities Max net Qty

Passenger and Cargo Aircraft Packing 203

Instructions

Passenger and Cargo Aircraft Max net 75Kg

Qty

Cargo Aircraft Packing Instructions 203 Cargo Aircraft Max net Qty 150Kg

Special Provisions A145, A167, A802

Emergency Response Guidebook (ERG) 10L

Code

Labels Labels



Classified as a Marine Pollutant.

14.4 Packing group

Packing group None

14.5 Environmental hazards

Environmental hazards

14.6 Special precautions for user

Special precautions for user

Not known.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No information available

SECTION 15: REGULATORY INFORMATION

15.1 US Federal Regulations

Listed: 79-20-9, 110-82-7, 109-66-0, 109-60-4 Toxic and hazardous substances (29

CFR 1910; Subpart Z)

National emission standards for Not listed

hazardous air pollutants (40 CFR 61.01)

SARA Title III Section 313 Not listed

TSCA (Toxic Substance Control Act) Listed: 79-20-9 (Active), 110-82-7 (Active), 98-56-6 (Active), 109-66-0 (Active), 109-

60-4 (Active), 1675-54-3 (Active), 287-92-3 (Active), 78-78-4 (Active), 68476-86-8

(Active)

CAA 602 - Ozone Depleting Substances Not listed

15.2 US State Regulations State Right to Know Lists

Proposition 65 (California) Listed: 98-56-6

Massachusetts Not listed

Listed: 79-20-9, 110-82-7, 109-66-0, 109-60-4, 287-92-3 Minnesota

New Jersey Listed: 79-20-9, 110-82-7, 109-66-0, 109-60-4, 287-92-3, 78-78-4 Pennsylvania Listed: 79-20-9, 110-82-7, 109-66-0, 109-60-4, 287-92-3, 78-78-4

Rhode Island Listed: 79-20-9, 110-82-7, 109-66-0, 109-60-4, 287-92-3

15.3 Other OSPAR List of Chemicals for Priority Not listed

Action

OSHA (List of Highly Hazardous Not listed

Chemicals, Toxics and Reactives)

NTP (National Toxicology Program) Not listed IARC (International Agency for Research Listed: 1675-54-3

on Cancer)

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements:

1-16



LEGEND

Hazard Pictogram(s)

Hazard classification

Hazard Statement(s)

Precautionary Statement(s)







GHS04: GHS: Gas cylinder GHS05: GHS: Corrosion

GHS06: GHS: Skull and crossbones Flam. Gas 1: Flammable gas, Category 1

Flammable aerosol 1: Flammable aerosol, Category 1

Flam. Liq. 1: Flammable liquid, Category 1 Flam. Liq. 2: Flammable liquid, Category 2 Flam. Liq. 3: Flammable liquid, Category 3

Press. Gas: Gases under pressure Asp. Tox. 1: Aspiration hazard, Category 1

Skin Irrit. 2: Skin corrosion/irritation, Category 2 Skin Sens. 1: Skin sensitization, Category 1 Skin Sens. 1B: Skin sensitization, Category 1B

Eye Irrit. 2A: Serious eye damage/irritation, Category 2A

STOT SE 3: Specific target organ toxicity — single exposure, Category 3

H220: Extremely flammable gas. H222: Extremely flammable aerosol

H224: Extremely flammable liquid and vapor. H225: Highly flammable liquid and vapor.

H226: Flammable liquid and vapor.

H280: Contains gas under pressure; may explode if heated.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Pressurised container - Do not pierce or burn, even after use.

P261: Avoid breathing mist/vapors/spray.

P264: Wash hands and exposed skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTER/doctor if you feel unwell.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F

P333+P313: If skin irritation or rash occurs: Get medical advice/attention. P337+P313: If eye irritation persists: Get medical advice/attention. P362+P364: Take off contaminated clothing and wash it before reuse.

Page: 8 - 9 Revision: 1



P501: Dispose of contents in accordance with local, state or national legislation.

Acronyms

ADN: European Agreement concerning the International Carriage of Dangerous

Goods by Inland Waterways

ADR: European Agreement concerning the International Carriage of Dangerous

Goods by Road

ATE: Acute Toxicity Estimate CAS: Chemical Abstracts Service

IATA: International Air Transport Association

IBC : Intermediate Bulk Container

ICAO: International Civil Aviation Organization IMDG : International Maritime Dangerous Goods LTEL : Long term exposure limit

RID : Regulations concerning the International Carriage of Dangerous Goods by Rail

STEL: Short term exposure limit STOT: Specific Target Organ Toxicity

UN: United Nations

Key literature references and sources for US CFR 1910.1200 data used to compile the SDS

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. The Gorilla Glue Company gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. The Gorilla Glue Company accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

> Page: 9 - 9 Revision: 1