

Product Safety Information Sheet

General environmental and safety information for consumers

1. Product and Company Identification

- 1.1 *Identification of the preparation* C6615 series No. 15 black ink.
- Company undertaking identification
 Hewlett-Packard Company
 1000 NE Circle Boulevard
 Corvallis OR 97330-4239
 USA
- 1.3 Emergency telephone number
 Hewlett-Packard Health Effects Line
 1-800-457-4209 (USA and Canada) or
 Intl +1-503-494-7199 (all other areas)
- 1.4 General information telephone number 1-208-323-2551 (USA and Canada) Intl +1-208-323-2551 (all other areas)

Hazard rating	NFPA/HMIS
Health	1
Flammability	2
Instability/Reactivity	0
Special	none

2. Composition/information on ingredients

This ink cartridge contains an aqueous ink formulation.

Component	CAS No.	% by weight	Workplace Limits (PEL, TLV)
carbon black	1333-86-4	<5	not established
isopropyl alcohol	67-63-0	<3	400 ppm(983 mg/m³) OSHA PEL and NIOSH TLV¹
2-pyrrolidone	616-45-5	<10	not established
trade secret materials	not specified	<10	not established
water	7732-18-5	balance	not established

¹ NIOSH also applies a 2000 ppm IDLH (immediately dangerous to life or health) and 500 ppm (1225 mg/m³) short term exposure limit to isopropyl alcohol.



Product Safety Information Sheet C6615 Series – No. 15 Black

3. Hazards Identification

3.1 *Primary Routes of Exposure* skin, eye, oral, and inhalation

3.2 Acute Health Hazards

Skin: May cause slight skin irritation characterized by redness and swelling after

prolonged contact. Indications may be masked by color of ink.

Eye: May be mildly irritating.

Oral: May cause stomach upset after ingestion.

Inhalation: Prolonged inhalation may result in irritation to the respiratory tract.

3.3 Chronic Health Hazards

None noted

3.4 Carcinogenicity

Carbon Black has been classified by the International Agency for Research on Cancer (IARC) as Group 2B (possible human carcinogen). Neither this component nor the other ingredients have been classified as carcinogens according to ACGIH, EPA, EU, MAK and OSHA criteria. According to IARC, printing inks are not classifiable as to their carcinogenicity to humans (Group 3).

4. First Aid Measures

4.1 Emergency First Aid Procedures

Call the HEWLETT-PACKARD HEALTH EFFECTS LINE at 1-800-457-4209 (Intl + 1-503-494-7199 outside USA and Canada).

First aid for skin

Wash affected areas thoroughly with soap and water. Clothing should be laundered before reuse. **Seek medical attention if skin irritation persists.**

First aid for eyes

Contact with eyes may cause mild irritation. Immediately flush with large amounts of clean, lukewarm water (low pressure) for at least 15 minutes. **Seek medical attention if eye irritation persists.**

First aid for ingestion

Ingestion of ink may cause stomach upset. Seek medical advice and then call the HEWLETT-PACKARD HEALTH EFFECTS LINE. **Seek medical attention if stomach upset persists.**

First aid for inhalation

Remove to fresh air.



Product Safety Information Sheet C6615 Series – No. 15 Black

5. Fire Fighting Measures

Flash point:	Autoignition temperature:
approximately 129°F -135°F. No ignition,	not determined
sustained combustion or flashing in the	
Sustained Combustibility Test (method in US	
49CFR173, Appendix H).	
Extinguishing media:	Special fire fighting procedures:
water, dry chemical, carbon dioxide, foam	none
Unusual fire and explosion hazards:	
no special hazards known	

6. Accidental release measures

Spill or Leak Procedures

No special procedures are indicated. Use absorbent towels to wipe up ink. Rinse area with damp cloth to remove remaining traces of ink.

7. Handling and storage

No special handling or storage required.

KEEP OUT OF THE REACH OF CHILDREN

Storage temperature: -40° – 70 °C	Shelf life: 1 year
Handling and storage precautions: do not use inkjet	Special sensitivity: none
cartridge when frozen. Ensure inkjet cartridge exterior is dry	
before inserting into printer.	

8. Exposure control / personal protection

No special eye or skin protection is needed for cleanup of spills. Standard eye and skin protection for laboratory chemical safety is required.

9. Physical and chemical properties

Appearance: black liquid	Physical state: liquid at room temperature
pH: 7.8 - 8.4	Solvent content: <20%
Solubility in water: soluble	Vapor density: >1 (air = 1.0)
Odor: not applicable	Vapor pressure: not applicable

6 July 2000 Page 3 of 4



Product Safety Information Sheet C6615 Series – No. 15 Black

10. Stability and reactivity

Stability: stable under normal storage conditions	Thermal decomposition products: Oxides of carbon/nitrogen, water
Incompatibilities: strong oxidizers	Hazardous polymerization: none

11. Toxicological information

Refer to sections 3. Hazards Identification and 4. First Aid Measures

12. Ecological information

This ink complies with the requirements for the German Blue Angel Environmental Certification for printers.

13. Disposal considerations

Dispose in accordance with all applicable federal, state and local laws

14. Transport information

Not a regulated article under DOT, IATA, ADR or RID.

15. Regulatory information

According to EU Directive 88/379/EEC, this product is not classified as dangerous and therefore no hazard label is required. For other countries, including the USA, no product label would be required.

TSCA Inventory: all components are listed.

TSCA Section 12(b) Export Notification required for Isopropyl alcohol (67-63-0), traces of tetrahydrofuran (CAS No: 109-99-9) and traces of triethylene glycol monoethyl ether (CAS No: 112-50-5)

16. Other Information

Date revised: 6 July 2000 Supersedes: March 30, 2000.

Sections revised: Section 2.0, 5.0 and 15.0

DISCLAIMER: This Product Safety Information Sheet is offered without charge to the customers of Hewlett-Packard. Data is the most current known to Hewlett-Packard at the time of preparation and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application.