

Transport Information Document

Date: May 13, 2019

3M ID Number: 70-0711-2641-4

Product Description: 3M(TM) Quat Disinfectant Cleaner Concentrate 5L, Black Cap, 2 Liter, 6/case

Transport Protective Service: PROTECTIVE SERVICE NOT REQUIRED

NMFC Item: 057100 NMFC Sub: 03 NMFC Class: 060.0

Flash Point (Closed-cup): No Flash Point

UNITED STATES DEPARTMENT	OF TRANSPORTATION - GRO	UND (U.S. DOT, 49 CFR)

LIMITED QUANTITY

UNITED STATES DEPARTMENT OF TRANSPORTATION - VESSEL (U.S. DOT, 49 CFR)

UN1903, DISINFECTANT, LIQUID, CORROSIVE, N.O.S., (BENZYL-C12-16-ALKYLDIMETHYL AMMONIUM CHLORIDES, SODIUM METASILICATE), 8, III, LIMITED QUANTITY

INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA)

UN1903, DISINFECTANT, LIQUID, CORROSIVE, N.O.S., (BENZYL-C12-16-ALKYLDIMETHYL AMMONIUM CHLORIDES, SODIUM METASILICATE), 8, III

INTERNATIONAL MARITIME ORGANIZATION (IMO)

UN1903, DISINFECTANT, LIQUID, CORROSIVE, N.O.S., (BENZYL-C12-16-ALKYLDIMETHYL AMMONIUM CHLORIDES, SODIUM METASILICATE), 8, III, LIMITED QUANTITY

The classification is authorized by the Competent Authority of the United States of America and may not meet the requirements of other competent authorities.

These transportation classifications are provided as a customer service. AS THE SHIPPER YOU REMAIN RESPONSIBLE FOR COMPLYING WITH ALL THE APPLICABLE LAWS AND REGULATIONS, INCLUDING PROPER TRANSPORTATION CLASSIFICATION AND PACKAGING. 3M's transportation classifications are based on product formulations, packaging, 3M policies and 3M's understanding of applicable current regulations and is valid for the original 3M package only. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and NOT THE PACKAGING, LABELING, OR MARKING REQUIREMENTS. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.



Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 17-9553-3
 Version Number:
 9.00

 Issue Date:
 05/21/18
 Supercedes Date:
 01/11/18

SECTION 1: Identification

1.1. Product identifier

3MTM Quat Disinfectant Cleaner Concentrate (Product No. 5, 3M(TM) Chemical Management Systems)

Product Identification Numbers

61-0000-6327-3, 61-0000-6328-1, 61-0000-6368-7, 61-0000-6369-5, 61-0000-6421-4, 70-0711-2639-8, 70-0711-2640-6, 70-0711-2641-4, 70-0711-2642-2, 70-0716-5990-1, 70-0716-6111-3

1.2. Recommended use and restrictions on use

Recommended use

Disinfectant, EPA-registered, quaternary disinfectant cleaner for use in hospitals.

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Commercial Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Corrosive to metal: Category 1. Flammable Liquid: Category 3. Acute Toxicity (oral): Category 4.

Serious Eye Damage/Irritation: Category 1. Skin Corrosion/Irritation: Category 1B. Reproductive Toxicity: Category 2.

2.2. Label elements

Signal word

Page 1 of 12

Danger

Symbols

Flame | Corrosion | Exclamation mark | Health Hazard |

Pictograms



Hazard Statements

May be corrosive to metals. Flammable liquid and vapor.

Harmful if swallowed.

Causes severe skin burns and eye damage.

Suspected of damaging fertility or the unborn child.

Precautionary Statements

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Keep container tightly closed.

Keep only in original container.

Use explosion-proof electrical/ventilating/lighting equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves, protective clothing, and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

Wash contaminated clothing before reuse.

Rinse mouth.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Absorb spillage to prevent material damage.

Storage:

Store in a corrosive resistant container with a resistant inner liner.

Store in a well-ventilated place. Keep cool.

Store locked up.

Page 2 of 12

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

May cause chemical gastrointestinal burns.

7% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
WATER	7732-18-5	60 - 90 Trade Secret *
BENZYL-C12-16-ALKYL DIMETHYL AMMONIUM CHLORIDES	68424-85-1	8.680
OCTYLDECYLDIMETHYLAMMONIUM CHLORIDE	32426-11-2	6.510
ETHOXYLATED C12-C15 ALCOHOLS	68131-39-5	5 - 10 Trade Secret *
ETHYL ALCOHOL	64-17-5	1 - 5 Trade Secret *
DIDECYLDIMETHYLAMMONIUM CHLORIDE	7173-51-5	3.906
EDTA TETRASODIUM SALT	64-02-8	1 - 5 Trade Secret *
DIOCTYL DIMETHYL AMMONIUM CHLORIDE	5538-94-3	2.604
SODIUM METASILICATE	6834-92-0	1 - 5 Trade Secret *

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eve Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Page 3 of 12

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam designed for use on solvents, such as alcohols and acetone, that can dissolve in water. An AR - AFFF type foam is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for use in transportation by appropriate authorities. The container must be lined with polyethylene plastic or contain a plastic drum liner made of polyethylene. Clean up residue with water. Cover, but do not seal for 48 hours. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. This product is not intended to be used without prior dilution as specified on the product label. Grounding or safety shoes with electrostatic dissipating soles (ESD) are not required with a chemical dispensing system. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Keep away from reactive metals (eg. Aluminum, zinc etc.) to avoid the formation of hydrogen gas that could create an explosion hazard. Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Keep only in original container. Store in a corrosive resistant container with a resistant inner liner. Store away from acids. Store away from oxidizing agents.

Page 4 of 12

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
ETHYL ALCOHOL	64-17-5	ACGIH	STEL:1000 ppm	A3: Confirmed animal
				carcin.
ETHYL ALCOHOL	64-17-5	OSHA	TWA:1900 mg/m3(1000 ppm)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

NOTE: When used with a chemical dispensing system as directed, special ventilation is not required.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

NOTE: When used with a chemical dispensing system as directed, eye contact with the concentrate is not expected to occur. If the product is not used with a chemical dispensing system or if there is an accidental release, wear protective eye/face protection. Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

NOTE: When used with a chemical dispensing system as directed, skin contact with the concentrate is not expected to occur. If product is not used with a chemical dispensing system or if there is an accidental release:

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary.

If product is not used with a chemical dispensing system or if there is an accidental release:

Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended:

Apron - polymer laminate

Boots - Rubber

Respiratory protection

Page 5 of 12

NOTE: When used with a chemical dispensing system as directed, respiratory protection is not required.

If product is not used with a chemical dispensing system or if there is an accidental release:

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:

Specific Physical Form:

Liquid

Liquid

Odor, Color, Grade: Opalescent green liquid with pleasant fragrance.

Odor threshold No Data Available

pHMelting point12.2 - 13.2No Data Available

Boiling Point > 212 °F

Flash Point 124.99 °F [Test Method: Tagliabue Closed Cup] [Details: Does not

sustain combustion according to ASTM 4206]

Evaporation rate

Flammability (solid, gas)

Flammable Limits(LEL)

Flammable Limits(UEL)

Vapor Pressure

Vapor Density

No Data Available

Specific Gravity 1.001 - 1.009 [Ref Std:WATER=1]

Solubility in Water Complete

Solubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNo Data AvailableDecomposition temperatureNo Data AvailableViscosity17.3 - 22.5 sec

Volatile Organic Compounds 3 - 7 % weight [Test Method: calculated per CARB title 2]

Percent volatile < 70 % weight

VOC Less H2O & Exempt Solvents 100 - 140 g/l [Test Method: calculated per CARB title 2]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Not determined

Page 6 of 12

10.5. Incompatible materials

Strong acids

10.6. Hazardous decomposition products

SubstanceConditionCarbon monoxideNot SpecifiedCarbon dioxideNot SpecifiedOxides of NitrogenNot Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

May be harmful in contact with skin.

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Eve Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Harmful if swallowed. Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Additional Information:

This product contains ethanol. Alcoholic beverages and ethanol in alcoholic beverages have been classified by the International Agency for Research on Cancer as carcinogenic to humans. There are also data associating human consumption of alcoholic beverages with developmental toxicity and liver toxicity. Exposure to ethanol during the

Page 7 of 12

foreseeable use of this product is not expected to cause cancer, developmental toxicity, or liver toxicity.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE2,000 - 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE300 - 2,000 mg/kg
BENZYL-C12-16-ALKYL DIMETHYL AMMONIUM CHLORIDES	Dermal	Rabbit	LD50 645 mg/kg
BENZYL-C12-16-ALKYL DIMETHYL AMMONIUM CHLORIDES	Ingestion	Rat	LD50 366 mg/kg
OCTYLDECYLDIMETHYLAMMONIUM CHLORIDE	Dermal		LD50 estimated to be > 5,000 mg/kg
OCTYLDECYLDIMETHYLAMMONIUM CHLORIDE	Ingestion	Rat	LD50 > 5,000 mg/kg
ETHOXYLATED C12-C15 ALCOHOLS	Dermal	Rat	LD50 5,000 mg/kg
ETHOXYLATED C12-C15 ALCOHOLS	Ingestion	Rat	LD50 1,200 mg/kg
ETHYL ALCOHOL	Dermal	Rabbit	LD50 > 15,800 mg/kg
ETHYL ALCOHOL	Inhalation-	Rat	LC50 124.7 mg/l
	Vapor (4		
	hours)		
ETHYL ALCOHOL	Ingestion	Rat	LD50 17,800 mg/kg
DIDECYLDIMETHYLAMMONIUM CHLORIDE	Ingestion	Rat	LD50 84 mg/kg
EDTA TETRASODIUM SALT	Ingestion	Rat	LD50 1,658 mg/kg
DIOCTYL DIMETHYL AMMONIUM CHLORIDE	Ingestion	Mouse	LD50 > 50 mg/kg
DIOCTYL DIMETHYL AMMONIUM CHLORIDE	Dermal	Rabbit	LD50 259 mg/kg
SODIUM METASILICATE	Dermal	Rabbit	LD50 > 4,640 mg/kg
SODIUM METASILICATE	Ingestion	Rat	LD50 500 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	In vitro data	Corrosive
ETHYL ALCOHOL	Rabbit	No significant irritation
SODIUM METASILICATE	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	similar	Corrosive
	health	
	hazards	
ETHOXYLATED C12-C15 ALCOHOLS	Not	Corrosive
	available	
ETHYL ALCOHOL	Rabbit	Severe irritant
SODIUM METASILICATE	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
ETHYL ALCOHOL	Human	Not classified
SODIUM METASILICATE	Mouse	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value

Page 8 of 12

05	/21	/18	

ETHYL ALCOHOL	In Vitro	Some positive data exist, but the data are not sufficient for classification
ETHYL ALCOHOL	In vivo	Some positive data exist, but the data are not sufficient for classification
SODIUM METASILICATE	In Vitro	Not mutagenic
SODIUM METASILICATE	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
ETHYL ALCOHOL	Ingestion	Multiple	Some positive data exist, but the data are not
		animal	sufficient for classification
		species	

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure
					Duration
ETHYL ALCOHOL	Inhalation	Not classified for development	Rat	NOAEL 38 mg/l	during gestation
ETHYL ALCOHOL	Ingestion	Not classified for development	Rat	NOAEL 5,200 mg/kg/day	premating & during gestation
SODIUM METASILICATE	Ingestion	Not classified for development	Mouse	NOAEL 200 mg/kg/day	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
ETHYL ALCOHOL	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	LOAEL 2.6 mg/l	30 minutes
ETHYL ALCOHOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	LOAEL 9.4 mg/l	not available
ETHYL ALCOHOL	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL not available	
ETHYL ALCOHOL	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg	
SODIUM METASILICATE	Inhalation	respiratory irritation	May cause respiratory irritation	official classifica tion	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
ETHYL ALCOHOL	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 124 mg/l	365 days
ETHYL ALCOHOL	Inhalation	hematopoietic system immune system	Not classified	Rat	NOAEL 25 mg/l	14 days
ETHYL ALCOHOL	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 8,000 mg/kg/day	4 months
ETHYL ALCOHOL	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg/day	7 days
SODIUM METASILICATE	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Dog	LOAEL 2,400 mg/kg/day	4 weeks

Page 9 of 12

SODIUM	Ingestion	endocrine system	Not classified	Rat	NOAEL 804	3 months
METASILICATE		blood			mg/kg/day	
SODIUM	Ingestion	heart liver	Not classified	Rat	NOAEL	8 weeks
METASILICATE					1,259	
					mg/kg/day	

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

A 3M Product Environmental Data Sheet (PED) is available.

Chemical fate information

A 3M Product Environmental Data Sheet (PED) is available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable), D002 (Corrosive), D018 (Benzene)

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501

SECTION 15: Regulatory information

15.1. US Federal Regulations

EPCRA 311/312 Hazard Classifications:

El CRA 511/512 Hazaru Classifications.			
Physical Hazards			
Corrosive to metal			
Flammable (gases, aerosols, liquids, or solids)			

Health Hazards	
Acute toxicity	
Hazard Not Otherwise Classified (HNOC)	

05/21/18

Reproductive toxicity

Serious eye damage or eye irritation

Skin Corrosion or Irritation

FIFRA

Status Registered

Registration Number

6836-78-10350

This chemical is a pesticide product registered by the United States Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-pesticide chemicals. The hazard information required on the pesticide label is reproduced below. The pesticide label also includes other important information, including directions for use.

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER. Corrosive. Causes irreversible eye damage and skin burns.

Do not get in eyes, on skin, or on clothing. Wear protective eyewear (goggles, face shield or safety glasses), protective clothing and protective (rubber

or chemical resistant) gloves. Harmful if swallowed and/or if absorbed through the skin. Wash thoroughly with soap and water after handling and

before eating, drinking, chewing gum, using tobacco or using the toilet. Remove contaminated clothing and wash clothing before reuse.

FIRST AID IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5

minutes, then continue rinsing eye. IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20

minutes. IF SWALLOWED: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to

swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Call a poison control center or doctor for treatment

advice. Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment. STORAGE AND DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Pesticide Storage: Open dumping is prohibited. Store in

original container in areas inaccessible to children. Pesticide Disposal: Pesticide wastes are acutely hazardous. Improper disposal of excess

pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact

your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Container Disposal: Nonrefillable container. Do not reuse or refill this container. Wrap empty container and put in trash.

15.2. State Regulations

15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain

restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

This product complies with the New Zealand Hazardous Substances and New Organisms Act (1996).

15.4. International Regulations

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 Flammability: 2 Instability: 0 Special Hazards: None

Corrosive: Yes

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 3 Flammability: 2 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

 Document Group:
 17-9553-3
 Version Number:
 9.00

 Issue Date:
 05/21/18
 Supercedes Date:
 01/11/18

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3Mproduct is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

3M USA SDSs are available at www.3M.com

Page 12 of 12