

SDS Revision Date: 12/20/2014

# 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity Clean N Disinfect, Aerosol Cleaner/Disinfectant

Alternate Names CAGE Code: 0FTT5

LHB Part Number: 0204---000

National Stock Number: 7930-01-513-9967

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended useSee Technical Data Sheet.Application MethodSee Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name LHB Industries

8833 Fleischer Place Berkeley, MO 63134

**Emergency** 

24 hour Emergency Telephone No. (800) 633-8253 (PERS)

Customer Service: LHB Industries (314) 423-4333

# 2. Hazard identification of the product

#### 2.1. Classification of the substance or mixture

Press. Gas;H280 Contains gas under pressure; may explode if heated.

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



H280 Contains gas under pressure; may explode if heated.

**SDS Revision Date:** 



12/20/2014

[Prevention]:

No GHS prevention statements

[Response]:

No GHS response statements

[Storage]:

P410+403 Protect from sunlight. Store in a well ventilated place.

[Disposal]:

No GHS disposal statements

## 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Butyl diglycol CAS Number: 0000112-34-5	1.0 - 10	Eye Irrit. 2;H319	[1]
Propane, 2-methyl- CAS Number: 0000075-28-5	1.0 - 10	Flam. Gas 1;H220 Press. Gas;H280	[1][2]
Butane CAS Number: 0000106-97-8	1.0 - 10	Flam. Gas 1;H220 Press. Gas;H280	[1][2]
Propane CAS Number: 0000074-98-6	1.0 - 10	Flam. Gas 1;H220 Press. Gas;H280	[1][2]

- [1] Substance classified with a health or environmental hazard.
- [2] Substance with a workplace exposure limit.

## 4. First aid measures

### 4.1. Description of first aid measures

General Move victim to fresh air.

Call 911 or emergency medical service if deemed necessary.

Give artificial respiration if victim is not breathing.

Administer oxygen if breathing is difficult.

Remove and isolate contaminated clothing and shoes.

In case of contact with liquefied gas, thaw frosted parts with lukewarm water.

Keep victim warm and quiet.

Ensure that medical personnel are aware of the material(s) involved and take precautions

to protect themselves.

<sup>[3]</sup> PBT-substance or vPvB-substance.
\*The full texts of the phrases are shown in Section 16.

LIGHTHOUSE for the BLIND ST. LOUIS, MO.

SDS Revision Date: 12/20/2014

**Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give

artificial respiration. If unconscious place in the recovery position and obtain immediate

medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and

seek medical attention.

**Skin** Remove and isolate contaminated clothing and shoes. Clothing frozen to the skin should

be thawed before being removed. In case of contact with liquefied gas, thaw frosted parts

with lukewarm water.

**Induce** vomiting if conscious. Never give anything by mouth to an unconscious person.

Consult physician.

#### 4.2. Most important symptoms and effects, both acute and delayed

Overview ROUTES OF EXPOSURE: Exposure may be by INGESTION, INHALATION and/or SKIN

or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment. EFFECTS OF OVEREXPOSURE: Irritation of eyes, skin and upper respiratory system. SIGNS AND SYMPTOMS OF OVEREXPOSURE: Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness

and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGRAVATED BY EXPOSURE: Pre-existing respiratory, skin, eye,

liver, kidney and lymphatic disorders. See section 2 for further details.

## 5. Fire-fighting measures

#### 5.1. Extinguishing media

**Fire involving Tanks:** Some of these materials, if spilled, may evaporate leaving a flammable residue. Some of these materials, if spilled, may evaporate leaving a flammable residue.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: CO and CO2

#### 5.3. Advice for fire-fighters

Wear positive pressure self-contained breathing apparatus (SCBA).

Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Structural firefighters' protective clothing will only provide limited protection.

Some may burn but none ignite readily.

Containers may explode when heated.

Ruptured cylinders may rocket.

Vapors may cause dizziness or asphyxiation without warning.

Vapors from liquefied gas are initially heavier than air and spread along ground.

Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite.

Fire may produce irritating, corrosive and/or toxic gases.

ERG Guide No. 126

LIGHTHOUSE for the BLIND ST. LOUIS, MO.

SDS Revision Date: 12/20/2014

### 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Do not touch or walk through spilled material.

Stop leak if you can do it without risk.

Do not direct water at spill or source of leak.

Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material. If possible, turn leaking containers so that gas escapes rather than liquid.

Prevent entry into waterways, sewers, basements or confined areas.

Allow substance to evaporate.

Ventilate the area.

#### 6.2. Environmental precautions

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

#### 6.3. Methods and material for containment and cleaning up

Wipe, scrape or soak up contents in an inert material. Pick up spill for recovery or disposal and place in a closed container

## 7. Handling and storage

### 7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

#### 7.2. Conditions for safe storage, including any incompatibilities

Keep out of reach of children. Do not take internally. Do not consume food, drink or smoke while handling this product.

Keep from freezing. Avoid storage in high temperatures or near open flame. Store in dry cool place.

Incompatible materials: Any acidic material, ammonia, urea, oxidizable materials and metals such as nickel, copper, tin, aluminum and iron.

CATEGORY - NFPA 30B Level 1 Aerosol

Do not store where temperatures may exceed 120°F (48.9°C).

See section 2 for further details. - [Storage]:

#### 7.3. Specific end use(s)

No data available.



SDS Revision Date: 12/20/2014

# 8. Exposure controls and personal protection

## 8.1. Control parameters

## **Exposure**

CAS No.	Ingredient	Source	Value
0000074-98-6 Propane		OSHA	TWA 1000 ppm (1800 mg/m3)
		ACGIH	Ensure Minimal Oxygen Content (ACGIH appendix F)
		NIOSH	TWA 1000 ppm (1800 mg/m3)
		Supplier	No Established Limit
0000075-28-5	Propane, 2-methyl-	OSHA	No Established Limit
		ACGIH	STEL: 1000ppm
		NIOSH	TWA 800 ppm (1900 mg/m3)
	Supplier	No Established Limit	
0000106-97-8 Butane		OSHA	No Established Limit
		ACGIH	TWA: 600 ppm STEL: 750 ppm
		NIOSH	TWA 800 ppm (1900 mg/m3)
		Supplier	No Established Limit
0000112-34-5	Butyl diglycol	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

## **Carcinogen Data**

CAS No.	Ingredient	Source	Value		
0000074-98-6 Propane		OSHA	Select Carcinogen: No		
			Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
		OSHA	Select Carcinogen: No		
		NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
0000106-97-8	Butane	OSHA	Select Carcinogen: No		
		NTP	Known: No; Suspected: No		
	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;			
0000112-34-5 Butyl diglycol		OSHA	Select Carcinogen: No		
		NTP	Known: No; Suspected: No		



SDS Revision Date: 12/20/2014

IARC Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

**Respiratory** Use NIOSH/MSHA approved respirator, following manufacturer's recommendations when

concentrations exceed permissible exposure limits.

**Eyes** Wear safety glasses with side shields to protect the eyes. An eye wash station is

suggested as a good workplace practice.

**Skin** Chemical resistant clothing such as coveralls/apron boots should be worn. Chemical

Impervious Gloves

**Engineering Controls** Provide adequate ventilation. Where reasonably practicable this should be achieved by the

use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits

suitable respiratory protection must be worn.

Other Work Practices Avoid contact with skin and clothing. Wear suitable protective clothing. Body garments

used should be based upon the task being performed (e.g., lab coat, chemical resistant protective suit, sleevelets, synthetic apron, gauntlets) to avoid exposed skin surfaces. Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is

necessary.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or

using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

## 9. Physical and chemical properties

Appearance Colorless Liquid/Gas

**Odor** Pleasant

Odor threshold Not Measured

**pH** 11.7

Melting point / freezing pointNot MeasuredInitial boiling point and boiling rangeNot Measured

Flash Point

Evaporation rate (Ether = 1)

Flammability (solid, gas)

Nonflammable (CSMA)

Slower than ether

Not Applicable

**Upper Explosive Limit: N/A** 

Vapor pressure (Pa)Not MeasuredVapor Density>1 (Air=1)

LIGHTHOUSE for the BLIND ST. LOUIS, MO.

SDS Revision Date: 12/20/2014

Specific Gravity 0.961 (8.01 lb/gal)

Solubility in Water Soluble

Partition coefficient n-octanol/water (Log Kow)Not MeasuredAuto-ignition temperatureNot MeasuredDecomposition temperatureNot MeasuredViscosity (cSt)Not MeasuredVOC Content5.0% by wt.

9.2. Other information

No other relevant information.

## 10. Stability and reactivity

#### 10.1. Reactivity

Hazardous Polymerization will not occur.

#### 10.2. Chemical stability

Stable under normal circumstances.

### 10.3. Possibility of hazardous reactions

No data available.

## 10.4. Conditions to avoid

No data available.

#### 10.5. Incompatible materials

Any acidic material, ammonia, urea, oxidizable materials and metals such as nickel, copper, tin, aluminum and iron.

#### 10.6. Hazardous decomposition products

CO and CO2

# 11. Toxicological information

### **Acute toxicity**

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Butyl diglycol - (112-34-5)	5,660.00, Rat - Category: NA	2,700.00, Rabbit - Category: 5	No data available	No data available	No data available
Propane, 2-methyl (75-28-5)	No data available	No data available	658.00, Rat - Category: NA	No data available	No data available



SDS Revision Date: 12/20/2014

Butane - (106-97-8)	No data available	No data available	658.00, Rat - Category: NA	No data available	No data available
Propane - (74-98-6)	No data available	No data available	658.00, Rat - Category: NA	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation		Not Applicable
Serious eye damage/irritation		Not Applicable
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure		Not Applicable
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable

# 12. Ecological information

#### 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

### **Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l	
Butyl diglycol - (112-34-5)	1,300.00, Lepomis macrochirus	100.00, Daphnia magna	Not Available	
Propane, 2-methyl (75-28-5)	Not Available	Not Available	Not Available	
Butane - (106-97-8)	6.00, Fish (Piscis)	Not Available	Not Available	



SDS Revision Date: 12/20/2014

Propane - (74-98-6)	Not Available	Not Available	Not Available

### 12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

## 13. Disposal considerations

#### 13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

# 14. Transport information

**DOT (Domestic Surface** IMO / IMDG (Ocean ICAO/IATA **Transportation)** Transportation) 14.1. UN number UN1950 UN1950 UN1950 14.2. UN proper UN1950, Aerosols, non-flammable, Aerosols, non-flammable, Aerosols, non-flammable, shipping name (each not exceeding 1 L capacity), (each not exceeding 1 L (each not exceeding 1 L 2.2, capacity) capacity) 14.3. Transport **DOT Hazard Class: 2.2 IMDG:** Not Applicable Air Class: Not Applicable hazard class(es) DOT Label: 2.2 Sub Class: Not Applicable 14.4. Packing Not Applicable Not Applicable Not Applicable

14.5. Environmental hazards

group

**IMDG** Marine Pollutant: No

14.6. Special precautions for user

No further information



SDS Revision Date: 12/20/2014

## 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected

regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA

Inventory.

WHMIS Classification A E

US EPA Tier II Hazards Fire: No

Sudden Release of Pressure: Yes

Reactive: No

Immediate (Acute): No Delayed (Chronic): No

#### EPCRA 311/312 Chemicals and RQs:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### **EPCRA 302 Extremely Hazardous:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### **EPCRA 313 Toxic Chemicals:**

Butyl diglycol

### Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### **Proposition 65 - Developmental Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### **Proposition 65 - Female Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### N.J. RTK Substances (>1%):

Butane

Propane

Propane, 2-methyl-

#### Penn RTK Substances (>1%):

Butane

Propane

Propane, 2-methyl-

LIGHTHOUSE for the BLIND ST. LOUIS, MO.

SDS Revision Date: 12/20/2014

## 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

IMPORTANT NOTE: This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or any process. Final determination of suitability of any material is the sole responsibility of the user.

**End of Document**