

www.meadpaper.com

The Mead Corporation  
Product Stewardship  
401 South Paint Street  
Chillicothe, Ohio 45601  
Telephone: 740-772-3893  
Fax: 740-772-0014



Paper Division

## Product Information Sheet #09

PURPOSE	
<p>Mead wishes to provide the customers and users of its paper products (coated and uncoated) with all the available information on the safety of its products. The following grade of paper is exempt from the OSHA Hazard Communication Regulation for a Material Safety Data Sheet (MSDS), since this grade is classed as “an article which will not release or otherwise result in exposure to, a hazardous chemical under conditions of normal use”. Mead offers this “Product Information Sheet” to give you information in writing about the safety of our products.</p>	
MANUFACTURER’S NAME & ADDRESS	INQUIRY TELEPHONE CONTACT
Mead Paper Division 401 South Paint Street Chillicothe, Ohio 45601	Field Technical Services Department 1-800-832-6323
PRODUCT IDENTIFICATION	
<b>Product Description</b> Cellulose Fiber – Coated, Carbonless Copy Paper or Carbonless Copy Paper (CB, CFB, CF)	<b>Trade Name</b> <b>MEAD CARBONLESS PAPERS</b> <ul style="list-style-type: none"><li>• <b>Excel® Snap-Set® (Pre-perfed, Pre-collated)</b></li><li>• <b>Excel® Heavyweight</b></li><li>• <b>Trans/rite® (blue or black image)</b></li><li>• <b>Trans/tab</b></li><li>• <b>CF Carbonless</b></li></ul>
SAFE HANDLING	
<p>Dust, which may be created in paper converting operations, should be controlled to the OSHA limits of 5 mg/m<sup>3</sup> respirable dust or 15 mg/m<sup>3</sup> total dust and the ACGIH limits of 3 mg/m<sup>3</sup> respirable dust or 10 mg/m<sup>3</sup> inhalable dust. (All limits are for 8 hour TWA). Use good industrial hygiene practices. Dust particles also cause foreign body irritation of the eyes. Flush for 15 minutes with clear water and see a physician if irritation persists.</p>	
DISPOSAL	HANDLING AND STORAGE
Dispose of as ordinary dry waste per local, state and federal regulations.	To preserve the performance characteristics of this paper, use or storage of this product within buildings meeting ANSI/NFPA No. 90A-1976 and ASHRAE Standards are considered good use practice. Store in dry locations.
PROPER DOT SHIPPING	NOTICE
Paper N.O.I.	Data contained herein is provided in good faith and to the best knowledge of the preparer represents accurate information. No warranties of use or otherwise are expressly made or to be implied from this data or information.

Prepared By: **William H. Wooden**  
Product Stewardship Manager