

| Version 1.0 | Revision Date 02/26/2015 | Print Date 02/15/2017 |
|-------------|--------------------------|-----------------------|
| | | |

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

| Material name | : | A07708MA TM MICRO MIST MANGO 5N2 | | |
|------------------------------------|---|---|--|--|
| Material number | : | 00000000001042453 | | |
| Manufacturer or supplier's details | | | | |
| Company | : | Zep Inc. | | |
| Address | : | 1310 Seaboard Industrial Blvd., NW Atlanta, GA 30318 | | |
| Telephone | : | 404-352-1680 | | |

| Emergency telephone numbers | | |
|-----------------------------|--|--|
| : | Compliance Services 1-877-428-9937 | |
| : | 877-541-2016 Toll Free - All Calls Recorded | |
| : | CHEMTREC: 800-424-9300 - All Calls Recorded. In the District of Columbia 202-483-7616 | |
| | : | |

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

| Appearance | Aerosol containing a liquefied gas |
|------------|------------------------------------|
| Colour | colourless |
| Odour | characteristic |

GHS Classification

| Flammable aerosols Gases under pressure Eye irritation Specific target organ toxicity - single exposure | : Category 1 : Liquefied gas : Category 2A : Category 3 (Central nervous system) |
|---|--|
| GHS Label element | |
| Hazard pictograms | |
| Signal word | : Danger |
| Hazard statements | H222 Extremely flammable aerosol. H280 Contains gas under pressure; may explode if heated. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. |
| Precautionary statements | Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. |



| rsion 1.0 | Revision Date 02/26/2015 | Print Date 02/15/2017 |
|--------------------------|--|---|
| | P251 Pressurized container: Do neuse. P261 Avoid breathing dust/ fume/ P264 Wash skin thoroughly after h P271 Use only outdoors or in a wee P280 Wear eye protection/ face prise P304 + P340 + P312 IF INHALED: and keep at rest in a position composition content polson CENTER or doctor/ phys P305 + P351 + P338 IF IN EYES: for several minutes. Remove contained easy to do. Continue rinsing. P337 + P313 If eye irritation persist attention. Storage: P405 Store locked up. P410 + P412 Protect from sunlight temperatures exceeding 50 °C/ 12 P403 Store in a well-ventilated plate Disposal: P501 Dispose of contents/contained regulation. | gas/ mist/ vapours/ spray. handling. ell-ventilated area. rotection. Remove victim to fresh air fortable for breathing. Call a ician if you feel unwell. Rinse cautiously with water act lenses, if present and sts: Get medical advice/ t. Do not expose to 22 °F. ce. |
| Potential Health Effects | | |
| Carcinogenicity: | | |
| IARC | No component of this product present equal to 0.1% is identified as probable human carcinogen by IARC. | |
| ACGIH | No component of this product present equal to 0.1% is identified as a carcino carcinogen by ACGIH. | |
| OSHA | No component of this product present equal to 0.1% is identified as a carcino carcinogen by OSHA. | |
| NTP | No component of this product present equal to 0.1% is identified as a known | |

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

| Chemical Name | CAS-No. | Concentration [%] |
|---------------------------|----------|-------------------|
| acetone | 67-64-1 | >= 30 - < 50 |
| 2-(2-ethoxyethoxy)ethanol | 111-90-0 | >= 20 - < 30 |
| propane | 74-98-6 | >= 20 - < 30 |

SECTION 4. FIRST AID MEASURES

General advice

: Move out of dangerous area.



| Version 1.0 | Revision Date 02/26/2015 | Print Date 02/15/2017 |
|-------------------------|--|-----------------------|
| | Show this safety data sheet to the c Do not leave the victim unattended. | |
| If inhaled | : Consult a physician after significant If unconscious place in recovery po- advice. | |
| In case of skin contact | : If symptoms persist, call a physiciar If on clothes, remove clothes. Wash off immediately with plenty of minutes. | |
| In case of eye contact | Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a sp Rinse immediately with plenty of wa | |
| If swallowed | : Keep respiratory tract clear. Never give anything by mouth to an If symptoms persist, call a physiciar DO NOT induce vomiting unless dir physician or poison control center. | ì. |

SECTION 5. FIREFIGHTING MEASURES

| Suitable extinguishing media | : | Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray jet |
|--|---|--|
| Unsuitable extinguishing media | : | High volume water jet |
| Specific hazards during firefighting | : | Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products Specific extinguishing | : | Carbon dioxide (CO2) Carbon monoxide Smoke |
| methods | • | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Further information | : | For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers. |
| Special protective equipment for firefighters | : | Wear self-contained breathing apparatus for firefighting if necessary. |

SECTION 6. ACCIDENTAL RELEASE MEASURES



| Version 1.0 | Revision Date 02/26/2015 | Print Date 02/15/2017 |
|---|--|------------------------------|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipmen Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating t concentrations. Vapours can accu | o form explosive |
| Environmental precautions | : Prevent product from entering drai Prevent further leakage or spillage If the product contaminates rivers respective authorities. | e if safe to do so. |
| Methods and materials for containment and cleaning up | : Sweep up or vacuum up spillage a container for disposal. Soak up with inert absorbent mate acid binder, universal binder, sawo | rial (e.g. sand, silica gel, |

SECTION 7. HANDLING AND STORAGE

| Advice on safe handling | Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Always replace cap after use. Dispose of rinse water in accordance with local and national regulations. Do not breathe vapours or spray mist. |
|-----------------------------|--|
| Conditions for safe storage | BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Observe label precautions. Keep in a dry, cool and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards. |
| Materials to avoid | Oxidizing agents Do not store near acids. |

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis | |
|--------------------|-------------------------------------|---|-------|--|
|--------------------|-------------------------------------|---|-------|--|



| /ersion 1.0 | Revision | Date 02/26/2015 | Print | Date 02/15/2017 |
|---------------------------|----------|-----------------|--------------------------|-----------------|
| acetone | 67-64-1 | TWA | 500 ppm | ACGIH |
| | | STEL | 750 ppm | ACGIH |
| | | TWA | 250 ppm 590 mg/m3 | NIOSH REL |
| | | TWA | 1,000 ppm 2,400 mg/m3 | OSHA Z-1 |
| | | TWA | 750 ppm 1,800 mg/m3 | OSHA P0 |
| | | STEL | 1,000 ppm 2,400 mg/m3 | OSHA P0 |
| 2-(2-ethoxyethoxy)ethanol | 111-90-0 | TWA | 25 ppm | US WEEL |
| propane | 74-98-6 | TWA | 1,000 ppm | ACGIH |
| | | TWA | 1,000 ppm 1,800 mg/m3 | NIOSH REL |
| | | TWA | 1,000 ppm 1,800 mg/m3 | OSHA Z-1 |
| | | TWA | 1,000 ppm 1,800 mg/m3 | OSHA P0 |

Biological occupational exposure limits

| Component | CAS-No. | Control parameters | Biological specimen | Sampling time | Permissible concentration | Basis |
|-------------|---------|--------------------|---------------------|------------------|---------------------------|-----------|
| | 07.04.4 | + · | | | | |
| 2-PROPANONE | 67-64-1 | Acetone | Urine | End of | 50 mg/l | ACGIH BEI |
| | | | | shift (As | | |
| | | | | soon as | | |
| | | | | possible | | |
| | | | | after | | |
| | | | | exposure | | |
| | | | | ceases) | | |

Personal protective equipment

| Respiratory protection | : | Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. |
|----------------------------|---|---|
| Hand protection Remarks | : | The suitability for a specific workplace should be discussed with the producers of the protective gloves. |
| Eye protection | : | Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems. |
| Skin and body protection | : | impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place. |
| Hygiene measures | : | When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday. |



Version 1.0

Revision Date 02/26/2015

Print Date 02/15/2017

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| Appearance | : Aerosol containing a liquefied gas |
|--|--------------------------------------|
| Colour | : colourless |
| Odour | : characteristic |
| Odour Threshold | : no data available |
| рН | : not applicable |
| Melting point/freezing point | : no data available |
| Boiling point | : no data available |
| Flash point | : <-6.6 °C |
| – <i>– – –</i> | |
| Evaporation rate | : no data available |
| Flammability (solid, gas) | : Extremely flammable aerosol. |
| Upper explosion limit | : no data available |
| Lower explosion limit | : no data available |
| Vapour pressure | : 5,859.5 hPa |
| Density | : no data available |
| Solubility(ies) | |
| Water solubility | : partly soluble |
| Partition coefficient: n- octanol/water | : no data available |
| Auto-ignition temperature | : not determined |
| Thermal decomposition | : no data available |
| Viscosity | |
| Viscosity, kinematic | : no data available |
| Heat of combustion | : 37.25 kJ/g |
| | |

SECTION 10. STABILITY AND REACTIVITY

| Reactivity | : Stable |
|---------------------------------------|--|
| Chemical stability | : Stable under normal conditions. |
| Possibility of hazardous reactions | : No decomposition if stored and applied as directed. |
| | Vapours may form explosive mixture with air. |
| Conditions to avoid | : Heat, flames and sparks. Extremes of temperature and direct sunlight. |
| Incompatible materials | : Acids |



| Version | 10 | |
|---------|-----|--|
| version | 1.0 | |

Revision Date 02/26/2015

Print Date 02/15/2017

Amines Oxidizing agents

Hazardous decomposition : Carbon oxides products

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

no data available

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Product:

Remarks: Eye irritation

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

acetone: 2-(2-ethoxyethoxy)ethanol: propane:

STOT - single exposure

no data available

STOT - repeated exposure

no data available

Aspiration toxicity

no data available

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.



Version 1.0

Revision Date 02/26/2015

Print Date 02/15/2017

SECTION 12. ECOLOGICAL INFORMATION

| Ecotoxicity | |
|--|--|
| no data available | |
| Persistence and degradability | |
| no data available Bioaccumulative potential | |
| Product: | |
| Partition coefficient: n- octanol/water <u>Components:</u> 2-(2-ethoxyethoxy)ethanol: | : Remarks: no data available |
| · · · · · · · · · · · · · · · · · · · | : Pow: 0.54 |
| Mobility in soil | |
| no data available | |
| Other adverse effects | |
| no data available Product: | |
| Regulation | 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances |
| Remarks | This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). |
| Additional ecological information | : no data available |

SECTION 13. DISPOSAL CONSIDERATIONS

| Disposal methods | |
|------------------------|--|
| Waste from residues | Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations. |
| Contaminated packaging | Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum. |



Version 1.0

Revision Date 02/26/2015

Print Date 02/15/2017

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, 2.1, - Limited quantity

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|------------|---------|-----------------------|--------------------------------|
| acetone | 67-64-1 | 5000 | * |

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

| SARA 311/312 Hazards | Fire Hazard Sudden Release of Pressure Hazard Acute Health Hazard |
|----------------------|---|
| SARA 302 | SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302. |
| SARA 313 | SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313. |
| California Prop 65 | This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm. |



Version 1.0

Revision Date 02/26/2015

Print Date 02/15/2017


The components of this product are reported in the following inventories:

| TSCA | On TSCA Inventory |
|-------|---|
| DSL | All components of this product are on the Canadian DSL. |
| AICS | On the inventory, or in compliance with the inventory |
| NZIOC | Not in compliance with the inventory |
| PICCS | Not in compliance with the inventory |
| IECSC | On the inventory, or in compliance with the inventory |

Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION



OSHA GHS Label Information:

| Hazard pictograms | |
|--------------------------|---|
| Signal w ord | : Danger: |
| Hazard statements | : Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness. |
| Precautionary statements | |
| | Prevention: Keep aw ay from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash skin thoroughly after handling. Use only outdoors or in a w ell-ventilated area. Wear eye protection/face protection. Response: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unw ell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Storage: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a w ell-ventilated place. Disposal: Dispose of contents/container in accordance with local regulation. |

SAFETY DATA SHEET



A07708MATM MICRO MIST MANGO 5N2

Version 1.0

Revision Date 02/26/2015

Print Date 02/15/2017

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical[™], Selig[™], Misty®, Next Dimension[™], Petro®, i-Chem®, TimeMist®, TimeWick[™], MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National[™], FC Forward Chemicals®, Rexodan®, Mykal[™], and a number of private labeled brands.