Version 3.0



# A07881 ZP REPOSITINL ADH R37601 20N12OBS

Revision Date 08/31/2015

Print Date 02/21/2020

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name	:	A07881 ZP REPOSITINL ADH R37601 20N12OBS
Material number	:	0000000001046674
Manufacturer or supplier's	deta	ails
Company	:	Zep Inc.
Address	:	1310 Seaboard Industrial Blvd., NW Atlanta, GA 30318
Telephone	:	404-352-1680

Emergency telephone nu	mbers
For SDS Information	: Compliance Services 1-877-428-9937
For a Medical Emergency	: 877-541-2016 Toll Free - All Calls Recorded
For a Transportation	: CHEMTREC: 800-424-9300 - All Calls Recorded.
Emergency	In the District of Columbia 202-483-7616

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	light yellow
Odour	solvent-like

#### **GHS Classification**

Flammable aerosols Gases under pressure Skin irritation Eye irritation Specific target organ toxicity - single exposure	<ul> <li>Category 1</li> <li>Liquefied gas</li> <li>Category 2</li> <li>Category 2A</li> <li>Category 3 (Central nervous system)</li> </ul>
GHS Label element	
Hazard pictograms	
Signal word	: Danger
Hazard statements	<ul> <li>H222 Extremely flammable aerosol.</li> <li>H280 Contains gas under pressure; may explode if heated.</li> <li>H315 Causes skin irritation.</li> <li>H319 Causes serious eye irritation.</li> <li>H336 May cause drowsiness or dizziness.</li> </ul>
Precautionary statements	: <b>Prevention:</b> P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.



sion 3.0	Revision Date 08/31/2015         Print Date 02/21/2020
	<ul> <li>P211 Do not spray on an open flame or other ignition source.</li> <li>P251 Pressurized container: Do not pierce or burn, even after use.</li> <li>P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.</li> <li>P264 Wash skin thoroughly after handling.</li> <li>P271 Use only outdoors or in a well-ventilated area.</li> <li>P280 Wear eye protection/ face protection.</li> <li>P280 Wear protective gloves.</li> <li><b>Response:</b></li> <li>P302 + P352 IF ON SKIN: Wash with plenty of soap and water.</li> <li>P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.</li> <li>P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P332 + P313 If skin irritation occurs: Get medical advice/ attention.</li> <li>P362 Take off contaminated clothing and wash before reuse.</li> <li><b>Storage:</b></li> <li>P403 + P233 Store in a well-ventilated place. Keep container tightly closed.</li> <li>P405 Store locked up.</li> <li>P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.</li> <li><b>Disposal:</b></li> <li>Dispose of contents/container in accordance with local regulation.</li> </ul>
Potential Health Effects Carcinogenicity:	
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential
NTP	carcinogen by OSHA. No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Hazardous components

Chemical Name	CAS-No.	Concentration [%]
propane	74-98-6	>= 20 - < 30

Version 3.0



# A07881 ZP REPOSITINL ADH R37601 20N12OBS

Revision Date 08/31/2015

Print Date 02/21/2020

acetone	67-64-1	>= 20 - < 30
butane	106-97-8	>= 10 - < 20
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 10 - < 20
methyl acetate	79-20-9	>= 5 - < 10

#### **SECTION 4. FIRST AID MEASURES**

General advice	:	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	:	Consult a physician after significant exposure. If unconscious place in recovery position and seek medical advice.
In case of skin contact	:	If skin irritation persists, call a physician. Wash off immediately with plenty of water for at least 15 minutes. If on clothes, remove clothes.
In case of eye contact	:	Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. Rinse immediately with plenty of water for at least 15 minutes.
If swallowed	:	Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. DO NOT induce vomiting unless directed to do so by a physician or poison control center. Take victim immediately to hospital.

### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray jet
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must



		-
Version 3.0	Revision Date 08/31/2015	Print Date 02/21/2020
	be disposed of in accordance w For safety reasons in case of fir separately in closed containmer Use a water spray to cool fully c	e, cans should be stored hts.
Special protective equipment for firefighters	: Wear self-contained breathing a necessary.	pparatus for firefighting if

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

### SECTION 7. HANDLING AND STORAGE

Advice on safe handling	<ul> <li>Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Do not breathe vapours or spray mist. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations. Always replace cap after use.</li> </ul>
Conditions for safe storage	<ul> <li>BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking.</li> <li>Keep in a dry, cool and well-ventilated place.</li> <li>Observe label precautions.</li> <li>Electrical installations / working materials must comply with the technological safety standards.</li> </ul>
Materials to avoid	: Strong oxidizing agents



Version 3.0

Revision Date 08/31/2015

Print Date 02/21/2020

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
acetone	67-64-1	TWA	500 ppm	ACGIH
		STEL	750 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
methyl acetate	79-20-9	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 610 mg/m3	NIOSH REL
		ST	250 ppm 760 mg/m3	NIOSH REL
		TWA	200 ppm 610 mg/m3	OSHA Z-1
		TWA	200 ppm 610 mg/m3	OSHA P0
		STEL	250 ppm 760 mg/m3	OSHA P0

#### **Biological occupational exposure limits**

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	50 mg/l	ACGIH BEI

#### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust



ersion 3.0	Revision Date 08/31/2015	Print Date 02/21/2020
	ventilation is provided or exposure that exposures are within recomm	
Hand protection Remarks	: The suitability for a specific workp with the producers of the protectiv	
Eye protection	: Ensure that eyewash stations and the workstation location. Safety glasses	safety showers are close to
Skin and body protection	: Impervious clothing Choose body protection according concentration of the dangerous su	
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at	the end of workday.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Aerosol containing a liquefied gas
Colour	:	light yellow
Odour	:	solvent-like
Odour Threshold	:	No data available
рН	:	Not applicable
Melting point/freezing point	:	No data available
Boiling point	:	Not applicable
Flash point	:	-17 °C
		Method: closed cup
Evaporation rate	:	> 1
		n-Butyl Acetate = 1.0
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Density	:	0.841 g/cm3
Solubility(ies)		
Water solubility	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Auto-ignition temperature	:	not determined



# A07881 ZP REPOSITINL ADH R37601 20N12OBS

Version 3.0	Revision Date 08/31/2015	Print Date 02/21/2020
Thermal decomposition	: No data available	
Viscosity		
Viscosity, kinematic	: No data available	

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
reactions	Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: Carbon oxides

### SECTION 11. TOXICOLOGICAL INFORMATION

### Acute toxicity

#### Components:

propane:	
Acute inhalation toxicity	: LC50 Mouse: 1,237 mg/l Exposure time: 2 h
	LC50 Rat: 658 mg/l Exposure time: 4 h
	LC50 Rat: 1,355 mg/l
acetone:	
Acute oral toxicity	LD50 Rat: 5,800 mg/kg
Acute inhalation toxicity	: LC50 Rat: 132 mg/l Exposure time: 3 h
	LC50 Rat: 50.1 mg/l
Acute dermal toxicity	: LD50 Guinea pig: > 7,426 mg/kg
	LD50 Rabbit: > 7,426 mg/kg



# A07881 ZP REPOSITINL ADH R37601 20N12OBS

Version 3.0

L

Revision Date 08/31/2015

Print Date 02/21/2020

butane:

Acute inhalation toxicity

: LC50 Mouse: 1,237 mg/l Exposure time: 2 h

LC50 Rat: 1,355 mg/l

#### Skin corrosion/irritation

#### Product:

Remarks: Irritating to skin.

#### Serious eye damage/eye irritation

#### Product:

Remarks: Irritating to eyes.

#### Respiratory or skin sensitisation

No data available

#### Germ cell mutagenicity

No data available

#### Carcinogenicity

No data available

#### Reproductive toxicity

No data available

propane: acetone: butane: Naphtha (petroleum), hydrotreated light: methyl acetate:

#### STOT - single exposure

No data available

#### STOT - repeated exposure

No data available

#### Aspiration toxicity

No data available

#### **Further information**

#### Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.



Version 3.0

Revision Date 08/31/2015

Print Date 02/21/2020

ZepInc

### SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity	
No data available	
Persistence and degradability	
No data available <b>Bioaccumulative potential</b>	
Product:	
Partition coefficient: n- octanol/water <u>Components:</u> butane :	: Remarks: No data available
Partition coefficient: n- octanol/water	: Pow: 2.89
Mobility in soil	
No data available	
Other adverse effects	
No data available Product:	
Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological information	: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life.

### SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	<ul> <li>The product should not be allowed to enter drains, water courses or the soil.</li> <li>Do not contaminate ponds, waterways or ditches with chemical or used container.</li> <li>Send to a licensed waste management company.</li> </ul>
Contaminated packaging	<ul> <li>Empty remaining contents.</li> <li>Dispose of as unused product.</li> <li>Do not re-use empty containers.</li> <li>Do not burn, or use a cutting torch on, the empty drum.</li> </ul>



Version 3.0

Revision Date 08/31/2015

Print Date 02/21/2020

#### SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

#### SECTION 15. REGULATORY INFORMATION

#### EPCRA - Emergency Planning and Community Right-to-Know Act

#### **CERCLA** Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	: Fire Hazard Sudden Release of Pressure Hazard Acute Health Hazard
SARA 302	: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 313	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
California Prop 65 benzene	WARNING! This product contains a chemical known to the State of California to cause cancer. 71-43-2 WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
toluene benzene	108-88-3 71-43-2



Version 3.0

Revision Date 08/31/2015

Print Date 02/21/2020

#### The components of this product are reported in the following inventories:


TSCA	On TSCA Inventory
DSL	All components of this product are on the Canadian DSL
AICS	Not in compliance with the inventory
NZIoC	Not in compliance with the inventory
PICCS	On the inventory, or in compliance with the inventory
IECSC	Not in compliance with the inventory

#### Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

#### **SECTION 16. OTHER INFORMATION**





#### **OSHA GHS Label Information:**

Hazard pictograms	
Signal word	: Danger:
Hazard statements	<ul> <li>Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.</li> </ul>
Precautionary statements	<ul> <li>Prevention: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/ face protection. Wear protective gloves.</li> <li>Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.</li> <li>Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Disposal: Dispose of contents/container in accordance with local regulation.</li> </ul>



A07881 ZP REPOSITINL ADH R37601 20N12OBS

Version 3.0

#### Revision Date 08/31/2015

Print Date 02/21/2020

Version:	3.0
Revision Date:	08/31/2015
Print Date:	02/21/2020

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical<sup>™</sup>, Selig<sup>™</sup>, Misty®, Next Dimension<sup>™</sup>, Petro®, i-Chem®, TimeMist®, TimeWick<sup>™</sup>, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National<sup>™</sup>, FC Forward Chemicals®,Rexodan®, Mykal<sup>™</sup>, and a number of private labeled brands.