

**BZ7986 ZP ESY SCRIB HC PUMP F R42125 4/1G**

Version 2.0

Revision Date 02/07/2018

Print Date 12/11/2019

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : BZ7986 ZP ESY SCRIB HC PUMP F R42125 4/1G

Material number : 000000000001049470

**Manufacturer or supplier's details**

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE  
Emerson, GA 30137

Telephone : 404-352-1680

**Emergency telephone numbers****For SDS Information** : Compliance Services 1-877-428-9937**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded**For a Transportation** : CHEMTREC: 800-424-9300 - All Calls Recorded.**Emergency** : In the District of Columbia 202-483-7616**Recommended use of the chemical and restrictions on use**

Recommended use : Hand Care

**SECTION 2. HAZARDS IDENTIFICATION****Emergency Overview**

Appearance	viscous
Colour	light blue
Odour	characteristic

**GHS Classification**

Eye irritation : Category 2A

**GHS label elements**

Hazard pictograms :



Signal word : Warning

Hazard statements : H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**  
 P264 Wash skin thoroughly after handling.  
 P280 Wear eye protection/ face protection.  
**Response:**  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P337 + P313 If eye irritation persists: Get medical advice/

**BZ7986 ZP ESY SCRIB HC PUMP F R42125 4/1G**

Version 2.0

Revision Date 02/07/2018

Print Date 12/11/2019

attention.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components**

Chemical name	CAS-No.	Concentration [%]
Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts	68439-57-6	>= 5 - < 10
1-Propanaminium, N-(3-aminopropyl)-2-hydroxy-N,N-dimethyl-3-sulfo-, N-coco acyl derivs., hydroxides, inner salts	68139-30-0	>= 1 - < 5
Alcohols, C9-11, ethoxylated	68439-46-3	>= 1 - < 3
Fuller's earth	8031-18-3	>= 1 - < 5
stearic acid	57-11-4	>= 1 - < 5
quartz (SiO <sub>2</sub> )	14808-60-7	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

**SECTION 4. FIRST AID MEASURES**

- General advice : Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : This product is formulated for use on skin but should always be immediately washed off with plenty of water. Discontinue use if irritation and redness develop. If conditions persist for more than 72 hours, consult a physician.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.  
Symptoms may include irritation, redness, pain, and rash.  
Causes serious eye irritation.  
Review section 2 of SDS to see all potential hazards.
- Notes to physician : Treat symptomatically. Symptoms may be delayed.

**SECTION 5. FIREFIGHTING MEASURES**

**BZ7986 ZP ESY SCRIB HC PUMP F R42125 4/1G**

Version 2.0

Revision Date 02/07/2018

Print Date 12/11/2019

- Suitable extinguishing media : Dry chemical  
Foam  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : High volume water jet
- Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Smoke  
Nitrogen oxides (NO<sub>x</sub>)
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Standard procedure for chemical fires.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Material can create slippery conditions.  
Use non-slip safety shoes in areas where spills or leaks can occur.  
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

**SECTION 7. HANDLING AND STORAGE**

- Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Dispose of rinse water in accordance with local and national regulations.  
Avoid contact with eyes.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
- Materials to avoid : No materials to be especially mentioned.

**BZ7986 ZP ESY SCRIB HC PUMP F R42125 4/1G**

Version 2.0

Revision Date 02/07/2018

Print Date 12/11/2019

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
stearic acid	57-11-4	TWA	10 mg/m <sup>3</sup>	ACGIH
		TWA (total dust)	30 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (Respirable dust)	0.05 mg/m <sup>3</sup>	NIOSH REL
		TWA (Respirable dust)	0.05 mg/m <sup>3</sup>	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m <sup>3</sup>	CAL PEL

**Engineering measures** : effective ventilation in all processing areas

**Personal protective equipment**

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection  
Remarks : No special protection is required.

Eye protection : Eye protection is not required while washing with this product. In the workplace, the use of safety glasses is recommended to avoid eye exposure during the handling of containers or during spill clean-up.

Skin and body protection : No special protection is required.

Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and immediately after handling the product.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : viscous

Colour : light blue

Odour : characteristic

**BZ7986 ZP ESY SCRIB HC PUMP F R42125 4/1G**

Version 2.0

Revision Date 02/07/2018

Print Date 12/11/2019

Odour Threshold	: No data available
pH	: 5.5 - 6.5
Melting point/freezing point	: No data available
Boiling point	: 100 °C
Flash point	: does not flash
Evaporation rate	: 1
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Density	: 1.102 g/cm <sup>3</sup>
Solubility(ies)	
Water solubility	: soluble
Solubility in other solvents	: not determined
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Stable under recommended storage conditions. No hazards to be specially mentioned.
Conditions to avoid	: No data available
Incompatible materials	: None.
Hazardous decomposition products	: Carbon oxides

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Potential Health Effects**

**BZ7986 ZP ESY SCRIB HC PUMP F R42125 4/1G**

Version 2.0

Revision Date 02/07/2018

Print Date 12/11/2019

Aggravated Medical Condition : None known.  
Symptoms of Overexposure : Effects are immediate and delayed.  
Symptoms may include irritation, redness, pain, and rash.

**Carcinogenicity:**

**IARC** Group 1: Carcinogenic to humans  
quartz (SiO<sub>2</sub>) 14808-60-7

**ACGIH** No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Acute toxicity****Product:**

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 61.7 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

**Components:****Alcohols, C9-11, ethoxylated:**

Acute oral toxicity : LD50 Oral Rat: 1,400 mg/kg

**Skin corrosion/irritation****Product:**

Result: No skin irritation

**Serious eye damage/eye irritation****Product:**

Result: Irritating to eyes.

**Respiratory or skin sensitisation**

No data available

**Germ cell mutagenicity**

No data available

**Carcinogenicity****Product:**

**BZ7986 ZP ESY SCRIB HC PUMP F R42125 4/1G**

Version 2.0

Revision Date 02/07/2018

Print Date 12/11/2019

Carcinogenicity -  
Assessment: Not classified due to product form (liquid) and  
classification route of entry (inhaled powder)., Not  
classifiable as a human carcinogen.**Reproductive toxicity**

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

**Aspiration toxicity**

No data available

**Further information****Product:**

Remarks: No data available

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential****Product:**Partition coefficient: n-  
octanol/water

: Remarks: No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Regulation

40 CFR Protection of Environment; Part 82 Protection of  
Stratospheric Ozone - CAA Section 602 Class I  
Substances

Remarks

This product neither contains, nor was manufactured  
with a Class I or Class II ODS as defined by the U.S.  
Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A  
+ B).

**BZ7986 ZP ESY SCRIB HC PUMP F R42125 4/1G**

Version 2.0

Revision Date 02/07/2018

Print Date 12/11/2019

Additional ecological information : No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

- Waste from residues : Dispose of in accordance with local regulations. The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container.
- Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

---

**SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):  
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):  
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Cargo Air):  
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Passenger Air):  
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: TDG (Canada):  
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

---

**SECTION 15. REGULATORY INFORMATION**



**BZ7986 ZP ESY SCRIB HC PUMP F R42125 4/1G**

Version 2.0

Revision Date 02/07/2018

Print Date 12/11/2019

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

**EPCRA - Emergency Planning and Community Right-to-Know Act**
**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
methanol	67-56-1	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Serious eye damage or eye irritation

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**California Prop. 65**

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

**The components of this product are reported in the following inventories:**

**DSL** This product contains one or more components that are listed on the Canadian NDSL. All other components are on the Canadian DSL.  
**TSCA** On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

**Inventory Acronym and Validity Area Legend:**

TSCA (USA), DSL (Canada), NDSL (Canada)

---

**SECTION 16. OTHER INFORMATION**

# SAFETY DATA SHEET



## BZ7986 ZP ESY SCRIB HC PUMP F R42125 4/1G


Version 2.0

Revision Date 02/07/2018

Print Date 12/11/2019

### Further information

#### NFPA:



#### HMIS III:

<b>HEALTH</b>	<b>2</b>
<b>FLAMMABILITY</b>	<b>0</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

### OSHA - GHS Label Information:

Hazard pictograms :



Signal word :

**Warning:**

Hazard statements :

Causes serious eye irritation.

Precautionary statements :

**Prevention:** Wash skin thoroughly after handling. Wear eye protection/ face protection.  
**Response:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.

Version:	2.0
Revision Date:	02/07/2018
Print Date:	12/11/2019

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.