

Version 5.0	Revision Date 03/08/2018	Print Date 01/15/2019	
SECTION 1. PRODUCT AND COMPANY IDENTIFICATION			

Material name	:	A00732 MST BRK&PARTS CLNR EF 20NET14
Material number	:	00000000001003164
Manufacturer or supplier's	deta	ails
Company	:	Zep Inc.
Address	:	350 Joe Frank Harris Parkway, SE Emerson, GA 30137
Telephone	:	404-352-1680

# Emergency telephone numbers

For SDS Information	:	Compliance Services 1-877-428-9937
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded
For a Transportation	:	CHEMTREC: 800-424-9300 - All Calls Recorded.
Emergency		In the District of Columbia 202-483-7616

## Recommended use of the chemical and restrictions on use

Recommended use : Cleaner

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### Emergency Overview

Appearance	Aerosol containing a compressed gas
Colour	clear
Odour	solvent-like

#### **GHS Classification**

Flammable aerosols Gases under pressure Skin irritation Eye irritation Specific target organ toxicity -	<ul> <li>Category 1</li> <li>Compressed gas</li> <li>Category 2</li> <li>Category 2A</li> <li>Category 1</li> </ul>
single exposure Specific target organ toxicity - single exposure Aspiration hazard	<ul><li>Category 3 (Central nervous system)</li><li>Category 1</li></ul>
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	: H222 Extremely flammable aerosol. H280 Contains gas under pressure; may explode if heated.



Version 5.0	Revision Date 03/08/2018	Print Date 01/15/2019
	H304 May be fatal if swallowed H315 Causes skin irritation. H319 Causes serious eye irritat H336 May cause drowsiness or H370 Causes damage to organs	ion. dizziness.
Precautionary statements	<ul> <li>Prevention:</li> <li>P210 Keep away from heat/spar. No smoking.</li> <li>P211 Do not spray on an open of P251 Pressurized container: Do use.</li> <li>P260 Do not breathe dust/ fume P264 Wash skin thoroughly afte P270 Do not eat, drink or smoke P271 Use only outdoors or in a P280 Wear protective gloves/ ey <b>Response:</b></li> <li>P301 + P310 IF SWALLOWED: CENTER/doctor.</li> <li>P302 + P352 IF ON SKIN: Wasi P304 + P340 + P312 IF INHALE and keep comfortable for breath CENTER/doctor if you feel unwe P305 + P351 + P338 IF IN EYE for several minutes. Remove co easy to do. Continue rinsing.</li> <li>P307 + P311 IF exposed: Call a physician.</li> <li>P331 Do NOT induce vomiting.</li> <li>P332 + P313 If skin irritation ocd attention.</li> <li>P337 + P313 If eye irritation per attention.</li> <li>P362 Take off contaminated clo <b>Storage:</b></li> <li>P410 + P412 Protect from sunlig temperatures exceeding 50 °C/</li> <li>P403 Store in a well-ventilated p <b>Disposal:</b></li> <li>P501 Dispose of contents/contar regulation.</li> </ul>	flame or other ignition source. o not pierce or burn, even after e/ gas/ mist/ vapours/ spray. e when using this product. well-ventilated area. ye protection/ face protection. face protection.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Hazardous components

Chemical name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 50 - < 70
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 30 - < 50
carbon dioxide	124-38-9	>= 5 - < 10
methanol	67-56-1	>= 3 - < 5
heptane	142-82-5	>= 1 - < 3



Version 5.0

Revision Date 03/08/2018

Print Date 01/15/2019

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES		
General advice	<ul> <li>Move out of dangerous area.</li> <li>Show this safety data sheet to the doctor in attendance.</li> <li>Do not leave the victim unattended.</li> <li>Get medical attention immediately.</li> </ul>	
If inhaled	<ul> <li>Consult a physician after significant exposure.</li> <li>If unconscious, place in recovery position and seek medical advice.</li> </ul>	
In case of skin contact	<ul> <li>If skin irritation persists, call a physician.</li> <li>Wash off immediately with plenty of water for at least 15 minutes.</li> <li>Remove contaminated clothing and shoes.</li> <li>Wash contaminated clothing before re-use.</li> </ul>	
In case of eye contact	<ul> <li>Remove contact lenses.</li> <li>Protect unharmed eye.</li> <li>Keep eye wide open while rinsing.</li> <li>If eye irritation persists, consult a specialist.</li> <li>Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.</li> </ul>	
If swallowed	<ul> <li>Keep respiratory tract clear.</li> <li>Never give anything by mouth to an unconscious person.</li> <li>If symptoms persist, call a physician.</li> <li>DO NOT induce vomiting unless directed to do so by a physician or poison control center.</li> </ul>	
Most important symptoms and effects, both acute and delayed	Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness, paralysis, and convulsions.	
	Effects are dependent on exposure (dose, concentration, contact time). Aspiration may cause pulmonary oedema and pneumonitis. Causes serious eye irritation. May cause drowsiness or dizziness. Review section 2 of SDS to see all potential hazards. May be fatal if swallowed and enters airways.	
Notes to physician	Treat symptomatically. Symptoms may be delayed.	

## **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media	: Alcohol-resistant foam
	Carbon dioxide (CO2)
	Dry chemical



Version 5.0		Revision Date 03/08/2018	Print Date 01/15/2019
Unsuitable extinguishing media	:	High volume water jet	
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to courses.	o enter drains or water
Hazardous combustion products	:	Carbon dioxide (CO2) Carbon monoxide Smoke	
Specific extinguishing methods	:	Use extinguishing measures that are a circumstances and the surrounding en	
Further information	:	Collect contaminated fire extinguishing must not be discharged into drains. Fire residues and contaminated fire ex be disposed of in accordance with loca For safety reasons in case of fire, cans separately in closed containments. Use a water spray to cool fully closed of	tinguishing water must al regulations. s should be stored
Special protective equipment for firefighters	:	Wear self-contained breathing apparat necessary.	us for firefighting if

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, : protective equipment and emergency procedures	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions :	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for : containment and cleaning up	Sweep up or vacuum up spillage and collect in suitable container for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

## SECTION 7. HANDLING AND STORAGE

Advice on safe handling	<ul> <li>Do not breathe vapours or spray mist. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national</li> </ul>
-------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



Version 5.0	Revision Date 03/08/2018	Print Date 01/15/2019
	regulations. Always replace cap after use.	
Conditions for safe storage	<ul> <li>BEWARE: Aerosol is pressurized. Keep away from direct s exposure and temperatures over 50 °C. Do not open by fo or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking.</li> <li>Keep in a dry, cool and well-ventilated place.</li> <li>Observe label precautions.</li> <li>Electrical installations / working materials must comply with the technological safety standards.</li> </ul>	
Materials to avoid	: Strong oxidizing agents	

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
		(Form of	parameters /	
		exposure)	Permissible	
			concentration	
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm	NIOSH REL
			590 mg/m3	
		TWA	1,000 ppm	OSHA Z-1
			2,400 mg/m3	
		TWA	750 ppm	OSHA P0
			1,800 mg/m3	
		STEL	1,000 ppm	OSHA P0
			2,400 mg/m3	
		STEL	750 ppm	CAL PEL
			1,780 mg/m3	
		С	3,000 ppm	CAL PEL
		PEL	500 ppm	CAL PEL
			1,200 mg/m3	
carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm	NIOSH REL
			9,000 mg/m3	
		ST	30,000 ppm	NIOSH REL
			54,000 mg/m3	
		TWA	5,000 ppm	OSHA Z-1
			9,000 mg/m3	
		TWA	10,000 ppm	OSHA P0
			18,000 mg/m3	
		STEL	30,000 ppm	OSHA P0
			54,000 mg/m3	
		PEL	5,000 ppm	CAL PEL
			9,000 mg/m3	
		STEL	30,000 ppm	CAL PEL
			54,000 mg/m3	
methanol	67-56-1	TWA	200 ppm	ACGIH



Version 5.0	Revision	Revision Date 03/08/2018		Print Date 01/15/2019	
1	I	STEL	250 ppm	ACGIH	
		TWA	200 ppm 260 mg/m3	NIOSH REL	
		ST	250 ppm 325 mg/m3	NIOSH REL	
		TWA	200 ppm 260 mg/m3	OSHA Z-1	
		STEL	250 ppm 325 mg/m3	OSHA P0	
		TWA	200 ppm 260 mg/m3	OSHA P0	
		С	1,000 ppm	CAL PEL	
		PEL	200 ppm 260 mg/m3	CAL PEL	
		STEL	250 ppm 325 mg/m3	CAL PEL	
heptane	142-82-5	TWA	85 ppm 350 mg/m3	NIOSH REL	
		С	440 ppm 1,800 mg/m3	NIOSH REL	
		TWA	500 ppm 2,000 mg/m3	OSHA Z-1	
		TWA	400 ppm 1,600 mg/m3	OSHA P0	
		STEL	500 ppm 2,000 mg/m3	OSHA P0	
		PEL	400 ppm 1,600 mg/m3	CAL PEL	
		STEL	500 ppm 2,000 mg/m3	CAL PEL	
		TWA	400 ppm	ACGIH	
		STEL	500 ppm	ACGIH	

## **Biological occupational exposure limits**

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
2-PROPANONE	67-64-1	Acetone	Urine	End of	25 mg/l	ACGIH BEI
				shift (As		
				soon as		
				possible		
				after		
				exposure		
				ceases)		
Methanol	67-56-1	Methanol	Urine	End of	15 mg/l	ACGIH BEI
				shift (As		
				soon as		
				possible		
				after		
				exposure		
				ceases)		

**Engineering measures** 

: effective ventilation in all processing areas

#### Personal protective equipment

Respiratory protection



Version 5.0	Revision Date 03/08/2018	Print Date 01/15/2019
	ventilation is provided or exposure that exposures are within recomme	
Hand protection Material Remarks	<ul><li>Protective gloves</li><li>The suitability for a specific workpla with the producers of the protective</li></ul>	
Eye protection	: Safety goggles Access to clean water to rinse eyes include: eye wash stations or show with pure water.	
Skin and body protection	: Impervious clothing Choose body protection according concentration of the dangerous sub	
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at	the end of workday.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a compressed gas
Colour	: clear
Odour	: solvent-like
Odour Threshold	: No data available
рН	: Not applicable
Melting point/freezing point	: No data available
Boiling point	: No data available
Flash point	: Not applicable
Evaporation rate	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Density	: 0.728 g/cm3
Solubility(ies)	
Water solubility	: slightly soluble
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: not determined



Version 5.0	Revision Date 03/08/2018	Print Date 01/15/2019
Thermal decomposition	: No data available	
Viscosity		
Viscosity, kinematic	: No data available	
Heat of combustion	: 34.35 kJ/g	

# SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: Carbon oxides

## SECTION 11. TOXICOLOGICAL INFORMATION

#### Potential Health Effects

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness, paralysis, and convulsions.
	Effects are dependent on exposure (dose, concentration, contact time).
	Aspiration may cause pulmonary oedema and pneumonitis.
Carcinogenicity:	
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential



ersion 5.0	Revision Date 03/08/2018	Print Date 01/15/2019
OSHA NTP	carcinogen by ACGIH. No component of this product present equal to 0.1% is on OSHA's list of reg No component of this product present equal to 0.1% is identified as a known by NTP.	ulated carcinogens. at levels greater than or
cute toxicity		
Product:		
Acute oral toxicity	: Acute toxicity estimate : 2,636 mg/k Method: Calculation method	g
Acute inhalation toxicity	: Acute toxicity estimate : 13.18 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method	
Acute dermal toxicity	: Acute toxicity estimate : > 5,000 mg Method: Calculation method	]/kg
Components:		
acetone: Acute oral toxicity	: LD50 Rat: 5,800 mg/kg	
Acute inhalation toxicity	: LC50 Rat: 132 mg/l Exposure time: 3 h	
	LC50 Rat: 50.1 mg/l	
Acute dermal toxicity	: LD50 Guinea pig: > 7,426 mg/kg	
	LD50 Rabbit: > 7,426 mg/kg	
heptane: Acute inhalation toxicity	: LC50 Rat: 103 mg/l Exposure time: 4 h	
kin corrosion/irritation		
Product:		
Remarks: Irritating to skin.		
erious eye damage/eye irritatior		
Product:		
Remarks: Severe eye irritation		
espiratory or skin sensitisation		
o data available		



Version 5.0

Revision Date 03/08/2018

Print Date 01/15/2019

#### Germ cell mutagenicity

No data available

#### Carcinogenicity

No data available

#### Reproductive toxicity

No data available

#### STOT - single exposure

No data available

#### STOT - repeated exposure

No data available

#### Aspiration toxicity

## Product:

May be fatal if swallowed and enters airways.

#### Further information

## Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

## SECTION 12. ECOLOGICAL INFORMATION

## Ecotoxicity

No data available

#### Persistence and degradability

No data available Bioaccumulative potential

#### Product:

Partition coefficient: n- octanol/water <u>Components:</u> heptane :	: Remarks: No data available
Partition coefficient: n- octanol/water	: log Pow: 5
Mobility in soil	

No data available

#### Other adverse effects



Version 5.0	Revision Date 03/08/2018	Print Date 01/15/2019
No data available <u>Product:</u>		
Regulation	40 CFR Protection of Environm Stratospheric Ozone - CAA Sec Substances	
Remarks	This product neither contains, r with a Class I or Class II ODS a Clean Air Act Section 602 (40 0 + B).	as defined by the U.S.
Additional ecological information	: No data available	

## SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations.
Contaminated packaging	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

## SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.



Version 5.0

Revision Date 03/08/2018

Print Date 01/15/2019

#### **SECTION 15. REGULATORY INFORMATION**

**TSCA list** : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

#### EPCRA - Emergency Planning and Community Right-to-Know Act

#### **CERCLA** Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
acetone	67-64-1	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	:	Flammable (gases, aerosols, liquids, Gases under pressure Skin corrosion or irritation Serious eye damage or eye irritation Specific target organ toxicity (single o Aspiration hazard		osure)
SARA 302	:	No chemicals in this material are subj requirements of SARA Title III, Sectio		ting
SARA 313	:	The following components are subject established by SARA Title III, Section methanol		vels 3.7943 %
California Prop. 65				
		WARNING: This product can expos	•	



WARNING: This product can expose you to chemicals including methanol, toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

#### The components of this product are reported in the following inventories:

DSL	All components of this product are on the Canadian DSL
TSCA	On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

#### Inventory Acronym and Validity Area Legend:




Version 5.0

Revision Date 03/08/2018

Print Date 01/15/2019

TSCA (USA), DSL (Canada), NDSL (Canada)

## **SECTION 16. OTHER INFORMATION**



# OSHA - GHS Label Information:

Hazard pictograms	
Signal word	: Danger:
Hazard statements	<ul> <li>Extremely flammable aerosol. Contains gas under pressure; may explode if heated.</li> <li>May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Causes damage to organs.</li> </ul>
Precautionary statements	
	<ul> <li>Prevention: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/ eye protection/ face protection.</li> <li>Response: IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed: Call a POISON CENTER or doctor/ physician. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.</li> <li>Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place.</li> <li>Disposal: Dispose of contents/container in accordance with local regulation.</li> </ul>

Version:	5.0
Revision Date:	03/08/2018
Print Date:	01/15/2019



Version 5.0

Revision Date 03/08/2018

Print Date 01/15/2019

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®,Rexodan®, Mykal™, and a number of private labeled brands.