

Material name	:	A00209SB MST SEAS SUMMER BREEZE 12NET7
Material number	:	0000000001015013
Manufacturer or supplier's of	deta	ails
Company	:	Zep Inc.
Address	:	350 Joe Frank Harris Parkway, SE Emerson, GA 30137
Telephone	:	404-352-1680

Emergency telephone numbers

For SDS Information	:	Compliance Services 1-877-428-9937
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded
For a Transportation	:	CHEMTREC: 800-424-9300 - All Calls Recorded.
Emergency		In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Air Care

Note: This product is labeled as a consumer product in accordance with the United States Consumer Product Safety Commission regulations. The warnings presented below in this Safety Data Sheet (SDS) comply with the 2012 OSHA Hazard Communication Standard (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	clear
Odour	characteristic

GHS Classification

Flammable aerosols	:	Category 1
Gases under pressure	:	Liquefied gas
Eye irritation	:	Category 2A
Skin sensitisation	:	Category 1
Specific target organ toxicity -	:	Category 3 (Central nervous system)
single exposure		

GHS label elements

Hazard pictograms

Signal word





Version 2.0	Revision Date 04/20/2018	Print Date 01/15/2019
Hazard statements	 H222 Extremely flammable aer H280 Contains gas under press H317 May cause an allergic ski H319 Causes serious eye irrita H336 May cause drowsiness of 	sure; may explode if heated. in reaction. tion.
Precautionary statements	and other ignition sources. No s P211 Do not spray on an open P251 Pressurized container: Do use. P261 Avoid breathing dust/ fur P264 Wash skin thoroughly afte P271 Use only outdoors or in a P272 Contaminated work clothing the workplace. P280 Wear eye protection/ face P280 Wear protective gloves. Response:	flame or other ignition source. o not pierce or burn, even after ne/ gas/ mist/ vapours/ spray. er handling. well-ventilated area. ing should not be allowed out of e protection. sh with plenty of soap and water. ED: Remove victim to fresh air omfortable for breathing. Call a hysician if you feel unwell. ES: Rinse cautiously with water ontact lenses, if present and rash occurs: Get medical ersists: Get medical advice/ hing before reuse. ight. Do not expose to ' 122 °F. place.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture :

: Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 70 - < 90
propane	74-98-6	>= 10 - < 20
butane	106-97-8	>= 5 - < 10
Oils, sweet orange (terpenes and terpenoids)	68647-72-3	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.



Version 2.0 Revision Date 04/20/2018

Print Date 01/15/2019

SECTION 4. FIRST AID MEASURES	
General advice :	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled :	Move to fresh air. Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact :	Wash off with soap and water. Wash off immediately with plenty of water for at least 15 minutes. Wash contaminated clothing before reuse. Call a physician if irritation develops or persists.
In case of eye contact :	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed :	DO NOT induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms : and effects, both acute and delayed	Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness, paralysis, and convulsions.
	Effects are dependent on exposure (dose, concentration, contact time). May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Review section 2 of SDS to see all potential hazards.
Notes to physician :	Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray jet
Unsuitable extinguishing media	:	High volume water jet



Version 2.0	Revision Date 04/20/2018	Print Date 01/15/2019
Specific hazards during firefighting	: Do not allow run-off from fire figh courses.	ting to enter drains or water
Hazardous combustion products	: Carbon dioxide (CO2) Carbon monoxide Smoke	
Specific extinguishing methods	: Use extinguishing measures that circumstances and the surroundi	
Further information	: For safety reasons in case of fire separately in closed containment Use a water spray to cool fully cl	ts.
Special protective equipment for firefighters	: Wear self-contained breathing ap necessary.	oparatus for firefighting if

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	 Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	 Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Container may be opened only under exhaust ventilation hood. Always replace cap after use. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.



Version 2.0	Revision Date 04/20/2018	Print Date 01/15/2019
	Do not breathe vapours or spray mis	st.
Conditions for safe storage	 BEWARE: Aerosol is pressurized. K exposure and temperatures over 50 or throw into fire even after use. Do r red-hot objects. No smoking. Observe label precautions. Keep in a dry, cool and well-ventilate Electrical installations / working mate the technological safety standards. 	°C. Do not open by force not spray on flames or ed place.
Materials to avoid	: Oxidizing agents Store and keep away from bases an	d alkalies.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
		STEL	750 ppm 1,780 mg/m3	CAL PEL
		С	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL

Biological occupational exposure limits

SAFETY DATA SHEET



A00209SB MST SEAS SUMMER BREEZE 12NET7

ersion 2.0	R	evision Date 0	4/20/2018		Print Date 01/15	5/2019
Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BE
Engineering measures	: No	ot applicable				
Personal protective equ	uipment					
Respiratory protection	ve	ntilation is prov	/ided or expo	sure asses	te local exhaus sment demonst exposure guide	rates
Hand protection Material Remarks	: Th	otective gloves ne suitability for th the produce	a specific w		ould be discuss s.	ed
Eye protection	the	nsure that eyew e workstation lo afety glasses		and safety	showers are clo	ose to
Skin and body protection	Ch	pervious clothi noose body pro ncentration of	tection acco		amount and e at the work pla	ace.
Hygiene measures	W	hen using do n hen using do n ash hands befo	ot smoke.		d of workdow	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a liquefied gas
Colour	: clear
Odour	: characteristic
Odour Threshold	: No data available
рН	: No data available
Melting point/freezing point	: No data available
Boiling point	: No data available
Flash point	: Not applicable
Evaporation rate	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.

octanol/water

Viscosity

Auto-ignition temperature

Thermal decomposition

Viscosity, kinematic



A00209SB MST SEAS SUMMER BREEZE 12NET7

		-
Version 2.0	Revision Date 04/20/2018	Print Date 01/15/2019
Upper explosion limit	: No data available	
Lower explosion limit	: No data available	
Vapour pressure	: 4,826 hPa	
Relative vapour density	: No data available	
Density	: <1 g/cm3	
Solubility(ies)		
Water solubility	: soluble	
Partition coefficient: n-	: No data available	

: not determined

: No data available

: No data available

SECTION 10.	STABILITY	' AND REA	CTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents Amines Bases
Hazardous decomposition products	: Carbon monoxide Carbon dioxide (CO2)

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	:	None known.
Symptoms of Overexposure	:	Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness, paralysis, and convulsions.



AUUZUSSD MIST SEAS	SUMMER BREEZE IZNEI	
Version 2.0	Revision Date 04/20/2018	Print Date 01/15/2019
	Effects are dependent on exposur contact time).	re (dose, concentration,
Carcinogenicity:		
IARC	No component of this product preser equal to 0.1% is identified as probab human carcinogen by IARC.	
ACGIH	No component of this product preser equal to 0.1% is identified as a carci carcinogen by ACGIH.	
OSHA	No component of this product preser equal to 0.1% is on OSHA's list of re	
NTP	No component of this product preser equal to 0.1% is identified as a know by NTP.	nt at levels greater than or
Acute toxicity		
Components:		
acetone: Acute oral toxicity	: LD50 Rat: 5,800 mg/kg	
Acute inhalation toxicity	: LC50 Rat: 132 mg/l Exposure time: 3 h	
	LC50 Rat: 50.1 mg/l	
Acute dermal toxicity	: LD50 Guinea pig: > 7,426 mg/kg	
	LD50 Rabbit: > 7,426 mg/kg	
Skin corrosion/irritation		
Product:		
Remarks: May cause skin irri	itation and/or dermatitis.	
Serious eye damage/eye irritatio	on	
Product:		

Remarks: Eye irritation

Respiratory or skin sensitisation

Product:

Remarks: Causes sensitisation.

Germ cell mutagenicity

No data available



•••••••••••••••••••••••••••••••••••••••		Lepinc
A00209SB MST SEAS	SUMMER BREEZE 12NET7	-
Version 2.0	Revision Date 04/20/2018	Print Date 01/15/2019
Carcinogenicity		
No data available		
Reproductive toxicity		
No data available		
STOT - single exposure		
No data available		
STOT - repeated exposure		
No data available		
Aspiration toxicity		
No data available		
SECTION 12. ECOLOGICAL INF	ORMATION	
Ecotoxicity		
No data available		
Persistence and degradability		
No data available Bioaccumulative potential		
Product:		
Partition coefficient: n- octanol/water <u>Components:</u> butane :	: Remarks: No data available	
Partition coefficient: n- octanol/water	: Pow: 2.89	

Mobility in soil

No data available

Other adverse effects

No data available	
Product:	

information

Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological	: No data available



Version 2.0

Revision Date 04/20/2018

Print Date 01/15/2019

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list

: No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity



sion 2.0		Revision Date 04/2	0/2018	Print Date 01/15/201
Components		CAS-No.	Component RQ (lbs)	Calculated product RC (lbs)
acetone		67-64-1	5000	*
*: Calculated RQ exceeds re	easonal	bly attainable upper	limit.	
SARA 304 Extremely Haza	ardous	Substances Repor	rtable Quantity	
This material does not conta	ain any	components with a	section 304 EHS	RQ.
SARA 311/312 Hazards	Ga Se Re	 Flammable (gases, aerosols, liquids, or solids) Gases under pressure Serious eye damage or eye irritation Respiratory or skin sensitisation Specific target organ toxicity (single or repeated exposure) 		
SARA 302		o chemicals in this r quirements of SAR		
SARA 313	kr	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.		
California Prop. 65				
		This product does n California to cause o reproductive harm.		emicals known to State cts, or any other

The components of this product are reported in the following inventories:

DSL	All components of this product are on the Canadian DSL
TSCA	On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)


SECTION 16. OTHER INFORMATION



Revision Date 04/20/2018

Print Date 01/15/2019

Further information



HMIS III:

HEALTH	2
FLAMMABILITY	4
PHYSICAL HAZARD	3

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High 4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms	
O'man di susa na l	
Signal word	: Danger:
Hazard statements	 Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statements	
	 Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear eye protection/ face protection. Wear protective gloves. Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Wash contaminated clothing before reuse. Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Disposal: Dispose of contents/container in accordance with local regulation.

Version:	2.0
Revision Date:	04/20/2018
Print Date:	01/15/2019

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.



Version 2.0

Revision Date 04/20/2018

Print Date 01/15/2019

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical[™], Selig[™], Misty®, Next Dimension[™], Petro®, i-Chem®, TimeMist®, TimeWick[™], MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National[™], FC Forward Chemicals®,Rexodan®, Mykal[™], and a number of private labeled brands.