

# SAFETY DATA SHEET

Issuing Date No data available

Revision Date 22-May-2015

Revision Number 1



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product identifier

Product Name Yellow Pencil

### Other means of identification

Synonyms None

### Recommended use of the chemical and restrictions on use

Recommended Use Writing Instrument

Uses advised against No information available

### Details of the supplier of the safety data sheet

Supplier Name PT. Pelinda Sarana Sukses

Supplier Address JL.Ancol Barat VII Blok A 5D No.2 14430, jakarta - Indonesia  
Jl.Raya Serang KM.18 Cikupa Tangerang 15710-Indonesia  
Jakarta  
Jakarta  
14430  
ID

Supplier Phone Number Phone:6221-5960771  
Fax:6221-6900823  
Contact Phone6221-6901171

Supplier Email dewi.puspa@pelinda.co.id

### Emergency telephone number

## 2. HAZARDS IDENTIFICATION

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)


Acute toxicity - Inhalation (Vapors)	Category 4
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 1A



Specific target organ toxicity (single exposure)	Category 3
--	------------

**GHS Label elements, including precautionary statements**

**Emergency Overview**

<b>Signal word</b>	<b>Danger</b>	
<b>Hazard Statements</b>		
Harmful if inhaled		
Causes serious eye irritation		
May cause cancer		
May cause drowsiness or dizziness		
		
<b>Appearance</b>	<b>Physical state</b>	<b>Odor</b>
Yellow	Solid containing liquid Solid	Slight moderate

**Precautionary Statements - Prevention**

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Avoid breathing dust/fume/gas/mist/vapors/spray
- Use only outdoors or in a well-ventilated area
- Wash face, hands and any exposed skin thoroughly after handling
- Wear eye/face protection

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention

**Inhalation**

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

**Precautionary Statements - Storage**

- Store locked up
- Store in a well-ventilated place. Keep container tightly closed

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Unknown Toxicity**



21% of the mixture consists of ingredient(s) of unknown toxicity

#### Other information

Causes mild skin irritation

Harmful to aquatic life with long lasting effects

Exposure to chlorinated hydrocarbons, such as chloroform and trichloroethane, may increase toxic effects

INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS

#### Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Acetone	67-64-1	10 - 30	*
Ethylacetate	141-78-6	7 - 13	*
n-Butyl acetate	123-86-4	7 - 13	*
Butanamide, 2,2'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl	5468-75-7	7 - 13	*
Titanium dioxide	13463-67-7	5 - 10	*
Epoxidized soybean oil	8013-07-8	3 - 7	*
Isobutyl alcohol	78-83-1	1 - 5	*
3H-Pyrazol-3-one, 4,4'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl)bis(azo)] bis[2,4-dihydro-5-methyl-2-phenyl-	3520-72-7	1 - 5	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret

### 4. FIRST AID MEASURES

#### First aid measures

##### General Advice

Show this safety data sheet to the doctor in attendance.

##### Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.

##### Skin contact

Wash with soap and water.

##### Inhalation

Remove to fresh air.

##### Ingestion

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.

#### Most important symptoms and effects, both acute and delayed

##### **Most Important Symptoms and Effects**

Burning sensation. Coughing and/ or wheezing. Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

**Indication of any immediate medical attention and special treatment needed**

**Notes to Physician**                      Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media**

CAUTION: Use of water spray when fighting fire may be inefficient.

**Specific hazards arising from the chemical**

No information available.

<b>Uniform Fire Code</b>	Irritant: Solid Toxic: Solid
--------------------------	---------------------------------

**Hazardous Combustion Products**

Carbon oxides.

**Explosion Data**

**Sensitivity to Mechanical Impact**      No.

**Sensitivity to Static Discharge**        No.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions**                      Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Ensure adequate ventilation. Avoid breathing vapors or mists. Avoid generation of dust. Do not breathe dust. Evacuate personnel to safe areas.

**Other Information**                              Refer to protective measures listed in Sections 7 and 8.

**Environmental precautions**

**Environmental precautions**                Refer to protective measures listed in Sections 7 and 8.

**Methods and material for containment and cleaning up**

**Methods for containment**                    Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up**                    Pick up and transfer to properly labeled containers.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

#### **Handling**

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Avoid breathing vapors or mists. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Take off contaminated clothing and wash before reuse.

### Conditions for safe storage, including any incompatibilities

#### **Storage**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children.

#### **Incompatible Products**

Strong oxidizing agents. Chlorinated compounds.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) STEL: 2400 mg/m <sup>3</sup> The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm 10% LEL TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>
Ethylacetate 141-78-6	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 1400 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup>
n-Butyl acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m <sup>3</sup> (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m <sup>3</sup>	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
Isobutyl alcohol 78-83-1	TWA: 50 ppm	TWA: 100 ppm TWA: 300 mg/m <sup>3</sup> (vacated) TWA: 50 ppm (vacated) TWA: 150 mg/m <sup>3</sup>	IDLH: 1600 ppm TWA: 50 ppm TWA: 150 mg/m <sup>3</sup>

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

#### **Other Exposure Guidelines**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

### Appropriate engineering controls



**Engineering Measures**  
Showers  
Eyewash stations  
Ventilation systems

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** If splashes are likely to occur: Wear safety glasses with side shields (or goggles). None required for consumer use.

**Skin and body protection** Wear protective gloves and protective clothing.

**Respiratory protection** No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Do not breathe dust. Wash hands before breaks and immediately after handling the product.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical and Chemical Properties**

<b>Physical state</b>	Solid containing liquid, Solid	<b>Odor</b>	Slight moderate
<b>Appearance</b>	Yellow	<b>Odor Threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH	No data available	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	No data available	None known	
Flash Point	No data available	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Specific Gravity	No data available	None known	
Water Solubility	Very slight	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/water	0	None known	
Autoignition temperature	No data available	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	15000	None known	
Explosive properties	No data available		
Oxidizing properties	No data available		

**Other Information**

<b>Softening Point</b>	No data available
<b>VOC Content (%)</b>	No data available
<b>Particle Size</b>	No data available
<b>Particle Size Distribution</b>	



## 10. STABILITY AND REACTIVITY

### Reactivity

No data available.

### Chemical stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

### Hazardous Polymerization

Hazardous polymerization does not occur.

### Conditions to avoid

Excessive heat.

### Incompatible materials

Strong oxidizing agents. Chlorinated compounds.

### Hazardous Decomposition Products

Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### Product Information

##### **Inhalation**

Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Harmful by inhalation. (based on components). May cause drowsiness and dizziness.

##### **Eye contact**

Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.

##### **Skin contact**

Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.

##### **Ingestion**

Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

#### Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	-	-	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
Ethylacetate 141-78-6	= 5620 mg/kg ( Rat )	> 20 mL/kg ( Rabbit )	-
n-Butyl acetate 123-86-4	= 14.13 mg/kg ( Rat ) = 10768 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	= 390 ppm ( Rat ) 4 h
Titanium dioxide 13463-67-7	> 10000 mg/kg ( Rat )	-	-
Epoxidized soybean oil 8013-07-8	= 21000 mg/kg ( Rat )	> 20 mL/kg ( Rabbit )	-
Isobutyl alcohol 78-83-1	= 2460 mg/kg ( Rat )	= 3400 mg/kg ( Rabbit )	> 6.5 mg/L ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** May cause redness and tearing of the eyes. Coughing and/ or wheezing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.

**Mutagenic Effects** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Butanamide, 2,2'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl 5468-75-7		Group 1	Known	X
Titanium dioxide 13463-67-7		Group 2B		X
3H-Pyrazol-3-one, 4,4'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl)bis(azo)]bis[2, 4-dihydro-5-methyl-2-phenyl- 3520-72-7		Group 1	Known	X

*IARC (International Agency for Research on Cancer)*

*Group 1 - Carcinogenic to Humans*

*Group 2A - Probably Carcinogenic to Humans*

*Group 2B - Possibly Carcinogenic to Humans*

*NTP (National Toxicology Program)*

*Known - Known Carcinogen*

*OSHA (Occupational Safety and Health Administration of the US Department of Labor)*

*X - Present*

**Reproductive toxicity** No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Chronic Toxicity**

No known effect based on information supplied. Contains a known or suspected carcinogen. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects. Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation.

**Target Organ Effects**

Eyes. Respiratory system. Skin. Gastrointestinal tract (GI). Bladder. Blood. Central Nervous System (CNS). Kidney. Liver. Lungs.

**Aspiration Hazard** No information available.

**Numerical measures of toxicity Product Information**

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)**

19,763.00 mg/kg

**ATEmix (inhalation-dust/mist)**

395.80 mg/l

**ATEmix (inhalation-vapor)**

14.64 ATEmix



## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Acetone 67-64-1		96h LC50: 4.74 - 6.33 mL/L (Oncorhynchus mykiss) 96h LC50: 6210 - 8120 mg/L (Pimephales promelas) 96h LC50: = 8300 mg/L (Lepomis macrochirus)	EC50 = 14500 mg/L 15 min	48h EC50: 10294 - 17704 mg/L 48h EC50: 12600 - 12700 mg/L
Ethylacetate 141-78-6	48h EC50: = 3300 mg/L (Desmodesmus subspicatus)	96h LC50: 220 - 250 mg/L (Pimephales promelas) 96h LC50: 352 - 500 mg/L (Oncorhynchus mykiss) 96h LC50: = 484 mg/L (Oncorhynchus mykiss)	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h	48h EC50: = 560 mg/L
n-Butyl acetate 123-86-4	72h EC50: = 674.7 mg/L (Desmodesmus subspicatus)	96h LC50: = 100 mg/L (Lepomis macrochirus) 96h LC50: 17 - 19 mg/L (Pimephales promelas) 96h LC50: = 62 mg/L (Leuciscus idus)	EC50 = 70.0 mg/L 5 min EC50 = 82.2 mg/L 15 min EC50 = 959 mg/L 18 h EC50 = 98.9 mg/L 30 min	24h EC50: = 72.8 mg/L
Epoxidized soybean oil 8013-07-8	72h EC50: = 8 mg/L (Desmodesmus subspicatus)	48h LC50: = 900 mg/L (Leuciscus idus)		24h EC50: > 100 mg/L
Isobutyl alcohol 78-83-1	48h EC50: = 230 mg/L (Desmodesmus subspicatus)	96h LC50: = 375 mg/L (Pimephales promelas) 96h LC50: 1480 - 1730 mg/L (Lepomis macrochirus) 96h LC50: 1120 - 1520 mg/L (Oncorhynchus mykiss) 96h LC50: 1370 - 1670 mg/L (Pimephales promelas)	EC50 = 1224.6 mg/L 15 min	48h EC50: = 1300 mg/L 48h EC50: 1070 - 1933 mg/L

### Persistence and Degradability

No information available.

### Bioaccumulation

Chemical Name	Log Pow
Acetone 67-64-1	-0.24
Ethylacetate 141-78-6	0.6
n-Butyl acetate 123-86-4	1.81
Isobutyl alcohol 78-83-1	0.79

### Other adverse effects

No information available.

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal methods**

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

**Contaminated Packaging**

Dispose of contents/containers in accordance with local regulations.

**US EPA Waste Number**

U002 U140

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone 67-64-1		Included in waste stream: F039		U002
Ethylacetate 141-78-6		Included in waste stream: F039		U112
Isobutyl alcohol 78-83-1	U140	Included in waste streams: F005, F039		U140

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Acetone 67-64-1	Ignitable
Ethylacetate 141-78-6	Toxic Ignitable
n-Butyl acetate 123-86-4	Toxic

**14. TRANSPORT INFORMATION**

**DOT**  
 Proper Shipping Name: NOT REGULATED  
 Hazard Class: NON REGULATED  
 N/A

**TDG**: Not regulated

**MEX**: Not regulated

**ICAO**: Not regulated

**IATA**  
 Proper Shipping Name: Not regulated  
 Hazard Class: NON REGULATED  
 N/A

**IMDG/IMO**  
 Hazard Class: Not regulated  
 N/A

**RID**: Not regulated

**ADR**: Not regulated



**ADN** Not regulated

## 15. REGULATORY INFORMATION

### International Inventories

TSCA Complies  
 DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

### US Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

#### SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

#### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
n-Butyl acetate 123-86-4	5000 lb			X

#### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Acetone 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Ethylacetate 141-78-6			RQ 5000 lb final RQ RQ 2270 kg final RQ
n-Butyl acetate 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Isobutyl alcohol 78-83-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

### US State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Butanamide, 2,2'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl) - 5468-75-7	Carcinogen
Titanium dioxide - 13463-67-7	Carcinogen
3H-Pyrazol-3-one, 4,4'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl)bis(azo)]bis[2,4-dihydro-5-met hyl-2-phenyl- - 3520-72-7	Carcinogen

### U.S. State Right-to-Know Regulations

.



Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Acetone 67-64-1		X		X	
Nitrocellulose 9004-70-0	X	X	X		X
Ethylacetate 141-78-6	X	X	X	X	
n-Butyl acetate 123-86-4	X	X	X	X	
Titanium dioxide 13463-67-7	X	X	X		
Isobutyl alcohol 78-83-1	X	X	X	X	

**International Regulations**

**Mexico**

**National occupational exposure limits**

Component	Carcinogen Status	Exposure Limits
Acetone 67-64-1 ( 10 - 30 )		Mexico: TWA= 1000 ppm Mexico: TWA= 2400 mg/m <sup>3</sup> Mexico: STEL= 1260 ppm Mexico: STEL= 3000 mg/m <sup>3</sup>
Ethylacetate 141-78-6 ( 7 - 13 )		Mexico: TWA 400 ppm Mexico: TWA 1400 mg/m <sup>3</sup>
n-Butyl acetate 123-86-4 ( 7 - 13 )		Mexico: TWA 150 ppm Mexico: TWA 710 mg/m <sup>3</sup> Mexico: STEL 200 ppm Mexico: STEL 950 mg/m <sup>3</sup>
Titanium dioxide 13463-67-7 ( 5 - 10 )		Mexico: TWA= 10 mg/m <sup>3</sup> Mexico: STEL= 20 mg/m <sup>3</sup>
Isobutyl alcohol 78-83-1 ( 1 - 5 )		Mexico: TWA 50 ppm Mexico: TWA 150 mg/m <sup>3</sup> Mexico: STEL 75 ppm Mexico: STEL 225 mg/m <sup>3</sup>

Mexico - Occupational Exposure Limits - Carcinogens

**16. OTHER INFORMATION**

<b>NFPA</b>	<b>Health Hazards</b> 3	<b>Flammability</b> 0	<b>Instability</b> 0	<b>Physical and Chemical Hazards - Personal Protection</b> X
<b>HMIS</b>	<b>Health Hazards</b> 3 *	<b>Flammability</b> 0	<b>Physical Hazard</b> 0	

**Chronic Hazard Star Legend** \* = Chronic Health Hazard

**Prepared By** Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Revision Date** 22-May-2015

**Revision Note** No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text



**End of Safety Data Sheet**

