

Version 3.0	Revision Date: 05/05/2015		SDS Number: 491-00004	Date of last issue: 04/17/2015 Date of first issue: 12/11/2014	
SECTION	1. IDENTIFICATION				
Produ	Product name		GOJO® E2 Foam	Handwash with PCMX	
Manu	facturer or supplier's	deta	ils		
	pany name of supplier	:			
Addre	Address		One GOJO Plaza, Suite 500 Akron OH 44311		
Telep	hone	:	1 (330) 255-6000		
Emer	gency telephone	:	1-800-424-9300 CHEMTREC		
Recommended use of the		cherr	nical and restriction	ons on use	
Reco	Recommended use		Antibacterial Soap	0	
Restrictions on use		:	This is a personal care or cosmetic product that is safe for consumers and other users under normal and reasonably foreseeable use. Cosmetics and consumer products, specifically defined by regulations around the world, are exempt from the requirement of an SDS for the consumer. While this material is not considered hazardous, this SDS contains valuable information critical to the safe handling a proper use of the product for industrial workplace condition as well as unusual and unintended exposures such as large spills. This SDS should be retained and available for employees and other users of this product. For specific intended-use guidance, please refer to the information provided on the package or instruction sheet.		

## SECTION 2. HAZARDS IDENTIFICATION

GHS Classification Flammable liquids	: Category 3
Serious eye damage	: Category 1
GHS Label element Hazard pictograms	
Signal Word	: Danger
Hazard Statements	: H226 Flammable liquid and vapor. H318 Causes serious eye damage.



Version	Revision Date:	MSDS Number:	Date of last issue: 04/17/2015
3.0	05/05/2015	36491-00004	Date of first issue: 12/11/2014
Preca	utionary Statements	No smoking. P233 Keep conta P241 Use explose equipment. P242 Use only n P243 Take preca P280 Wear prote <b>Response:</b> P303 + P361 + F all contaminated P305 + P351 + F water for severa and easy to do. 0 CENTER or doct <b>Storage:</b> P403 + P235 Sto <b>Disposal:</b>	y from heat/sparks/open flames/hot surfaces. ainer tightly closed. sion-proof electrical/ ventilating/ lighting/ on-sparking tools. autionary measures against static discharge. ective gloves/ eye protection/ face protection. 2353 IF ON SKIN (or hair): Take off immediately clothing. Rinse skin with water/shower. P338 + P310 IF IN EYES: Rinse cautiously with minutes. Remove contact lenses, if present Continue rinsing. Immediately call a POISON tor/ physician.

#### Other hazards

Vapors may form explosive mixture with air.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture

### Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Ethanol	64-17-5	>= 5 - < 10
Dodecanoic acid	143-07-7	>= 5 - < 10
Ethanolamine	141-43-5	>= 1 - < 5
I-(+)-Lactic acid	79-33-4	>= 1 - < 5
4-chloro-3,5-dimethylphenol	88-04-0	>= 0.1 - < 1

#### **SECTION 4. FIRST AID MEASURES**

General advice	<ul> <li>In the case of accident or if you feel unwell, seek medical advice immediately.</li> <li>When symptoms persist or in all cases of doubt seek medical advice.</li> </ul>
If inhaled	: If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact	: Wash with water and soap as a precaution. Get medical attention if symptoms occur.
In case of eye contact	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.



Version 3.0	Revision Date: 05/05/2015	MSDS Number: 36491-00004	Date of last issue: 04/17/2015 Date of first issue: 12/11/2014	
		•	emove contact lens, if worn. ention immediately.	
If swallowed		: If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.		
Most important symptoms and effects, both acute and delayed		: Causes serious eye damage.		
Protection of first-aiders		and use the rec	nders should pay attention to self-protection, commended personal protective equipment tial for exposure exists.	
Note	s to physician	: Treat symptom	atically and supportively.	

## SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical	
Unsuitable extinguishing media	High volume water jet	
Specific hazards during fire fighting	Do not use a solid water stream as it may scatter and spr fire. Flash back possible over considerable distance. Vapors may form explosive mixtures with air. Exposure to combustion products may be a hazard to hea	
Hazardous combustion prod- ucts	Carbon oxides Nitrogen oxides (NOx)	
Specific extinguishing methods	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe so. Evacuate area.	
Special protective equipment for fire-fighters	In the event of fire, wear self-contained breathing apparate Use personal protective equipment.	tus.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions,	: Remove all sources of ignition.
protective equipment and	Use personal protective equipment.
emergency procedures	Follow safe handling advice and personal protective equipment recommendations.



Version 3.0	Revision Date: 05/05/2015	MSDS Number: 36491-00004	Date of last issue: 04/17/2015 Date of first issue: 12/11/2014	
Environmental precautions		<ul> <li>Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.</li> </ul>		
Methods and materials for containment and cleaning up		Soak up with ine Suppress (knock jet. For large spills, p containment to k can be pumped, container. Clean up remain absorbent. Local or national disposal of this r employed in the determine which Sections 13 and	ols should be used. In absorbent material. (a down) gases/vapors/mists with a water spray provide diking or other appropriate teep material from spreading. If diked material store recovered material in appropriate ing materials from spill with suitable regulations may apply to releases and naterial, as well as those materials and items cleanup of releases. You will need to regulations are applicable. 15 of this SDS provide information regarding ational requirements.	

#### SECTION 7. HANDLING AND STORAGE

Technical measures	: See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation	: Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation.
Advice on safe handling	<ul> <li>Avoid inhalation of vapor or mist. Do not swallow. Do not get in eyes. Avoid prolonged or repeated contact with skin. Handle in accordance with good industrial hygiene and safety practice. Non-sparking tools should be used. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment.</li> </ul>
Conditions for safe storage	<ul> <li>Keep in properly labeled containers.</li> <li>Keep tightly closed.</li> <li>Keep in a cool, well-ventilated place.</li> <li>Store in accordance with the particular national regulations.</li> <li>Keep away from heat and sources of ignition.</li> </ul>
Materials to avoid	: Do not store with the following product types:



Version	Revision Date:	MSDS Number:	Date of last issue: 04/17/2015
3.0	05/05/2015	36491-00004	Date of first issue: 12/11/2014
			s s stances and mixtures mixtures which in contact with water emit

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethanol	64-17-5	TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		STEL	1,000 ppm	ACGIH
Ethanolamine	141-43-5	TWA	3 ppm	ACGIH
		STEL	6 ppm	ACGIH
		TWA	3 ppm 8 mg/m3	NIOSH REL
		ST	6 ppm 15 mg/m3	NIOSH REL
		TWA	3 ppm 6 mg/m3	OSHA Z-1

#### Ingredients with workplace control parameters

#### Hazardous components without workplace control parameters

Ingredients	CAS-No.
Dodecanoic acid	143-07-7
I-(+)-Lactic acid	79-33-4
4-chloro-3,5-dimethylphenol	88-04-0

**Engineering measures** 

: Minimize workplace exposure concentrations.

Use only in an area equipped with explosion proof exhaust ventilation.

Use with local exhaust ventilation.

Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m3 - total dust, 5 mg/m3 - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m3 - respirable particles, 10 mg/m3 inhalable particles.



Vers 3.0	sion	Revision Date: 05/05/2015		DS Number: 491-00004	Date of last issue: 04/17/2015 Date of first issue: 12/11/2014	
	Persor	nal protective equipr	nent			
	Respira	atory protection	:	maintain vapor ex concentrations are unknown, appropr Follow OSHA resp use NIOSH/MSHA by air purifying res hazardous chemic supplied respirato release, exposure	exhaust ventilation is recommended to posures below recommended limits. Where e above recommended limits or are riate respiratory protection should be worn. birator regulations (29 CFR 1910.134) and A approved respirators. Protection provided spirators against exposure to any cal is limited. Use a positive pressure air r if there is any potential for uncontrolled levels are unknown, or any other re air purifying respirators may not provide on.	
	Hand p Mate	protection erial	:	Impervious gloves	3	
	Mate	erial	:	Flame retardant g	loves	
	Rem	arks	:	: Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.		
	Eye pro	otection	<ul> <li>Wear the following personal protective equipment: Chemical resistant goggles must be worn.</li> <li>If splashes are likely to occur, wear: Face-shield</li> </ul>		t goggles must be worn.	
	Skin ar	nd body protection	:	<ul> <li>Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.</li> <li>Wear the following personal protective equipment: Flame retardant antistatic protective clothing.</li> <li>Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).</li> </ul>		
	Hygien	e measures	:	located close to the When using do not	ushing systems and safety showers are he working place. ht eat, drink or smoke. ed clothing before re-use.	

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: Clear, colorless to pale yellow
Odor	: Fragrance free



Vers 3.0	sion	Revision Date: 05/05/2015		DS Number: 91-00004	Date of last issue: 04/17/2015 Date of first issue: 12/11/2014
	Odor Th	nreshold	:	No data available	
	рН		:	7.8 - 9.7	
	Melting	point/freezing point	:	No data available	
	Initial bo range	oiling point and boiling	:	No data available	
	Flash p	oint	:	45.6 °C	
	Evapora	ation rate	:	No data available	
	Flamma	ability (solid, gas)	:	Not applicable	
	Upper e	explosion limit	:	No data available	
	Lower e	explosion limit	:	No data available	
	Vapor p	pressure	:	No data available	
	Relative	e vapor density	:	No data available	
	Density		:	1 g/cm3	
	Solubilit Wate	ty(ies) er solubility	:	soluble	
	Partitior octanol	n coefficient: n- /water	:	Not applicable	
	Autoign	ition temperature	:	No data available	
	Decom	position temperature	:	The substance or	mixture is not classified self-reactive.
	Viscosit Visco	y osity, kinematic	:	10 - 20 mm2/s (2	0 °C)
	Explosiv	ve properties	:	Not explosive	
	Oxidizir	ng properties	:	The substance or	mixture is not classified as oxidizing.

## SECTION 10. STABILITY AND REACTIVITY

:	Not classified as a reactivity hazard.
:	Stable under normal conditions.
:	Flammable liquid and vapor. Vapors may form explosive mixture with air. Can react with strong oxidizing agents.
:	Heat, flames and sparks.
	:



Version 3.0	Revision Date: 05/05/2015		DS Number: 91-00004	Date of last issue: 04/17/2015 Date of first issue: 12/11/2014
Incom	patible materials	:	Oxidizing age	nts
Hazar produ	dous decomposition	:	No hazardous	decomposition products are known.
SECTION	11. TOXICOLOGICAL	. INFC	RMATION	
Inhala Skin o Ingest	contact	s of e	xposure	
Acute	e toxicity			
Not cl	assified based on avai	lable i	nformation.	
<u>Produ</u>				
Acute	oral toxicity	:	Acute toxicity e Method: Calcu	estimate: > 5,000 mg/kg lation method
Acute	inhalation toxicity	:	Acute toxicity of Exposure time Test atmosphe Method: Calcu	ere: vapor
Acute	dermal toxicity	:	Acute toxicity e Method: Calcu	estimate: > 5,000 mg/kg lation method
	dients:			
Ethar Acute	oral toxicity	:	LD50 (Rat): >	5,000 mg/kg
Acute	inhalation toxicity	:	LC50 (Rat): 12 Exposure time Test atmosphe	:4 h
	canoic acid: oral toxicity	:	LD50 (Rat): > Method: OECI	5,000 mg/kg ) Test Guideline 401
Acute	inhalation toxicity	:	LC50 (Rat): > Exposure time Test atmosphe Remarks: Bas	:4 h
Acute	dermal toxicity		Assessment: T toxicity	> 2,000 mg/kg The substance or mixture has no acute dermal ed on data from similar materials
	olamine: oral toxicity	:	LD50 (Rat): 1,	515 mg/kg
Acute	Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l			



ersion .0	Revision Date: 05/05/2015	MSDS Number: 36491-00004	Date of last issue: 04/17/2015 Date of first issue: 12/11/2014		
		Test atmosphe Method: Expert Remarks: Base 1272/2008, Anr	judgment d on harmonised classification in EU regulatio		
Acute	dermal toxicity	: LD50 (Rabbit):	1,025 mg/kg		
	actic acid: oral toxicity	: LD50 (Rat, fem	ale): 3,543 mg/kg		
Acute	inhalation toxicity	Exposure time: Test atmosphe	LC50 (Rat): > 7.94 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403		
Acute	dermal toxicity	: LD50 (Rabbit):	> 2,000 mg/kg		
	oro-3,5-dimethylphen oral toxicity	: Acute toxicity e Method: Expert	d on harmonised classification in EU regulatio		
Acute	inhalation toxicity	: LC50 (Rat): > 6 Test atmosphe			
Acute	dermal toxicity	: LD50 (Rat): > 2	2,000 mg/kg		
-	corrosion/irritation assified based on avai	lable information.			
<u>Produ</u> Resul	<u>uct:</u> t: No skin irritation				
Ethar Speci Metho	<b>dients:</b> <b>iol:</b> es: Rabbit od: OECD Test Guideli t: No skin irritation	ne 404			
Speci Metho	<b>canoic acid:</b> es: Rabbit od: OECD Test Guideli t: No skin irritation	ne 404			
Speci	<b>nolamine:</b> es: Rabbit t: Corrosive after 3 mir	nutes to 1 hour of expo	osure		
Speci	<b>-actic acid:</b> es: Rabbit t: Skin irritation				

## 4-chloro-3,5-dimethylphenol:



Version	Revision Date:	MSDS Number:
3.0	05/05/2015	36491-00004

Date of last issue: 04/17/2015 Date of first issue: 12/11/2014

#### Result: Skin irritation

Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

#### Serious eye damage/eye irritation

Causes serious eye damage.

#### Ingredients:

**Ethanol:** Species: Rabbit Result: Irritation to eyes, reversing within 21 days Method: OECD Test Guideline 405

#### Dodecanoic acid:

Species: Rabbit Result: Irreversible effects on the eye Method: OECD Test Guideline 405

#### Ethanolamine:

Species: Rabbit Result: Irreversible effects on the eye

I-(+)-Lactic acid: Species: Chicken eye Result: Irreversible effects on the eye

#### 4-chloro-3,5-dimethylphenol:

Result: Irreversible effects on the eye

#### Respiratory or skin sensitization

Skin sensitization: Not classified based on available information. Respiratory sensitization: Not classified based on available information.

#### Product:

Assessment: Does not cause skin sensitization.

#### Ingredients:

Ethanol:

Test Type: Local lymph node assay (LLNA) Routes of exposure: Skin contact Species: Mouse Result: negative

#### Dodecanoic acid:

Test Type: Maximization Test (GPMT) Routes of exposure: Skin contact Species: Guinea pig Result: negative

#### Ethanolamine:

Test Type: Maximization Test (GPMT) Routes of exposure: Skin contact Species: Guinea pig Result: negative



ersion 0	Revision Date: 05/05/2015	MSDS Number: 36491-00004	Date of last issue: 04/17/2015 Date of first issue: 12/11/2014
Test T Route Specie	actic acid: ype: Buehler Test s of exposure: Skin cor es: Guinea pig t: negative	ntact	
Asses	oro-3,5-dimethylphend sment: Probability or ev rks: Based on harmonis	vidence of skin sensit	ization in humans U regulation 1272/2008, Annex VI
	cell mutagenicity assified based on availa	able information.	
Ingred	dients:		
<b>Ethan</b> Genot	<b>ol:</b> oxicity in vitro	: Test Type: In vi Result: negative	tro mammalian cell gene mutation test
Genot	oxicity in vivo	: Test Type: Rod Species: Mouse Application Rou Result: negative	te: Ingestion
	canoic acid: oxicity in vitro	Method: OECD Result: negative	tro mammalian cell gene mutation test Test Guideline 476 e d on data from similar materials
	olamine: oxicity in vitro		tro mammalian cell gene mutation test Test Guideline 476 e
Genot	oxicity in vivo	cytogenetic ass Species: Mouse Application Rou	te: Ingestion Test Guideline 474
	actic acid: oxicity in vitro	Metabolic activa Result: negative	omosome aberration test in vitro ation: with and without metabolic activation e d on data from similar materials
			erial reverse mutation assay (AMES) ation: with and without metabolic activation
	oro-3,5-dimethylpheno oxicity in vitro		erial reverse mutation assay (AMES)



Version 3.0	Revision Date: 05/05/2015	-	DS Number: 91-00004	Date of last issue: 04/17/2015 Date of first issue: 12/11/2014
	nogenicity			
	assified based on availa	ble ir	nformation.	
<b>I-(+)-L</b> Specie Applic Expos Result	dients: actic acid: es: Rat ation Route: Ingestion ure time: 2 Years :: negative rks: Based on data from	ı simi	lar materials	
IARC		equ		product present at levels greater than or tified as probable, possible or confirmed y IARC.
OSH/	A	equ		product present at levels greater than or tified as a carcinogen or potential carcino-
NTP		equ		product present at levels greater than or tified as a known or anticipated carcinogen
Not cla Ingred Ethan	ductive toxicity assified based on availa <u>dients:</u> ol: s on fertility	:		
	c <b>anoic acid:</b> s on fertility		reproduction/deve Species: Rat Application Route Method: OECD To Result: negative	
Effect	s on fetal development		reproduction/deve Species: Rat Application Route Method: OECD To Result: negative	
	<b>olamine:</b> s on fertility	:	Test Type: Two-g	eneration reproduction toxicity study



Version 3.0	Revision Date: 05/05/2015	MSDS Number: 36491-00004	Date of last issue: 04/17/2015 Date of first issue: 12/11/2014
		Species: Rat Application Rou Result: negative	
Effect	ts on fetal developmen	Species: Rat Application Rou	Test Guideline 414
	<b>-single exposure</b> lassified based on avai	ilable information.	
Ethar	<u>dients:</u> nolamine: ssment: May cause res	spiratory irritation.	
	L <b>actic acid:</b> ssment: May cause res	spiratory irritation.	
	<b>F-repeated exposure</b> lassified based on avai	ilable information.	
<b>Ethar</b> Route			d in animals at concentrations of 0.2 mg/l/6h/c
Repe	ated dose toxicity		
<b>Ethar</b> Speci NOAE Applic	dients: nol: es: Rat EL: 2,400 mg/kg cation Route: Ingestion sure time: 2 y	1	
Speci NOAE Applic	canoic acid: les: Rat EL: 10,000 mg/kg cation Route: Ingestion sure time: 18 w	I	
Speci NOAE Applic	<b>nolamine:</b> les: Rat EL: 150 mg/m3 cation Route: inhalation sure time: 28 d	n (dust/mist/fume)	
Speci	Lactic acid: les: Rat		



Version	Revision Date:	MSDS Number:
3.0	05/05/2015	36491-00004

Date of last issue: 04/17/2015 Date of first issue: 12/11/2014

Application Route: Skin contact Exposure time: 13 w

## 4-chloro-3,5-dimethylphenol:

Species: Rabbit LOAEL: 180 mg/kg Application Route: Skin contact Exposure time: 90 d

## Aspiration toxicity

Not classified based on available information.

## **SECTION 12. ECOLOGICAL INFORMATION**

#### Ecotoxicity

## Ingredients:

Ethanol: Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 48 h
Toxicity to algae	:	EC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 9.6 mg/l Exposure time: 9 d
Toxicity to bacteria	:	EC50 (Photobacterium phosphoreum): 32.1 mg/l Exposure time: 0.25 h
<b>Dodecanoic acid:</b> Toxicity to fish	:	LC50 (Oryzias latipes (Japanese medaka)): 5 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 3.6 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	:	EC50 (Selenastrum capricornutum (green algae)): > 7.6 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: No toxicity at the limit of solubility.
		NOEC (Selenastrum capricornutum (green algae)): > 7.6 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: No toxicity at the limit of solubility.



Version 3.0	Revision Date: 05/05/2015	MSDS Number:Date of last issue: 04/17/201536491-00004Date of first issue: 12/11/2014	
Toxici toxicit	ity to fish (Chronic y)	: NOEC (Danio rerio (zebra fish)): 2 mg/l Exposure time: 28 d Remarks: Based on data from similar materials	
aquat	ty to daphnia and other ic invertebrates nic toxicity)	: NOEC (Daphnia magna (Water flea)): 0.47 mg/l Exposure time: 21 d Method: OECD Test Guideline 211	
Toxici	ty to bacteria	EC10 (Pseudomonas putida): > 1,000 mg/l Exposure time: 30 min Method: OECD Test Guideline 209	
	<b>nolamine:</b> ity to fish	: LC50 (Cyprinus carpio (Carp)): 349 mg/l Exposure time: 96 h	
	ty to daphnia and other ic invertebrates	: EC50 (Daphnia magna (Water flea)): 65 mg/l Exposure time: 48 h	
Toxici	ity to algae	: ErC50 (Selenastrum capricornutum (green algae)): 2.8 mg Exposure time: 72 h	g/l
		NOEC (Scenedesmus capricornutum (fresh water algae)): mg/l Exposure time: 72 h	: 1
Toxici toxicit	ty to fish (Chronic y)	: NOEC (Oryzias latipes (Orange-red killifish)): 1.24 mg/l Exposure time: 41 d	
aquat	ity to daphnia and other ic invertebrates nic toxicity)	: NOEC (Daphnia magna (Water flea)): 0.85 mg/l Exposure time: 21 d	
Toxici	ty to bacteria	: EC50 (Pseudomonas putida): 110 mg/l Exposure time: 17 h	
	<b>.actic acid:</b> ity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 130 mg/l Exposure time: 96 h	
	ty to daphnia and other ic invertebrates	: EC50 (Daphnia magna (Water flea)): 250 mg/l Exposure time: 48 h Method: OECD Test Guideline 202	
Toxici	ty to algae	<ul> <li>NOEC (Selenastrum capricornutum (fresh water algae)): 1 g/l</li> <li>Exposure time: 72 h</li> <li>Method: OECD Test Guideline 201</li> </ul>	1.9
		EC50 (Selenastrum capricornutum (fresh water algae)): 3. Exposure time: 72 h Method: OECD Test Guideline 201	.5 g/l
Toxici	ty to bacteria	: EC50: > 100 mg/l Exposure time: 3 h	



Vers 3.0	sion	Revision Date: 05/05/2015		DS Number: 491-00004	Date of last issue: 04/17/2015 Date of first issue: 12/11/2014	
				Method: OECD Te	est Guideline 209	
	4-chloro-3,5-dimethylphenol Toxicity to fish			LC50 (Oncorhync Exposure time: 96	hus mykiss (rainbow trout)): 0.76 mg/l bh	
	Toxicity to daphnia and other aquatic invertebrates			EC50 (Daphnia m Exposure time: 48		
	M-Fact icity)	or (Acute aquatic tox-	:	1		
	Persistence and degradability					
	Ingred					
	Ethanc Biodeg	n: radability	:	Result: Readily bio Biodegradation: 8 Exposure time: 20	34 %	
		<b>anoic acid:</b> radability	:	Result: Readily bio Biodegradation: 8 Exposure time: 30 Method: OECD Te	36 %	
		<b>lamine:</b> radability	:	Result: Readily bio Biodegradation: > Exposure time: 21	• 90 <sup>°</sup> %	
		radability	:	Result: Not readily Biodegradation: 6 Exposure time: 20	67 %	
	Bioacc	umulative potential				
	Ingredi Ethanc Partitio octanol	<b>l:</b> n coefficient: n-	:	log Pow: -0.35		
		anoic acid: umulation	:		actor (BCF): 234 - 288 on data from similar materials	
	Partitio octanol	n coefficient: n- /water	:	Pow: 4.6		
		<b>llamine:</b> n coefficient: n- /water	:	log Pow: -1.91		



Version 3.0	Revision Date: 05/05/2015	MSDS Number: 36491-00004	Date of last issue: 04/17/2015 Date of first issue: 12/11/2014
Partit	Lactic acid: ion coefficient: n- iol/water	: log Pow: -0.6	
Partit	oro-3,5-dimethylphe ion coefficient: n- ol/water	nol: : log Pow: 3.27	
	<b>lity in soil</b> ata available		
	r adverse effects ata available		

Disposal methods	
Waste from residues	: Dispose of in accordance with local regulations.
Contaminated packaging	<ul> <li>Dispose of as unused product.</li> <li>Empty containers should be taken to an approved waste handling site for recycling or disposal.</li> <li>Do not burn, or use a cutting torch on, the empty drum.</li> </ul>

## SECTION 14. TRANSPORT INFORMATION

: UN 1	993
: FLAN	MMABLE LIQUID, N.O.S.
(Etha	anol)
: 3	
: 111	
: 3	
: UN 1	993
: Flam	mable liquid, n.o.s.
(Etha	anol)
: 3	
: 111	
: Flam	mable Liquids
: 366	
: 355	
: UN 1	993
	(Etha : 3 : III : 3 : UN 1 : Flam (Etha : 3 : III : Flam : 366



Version 3.0	Revision Date: 05/05/2015	MSDS Number: 36491-00004	Date of last issue: 04/17/2015 Date of first issue: 12/11/2014
Proper shipping name Class Packing group Labels EmS Code Marine pollutant		: FLAMMABLE (Ethanol) : 3 : III : 3 : F-E, <u>S-E</u> : no	ELIQUID, N.O.S.
	sport in bulk accordin pplicable for product a	-	ARPOL 73/78 and the IBC Code
	estic regulation	s supplied.	
Prope	/NA number er shipping name	: NA 1993 : COMBUSTIB (Ethanol) : CBL : III	LE LIQUID, N.O.S.
	Code e pollutant		s only to containers over 119 gallons or 450 ulated if shipped in packages less than or equal s (450 liters).

## SECTION 15. REGULATORY INFORMATION

#### EPCRA - Emergency Planning and Community Right-to-Know

### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	Fire Hazard Acute Health Hazard	
SARA 302	No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.	
SARA 313	This material does not contain any chemical components known CAS numbers that exceed the threshold (De Minim reporting levels established by SARA Title III, Section 313	nis)

#### **US State Regulations**

Pennsylvania Right To Know				
Water	7732-18-5	70 - 90 %		
Ethanol	64-17-5	5 - 10 %		
Dodecanoic acid	143-07-7	5 - 10 %		




ersion .0	Revision Date: 05/05/2015	MSDS Number: 36491-00004	Date of last issue: 04/17/2 Date of first issue: 12/11/2	
	Ethanolam		141-43-5	1 - 5 %
	Dipropyler Propan-2-	•••	25265-71-8 67-63-0	1 - 5 % 0.1 - 1 %
New .	Jersey Right To Kno	w		
	Water		7732-18-5	70 - 90 %
	Ethanol		64-17-5	5 - 10 %
	Dodecano	ic acid	143-07-7	5 - 10 %
	Ethanolam	nine	141-43-5	1 - 5 %
	Dipropyler	ne glycol	25265-71-8	1 - 5 %
Califo	ornia Prop 65	•	bes not contain any chemicals nia to cause cancer, birth, or a efects.	
The i	ngredients of this pr	oduct are reported in	the following inventories:	
AICS		: All ingredients	-	
		-		

### Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

## **SECTION 16. OTHER INFORMATION**



#### Full text of other abbreviations

ACGIH NIOSH REL OSHA Z-1	USA. ACGIH Threshold Limit Values (TLV) USA. NIOSH Recommended Exposure Limits USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lir its for Air Contaminants	
ACGIH / TWA ACGIH / STEL NIOSH REL / TWA	<ul> <li>8-hour, time-weighted average</li> <li>Short-term exposure limit</li> <li>Time-weighted average concentration for up to a 10-hour</li> </ul>	



Version 3.0	Revision Date: 05/05/2015		SDS Number: 491-00004	Date of last issue: 04/17/2015 Date of first issue: 12/11/2014	
NIOSH REL / ST OSHA Z-1 / TWA		<ul> <li>workday during a 40-hour workweek</li> <li>STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday</li> <li>8-hour time weighted average</li> </ul>			
Sources of key data used to compile the Material Safety Data Sheet		:	: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen- cy, http://echa.europa.eu/		
Revision Date		:	05/05/2015		

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8