LIGHTHOUSE for the BLIND ST. LOUIS, MO.

SDS Revision Date:

07/31/2019

1. Identification

1.1. Product identifier		
Product Identity		
Alternate Names		

Metered Mist Apple Delight

Metered Mist Apple Delight LHB Part Number: 0744---003 CAGE 0FTT5 National Stock Number: 6840-01-368-4787

1.2. Relevant identified uses of the substance or mixture and uses advised against		
Intended use	See Technical Data Sheet.	
Application Method	See Product Label	
1.3 Details of the supplier of the safety data sheet		

1.3. Details of the supplier of the safety data sheet Company Name

LHB Industries 8833 Fleischer Place Berkeley, MO 63134

Emergency 24 hour Emergency Telephone No. Customer Service: LHB Industries

(800) 633-8253 (PERS) (314) 423-4333

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Flam. Aerosol 1;H222	Extremely flammable aerosol.
Press. Gas;H280	Contains gas under pressure; may explode if heated.
Eye Irrit. 2;H319	Causes serious eye irritation.
STOT SE 3;H336	May cause drowsiness or dizziness.
Simple Asphyxiant	May displace oxygen and cause rapid suffocation.
2.2. Label elements	



SDS Revision Date:

07/31/2019



H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

May displace oxygen and cause rapid suffocation.

Pressurized container: May burst if heated.

[Prevention]:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P211 Do not spray on an open flame or other ignition source.

P233 Keep container tightly closed.

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P337+313 If eye irritation persists: Get medical advice / attention.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

SDS Revision Date:

07/31/2019



3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Acetone CAS Number: 0000067-64-1	50 - 75	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]
Propane CAS Number: 0000074-98-6	10 - 25	Flam. Gas 1;H220 Press. Gas;H280	[1][2]
1,2-Propylene glycol CAS Number: 0000057-55-6	10 - 25	Asp. Tox. 1;H304	[1]
Ethanol CAS Number: 0000064-17-5	5 - 10	Flam. Liq. 2;H225 Eye Irrit. 2;H319 (@ > 50%)	[1][2]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.
*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	DO NOT INDUCE VOMITING. Give nothing by mouth. Get immediate medical attention.
4.2. Most important syr	nptoms and effects, both acute and delayed
Overview	 INHALATION: May be irritating to upper respiratory tract. SKIN: Low potential of causing irritation following exposure. Not absorbed topically. Some reddening of the skin may occur with lengthy exposure. EYE CONTACT: May cause mild irritation. INGESTION: No significant signs or symptoms indicative of any adverse health hazard are expected to occur as a result of ingestion. Large amounts may cause gastric disturbances. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous

SDS Revision Date:

07/31/2019



membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

InhalationMay cause drowsiness or dizziness.EvesCauses serious eve irritation.

5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray. Do not use: water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Carbon dioxide and carbon monoxide

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Do not spray on an open flame or other ignition source.

Keep container tightly closed.

Ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing dust / fume / gas / mist / vapors / spray.

5.3. Advice for fire-fighters

FIRE FIGHTING EQUIPMENT: Fire fighters should wear full protective equipment, and have self-contained breathing apparatus available.

SPECIAL PROCEDURES: Use water to cool containers exposed to a fire.

ERG Guide No. 126

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

SDS Revision Date:

07/31/2019



6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Avoid inhalation. Use good ventilation. Read entire label before using and follow all label directions. Dispose of in accordance with applicable Federal, State & Local regulations. Remove ignition sources and work with non-sparking tools. Use oil absorbent materials.

7. Handling and storage

7.1. Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

Keep out of reach of children. Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively. During use and until all vapors are gone: keep area ventilated- DO NOT SMOKE- Extinguish all flames, pilot lights, and heaters- Turn off stoves, electric tools and appliances, and any other source of ignition. Consult NFPA Code. Use approved Bonding and Grounding procedures. Contents under pressure. Do not puncture, incinerate, or expose to temperatures above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst, do not take internally.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials: Oxidizing agents, strong acids.

Category NFPA 30B Level 2 Aerosol Do not store where temperatures may exceed 120F (48.9C) See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

See Product Label

8. Exposure controls and personal protection

8.1. Control parameters

Exposure				
CAS No.	Ingredient	Source	Value	
0000057-55-6	1,2-Propylene glycol	OSHA	No Established Limit	
		ACGIH	TWA(Aerosol): 10 mg/m3	
		NIOSH	No Established Limit	
		Supplier	10 mg/m3 TWA (listed as AIHA WEEL)	

Evneeure



SDS Revision Date:

07/31/2019

0000064-17-5	Ethanol	OSHA	TWA 1000 ppm (1900 mg/m3)
		ACGIH	STEL: 1000 ppm Revised 2009,
		NIOSH	TWA 1000 ppm (1900 mg/m3)
		Supplier	No Established Limit
0000067-64-1 Acet	Acetone	OSHA	TWA 1000 ppm (2400 mg/m3) STEL 2400 mg/m3
		ACGIH	TWA: 500 ppm STEL: 750 ppm
		NIOSH	250 ppm (590 mg/m3) TWA
		Supplier	No Established Limit
0000074-98-6	Propane	OSHA	TWA 1000 ppm (1800 mg/m3)
		ACGIH	Ensure Minimal Oxygen Content (ACGIH appendix F)
		NIOSH	TWA 1000 ppm (1800 mg/m3)
		Supplier	No Established Limit

8.2. Exposure controls

o.z. Exposure controls	
Respiratory	If personal exposure cannot be controlled to below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2. When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust that may be generated from this product, underlying paint, or the abrasive.
Eyes	Wear safety glasses with side shields to protect the eyes. An eye wash station is suggested as a good workplace practice.
Skin	Wear overalls to keep skin contact to a minimum. Chemical resistant gloves may be needed for long term skin exposure.
Engineering Controls	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.
See section 2 for further	details.

9. Physical and chemical properties

Appearance	Colorless to light yellow Liquid
Odor	Peach
Odor threshold	Not determined
рН	Not Determined
Melting point / freezing point	Not Determined
Initial boiling point and boiling range	Not Determined
Flash Point	-156°F (Propane)



SDS Revision Date:

07/31/2019

Evaporation rate (Ether = 1) Flammability (solid, gas) Upper/lower flammability or explosive limits

Vapor pressure (Pa) Vapor Density Specific Gravity Solubility in Water Partition coefficient n-octanol/water (Log Kow) Auto-ignition temperature Decomposition temperature Viscosity (cSt) VOC Content Maximum Incremental Reactivity % Volatile (by volume) Not Determined Not Applicable Lower Explosive Limit: Not Determined Upper Explosive Limit: Not Determined Not Determined Not Determined Not Measured Insoluble Not Measured Not Determined Not Determined Not Determined <30 % by Wt. N/A 100

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.
10.2. Chemical stability
Stable under normal circumstances.
10.3. Possibility of hazardous reactions
No data available.
10.4. Conditions to avoid
Temperatures above 160 C
10.5. Incompatible materials
Oxidizing agents, strong acids.
10.6. Hazardous decomposition products
Carbon dioxide and carbon monoxide



SDS Revision Date:

07/31/2019

11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Acetone - (67-64-1)	5,800.00, Rat - Category: NA	7,426.00, Guinea Pig - Category: NA	76.00, Rat - Category: NA	50.10, Rat - Category: NA	No data available
Propane - (74-98-6)	No data available	No data available	658.00, Rat - Category: NA	No data available	No data available
1,2-Propylene glycol - (57-55-6)	20,000.00, Rat - Category: NA	20,800.00, Rabbit - Category: NA	105.00, Rat - Category: NA	No data available	No data available
Ethanol - (64-17-5)	7,060.00, Rat - Category: NA	20,000.00, Rabbit - Category: NA	124.70, Rat - Category: NA	No data available	No data available

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000057-55-6	1,2-Propylene glycol	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000064-17-5	Ethanol	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000067-64-1 Acetone		OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000074-98-6 Propane		OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;



SDS Revision Date:

07/31/2019

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation		Not Applicable
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-single exposure		Not Applicable
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable

12. Ecological information

12.1. Toxicity

Toxic to aquatic life

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Acetone - (67-64-1)	100.00, Pimephales promelas	10.00, Daphnia magna	20.565 (72 hr), Ulva pertusa
Propane - (74-98-6)	Not Available	Not Available	Not Available
1,2-Propylene glycol - (57-55-6)	40,613.00, Oncorhynchus mykiss	18,340.00, Ceriodaphnia dubia	19,000.00 (96 hr), Pseudokirchneriella subcapitata
Ethanol - (64-17-5)	42.00, Oncorhynchus mykiss	2.00, Daphnia magna	17.921 (96 hr), Ulva pertusa

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

SDS Revision Date:

07/31/2019



12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA	
14.1. UN number	UN1950	UN1950	UN1950	
14.2. UN proper shipping name	UN1950, Aerosols, Limited Quantity, 2.1,	Aerosols, Limited Quantity	Aerosols, Limited Quantity	
14.3. Transport hazard class(es)	DOT Hazard Class: 2.1	IMDG: 2.1 Sub Class: Not Applicable	Air Class: 2.1	
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable	
14.5. Environmental hazards				
IMDG Marine Pollutant: No;				
14.6. Special precautions for user: No further information				

15. Regulatory information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.	
Toxic Substance Control Act (TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.	
WHMIS 1988 Classification	A B5 D2B	
US EPA Tier II Hazards	Fire: Yes	
	Sudden Release of Pressure: Yes	
	Reactive: No	
	Immediate (Acute): Yes	
	Delayed (Chronic): No	

SDS Revision Date:

07/31/2019



Note: Ethanol (Ethyl alcohol) has been placed on the California Proposition 65 Cancer and Developmental Lists when in alcoholic beverages.

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

Ethanol

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

16. Other information

SDS Revision Date 07/31/2019

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

- H225 Highly flammable liquid and vapor.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness and dizziness.

IMPORTANT NOTE: This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or any process. Final determination of suitability of any material is the sole responsibility of the user.

End of Document