

Version 1.2	Revision Date: 03/18/2015		SDS Number: 6799-00003	Date of last issue: 02/10/2015 Date of first issue: 12/12/2014		
SECTION	1. IDENTIFICATION					
Produ	ict name	:	: PURELL® SKILCRAFT®Instant Hand Sanitizer with Aloe			
Produ	ict code	:	3143-0072 (8520-01-522-3888)			
Manu	facturer or supplier's	deta	ails			
Comp	eany name of supplier	:	Austin Lighthouse Travis Association for the Blind			
Address		:	2307 Business Center Drive Austin TX 78744			
Telephone		:	1-888-217-7232			
Emer	gency telephone	:	1-888-714-3496			
Reco	mmended use of the c	cher	nical and restriction	ons on use		
Recor	mmended use	:	Hand Sanitizer			
Restri	ictions on use	:	consumers and o foreseeable use. specifically define exempt from the n While this materia contains valuable proper use of the as well as unusua spills. This SDS s employees and o intended-use guid	I care or cosmetic product that is safe for ther users under normal and reasonably Cosmetics and consumer products, d by regulations around the world, are requirement of an SDS for the consumer. al is not considered hazardous, this SDS information critical to the safe handling and product for industrial workplace conditions al and unintended exposures such as large hould be retained and available for ther users of this product. For specific lance, please refer to the information ackage or instruction sheet.		

SECTION 2. HAZARDS IDENTIFICATION

GHS Label element Hazard pictograms	
Eye irritation	: Category 2A
GHS Classification Flammable liquids	: Category 3



Version 1.2	Revision Date: 03/18/2015	MSDS Number: 36799-00003	Date of last issue: 02/10/2015 Date of first issue: 12/12/2014			
Signa	ll Word	: Warning				
Haza	rd Statements		 H226 Flammable liquid and vapor. H319 Causes serious eye irritation. 			
Preca	autionary Statements	No smoking. P233 Keep cont P241 Use explose equipment. P242 Use only r P243 Take prect P264 Wash skin P280 Wear prote Response: P303 + P361 + I all contaminated P305 + P351 + I for several minut to do. Continue f P337 + P313 If e attention. Storage: P403 + P235 Ste Disposal:	y from heat/sparks/open flames/hot surfaces. ainer tightly closed. sion-proof electrical/ ventilating/ lighting/ non-sparking tools. autionary measures against static discharge. thoroughly after handling. ective gloves/ eye protection/ face protection. P353 IF ON SKIN (or hair): Take off immediately clothing. Rinse skin with water/shower. P338 IF IN EYES: Rinse cautiously with water tes. Remove contact lenses, if present and easy rinsing. eye irritation persists: Get medical advice/ ore in a well-ventilated place. Keep cool. f contents/ container to an approved waste			
Othe	r hazards					

Other hazards

Vapors may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Ethanol	64-17-5	>= 50 - < 70
Propan-2-ol	67-63-0	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice	:	In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.
If inhaled	:	If inhaled, remove to fresh air. Get medical attention if symptoms occur.



Version 1.2	Revision Date: 03/18/2015	MSDS Number: 36799-00003	Date of last issue: 02/10/2015 Date of first issue: 12/12/2014		
In case of skin contact			ater and soap as a precaution. attention if symptoms occur.		
In case of eye contact		 In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lens, if worn. Get medical attention. 			
If swallowed		Get medical a	: If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.		
Most important symptoms and effects, both acute and delayed		: Causes serio	us eye irritation.		
Prote	ection of first-aiders	and use the r	onders should pay attention to self-protection, ecommended personal protective equipment ential for exposure exists.		
Note	s to physician	: Treat symptomatically and supportively.			

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Dry chemical Carbon dioxide (CO2)
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire fighting	:	Do not use a solid water stream as it may scatter and spread fire. Flash back possible over considerable distance. Vapors may form explosive mixtures with air. Exposure to combustion products may be a hazard to health.
Hazardous combustion prod- ucts	:	Carbon oxides
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.



Version	Revision Date:	MSDS Number:	Date of last issue: 02/10/2015
1.2	03/18/2015	36799-00003	Date of first issue: 12/12/2014

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.
Environmental precautions	 Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	 Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapors/mists with a water spray jet. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures	: See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation	: Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation.
Advice on safe handling	 Do not breathe vapors or spray mist. Do not swallow. Do not get in eyes. Avoid prolonged or repeated contact with skin. Handle in accordance with good industrial hygiene and safety practice. Non-sparking tools should be used. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the



Version 1.2	Revision Date: 03/18/2015	MSDS Number: 36799-00003	Date of last issue: 02/10/2015 Date of first issue: 12/12/2014
		environment.	
Condit	ions for safe storage	Keep tightly clos Keep in a cool, Store in accorda	y labeled containers. sed. well-ventilated place. ance with the particular national regulations. h heat and sources of ignition.
Materia	als to avoid	Strong oxidizing Organic peroxid Flammable solid Pyrophoric liquid Pyrophoric solid Self-heating sub	es ds ds ls ostances and mixtures d mixtures which in contact with water emit

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethanol	64-17-5	TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		STEL	1,000 ppm	ACGIH
Propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1

Biological occupational exposure limits

Ingredients	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentratio n	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work- week	40 mg/l	ACGIH BEI

Engineering measures

: Minimize workplace exposure concentrations.



Version 1.2	Revision Date: 03/18/2015	MSDS 1 36799-0	Number:)0003	Date of last issue: 02/10/2015 Date of first issue: 12/12/2014
		vent	ilation.	area equipped with explosion proof exhaust exhaust ventilation.
Pers	onal protective equip	ment		
	piratory protection	: Gen main cond unkn Folld use by a haza supp relea circu	ntain vapor centrations nown, appro ow OSHA ro NIOSH/MS ir purifying ardous chei blied respira ase, exposi	cal exhaust ventilation is recommended to exposures below recommended limits. Where are above recommended limits or are opriate respiratory protection should be worn. espirator regulations (29 CFR 1910.134) and HA approved respirators. Protection provided respirators against exposure to any mical is limited. Use a positive pressure air ator if there is any potential for uncontrolled ure levels are unknown, or any other there air purifying respirators may not provide ction.
	d protection aterial	: Imp	ervious glov	/es
Ma	Material		ne retardan	t gloves
Re	Remarks		ne concentr is not dete special app stance to ch es with the	to protect hands against chemicals depending ration specific to place of work. Breakthrough rmined for the product. Change gloves often! lications, we recommend clarifying the nemicals of the aforementioned protective glove manufacturer. Wash hands before he end of workday.
Eye	protection		ar the follow ety goggles	ring personal protective equipment:
Skin	and body protection	resis pote Wea Flan Skin	stance data ential. ar the follow ne retardan i contact mi	ate protective clothing based on chemical and an assessment of the local exposure ving personal protective equipment: t antistatic protective clothing. ust be avoided by using impervious protective s, aprons, boots, etc).
Hygi	ene measures	loca Whe	ted close to en using do	e flushing systems and safety showers are the working place. not eat, drink or smoke. nated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance



Vers 1.2	sion	Revision Date: 03/18/2015		DS Number: ′99-00003	Date of last issue: 02/10/2015 Date of first issue: 12/12/2014
	. .				
	Color		:	clear, light green	
	Odor		:	alcohol-like	
	Odor T	hreshold	:	No data available	9
	рН		:	6.5 - 8.5	
	Melting	point/freezing point	:	No data available	9
	Initial b range	oiling point and boiling	:	76 °C	
	Flash p	point	:	24 °C	
	Evapor	ation rate	:	No data available	9
	Flamm	ability (solid, gas)	:	Not applicable	
	Upper	explosion limit	:	No data available	9
	Lower	explosion limit	:	No data available	9
	Vapor p	oressure	:	No data available	9
	Relativ	e vapor density	:	No data available)
	Density	/	:	0.881 g/cm3	
	0.1.1.1				
	Solubili Wate	ty(les) er solubility	:	soluble	
	Partitio octanol	n coefficient: n- /water	:	Not applicable	
	Autoigr	nition temperature	:	No data available	9
	Decom	position temperature	:	The substance of	r mixture is not classified self-reactive.
	Viscosi Visc	ty osity, kinematic	:	3,500 - 23,000 m	m2/s (20 °C)
	Explosi	ve properties	:	Not explosive	
	Oxidizi	ng properties	:	The substance of	r mixture is not classified as oxidizing.

SECTION 10. STABILITY AND REACTIVITY

Reactivity

: Not classified as a reactivity hazard.



Version 1.2	Revision Date: 03/18/2015		DS Number: 799-00003	Date of last issue: 02/10/2015 Date of first issue: 12/12/2014
Che	mical stability	:	Stable under nor	mal conditions.
Pos tions	sibility of hazardous reac- s	:		d and vapor. n explosive mixture with air. trong oxidizing agents.
Con	ditions to avoid	:	Heat, flames and	d sparks.
Inco	mpatible materials	:	Oxidizing agents	
	ardous decomposition lucts	:	No hazardous de	ecomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes Inhalation Skin contact Ingestion Eye contact	of exposure
Acute toxicity	
Not classified based on availa	able information.
Product:	
Acute oral toxicity	: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Ingredients:	
Ethanol:	
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 124.7 mg/l Exposure time: 4 h Test atmosphere: vapor
Propan-2-ol:	
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 72.6 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	: LD50 (Rat): > 5,000 mg/kg
Skin corrosion/irritation	

Not classified based on available information.

Product:

Result: No skin irritation

Ingredients:



Version	Revision Date:	MSDS Number:
1.2	03/18/2015	36799-00003

Date of last issue: 02/10/2015 Date of first issue: 12/12/2014

Ethanol:

Species: Rabbit Method: OECD Test Guideline 404 Result: No skin irritation

Propan-2-ol: Species: Rabbit Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Ingredients:

Ethanol: Species: Rabbit Result: Irritation to eyes, reversing within 21 days Method: OECD Test Guideline 405

Propan-2-ol:

Species: Rabbit Result: Irritation to eyes, reversing within 21 days

Respiratory or skin sensitization

Skin sensitization: Not classified based on available information. Respiratory sensitization: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitization.

Ingredients:

Ethanol: Test Type: Local lymph node assay (LLNA) Routes of exposure: Skin contact Species: Mouse Result: negative

Propan-2-ol:

Test Type: Buehler Test Routes of exposure: Skin contact Species: Guinea pig Method: OECD Test Guideline 406 Result: negative

Germ cell mutagenicity

Not classified based on available information.

Ingredients:

Ethanol:

Genotoxicity in vitro

: Test Type: In vitro mammalian cell gene mutation test Result: negative



ersion 2	Revision Date: 03/18/2015	MSDS Number: 36799-00003	Date of last issue: 02/10/2015 Date of first issue: 12/12/2014				
Genote	oxicity in vivo	: Test Type: Roc Species: Mous Application Ro Result: negativ	ute: Ingestion				
Propa	n-2-ol:						
•	oxicity in vitro	: Test Type: Bac Result: negativ	terial reverse mutation assay (AMES) e				
Genote	oxicity in vivo	cytogenetic ass Species: Mous Application Rot	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative				
Carcir	nogenicity						
	assified based on av	ailable information.					
Specie Applica Expos Metho	n-2-ol:	6					
IARC			his product present at levels greater than or dentified as probable, possible or confirmed n by IARC.				
OSHA	X		nis product present at levels greater than or dentified as a carcinogen or potential carcino-				
NTP			his product present at levels greater than or dentified as a known or anticipated carcinoger				
-	ductive toxicity	vailable information					
	lients:						
Ethan							
	s on fertility	Species: Mous Application Ro	ute: Ingestion Test Guideline 416				



Version 1.2	Revision Date: 03/18/2015		SDS Number: 799-00003	Date of last issue: 02/10/2015 Date of first issue: 12/12/2014
			Result: negative	
Effec	ts on fetal development	:	Test Type: Embr Species: Rat Application Rout Result: negative	yo-fetal development e: Ingestion
STO	T-single exposure			
Not c	lassified based on availa	able	information.	
	edients:			
	an-2-ol: ssment: May cause drov	vsin	ess or dizziness.	
STO	T-repeated exposure			
	lassified based on availa	able	information.	
Repe	eated dose toxicity			
Etha Spec NOA Appli	edients: nol: ies: Rat EL: 2,400 mg/kg cation Route: Ingestion isure time: 2 y			
Spec NOA Appli Expo	an-2-ol: ies: Rat EL: 5000 ppm cation Route: inhalation sure time: 104 w od: OECD Test Guidelin	•••	,	
-	ration toxicity classified based on availa	able	information.	
SECTION	12. ECOLOGICAL INF	ORM	IATION	
Ecot	oxicity			
	edients:			
Etha				
Toxic	city to fish	:	LC50 (Pimephale Exposure time: 9	es promelas (fathead minnow)): > 1,000 mg/l l6 h
	tity to daphnia and other tic invertebrates	:	EC50 (Daphnia r Exposure time: 4	nagna (Water flea)): > 1,000 mg/l 8 h
Toxic	city to algae	:	Exposure time: 7	vulgaris (Fresh water algae)): 275 mg/l 2 h Fost Guideline 201

Method: OECD Test Guideline 201



ersion 2	Revision Date: 03/18/2015		SDS Number: 799-00003	Date of last issue: 02/10/2015 Date of first issue: 12/12/2014
aquatio	ry to daphnia and other c invertebrates nic toxicity)	:	NOEC (Daphnia r Exposure time: 9	nagna (Water flea)): 9.6 mg/l d
Toxicit	y to bacteria	:	EC50 (Photobacte Exposure time: 0.	erium phosphoreum): 32.1 mg/l 25 h
	n-2-ol: ty to fish	:	LC50 (Pimephale Exposure time: 96	s promelas (fathead minnow)): 10,000 mg/l S h
	y to daphnia and other cinvertebrates	:	EC50 (Daphnia m Exposure time: 24	agna (Water flea)): > 10,000 mg/l ł h
Toxicit	y to algae	:	ErC50 (Scenedes mg/l Exposure time: 8	mus quadricauda (Green algae)): > 1,800 d
Toxicit	y to bacteria	:	EC50 (Pseudomo Exposure time: 16	nas putida): > 1,050 mg/l S h
Persis	stence and degradabil	ity		
Ingred	lients:			
Ethan Biodeg	ol: gradability	:	Result: Readily bi Biodegradation: 8 Exposure time: 20	34 %
	n-2-ol: gradability	:	Result: rapidly de	gradable
Bioac	cumulative potential			
Ingred				
	ol: on coefficient: n- ol/water	:	log Pow: -0.35	
Partitic	n-2-ol: on coefficient: n- ol/water	:	log Pow: 0.05	
	ty in soil ta available			
	adverse effects ta available			



Version	Revision Date:	MSDS Number:	Date of last issue: 02/10/2015
1.2	03/18/2015	36799-00003	Date of first issue: 12/12/2014

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods Waste from residues	: Dispose of in accordance with local regulations.
Contaminated packaging	 Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulation

UNRTDG UN number Proper shipping name Class Packing group Labels	 : UN 1987 : ALCOHOLS, N.O.S. (Ethanol, Propan-2-ol) : 3 : III : 3
IATA-DGR UN/ID No. Proper shipping name Class Packing group Labels Packing instruction (cargo aircraft)	 : UN 1987 : Alcohols, n.o.s. (Ethanol, Propan-2-ol) : 3 : III : Flammable Liquids : 366
Packing instruction (passenger aircraft) IMDG-Code UN number Proper shipping name Class Packing group Labels EmS Code Marine pollutant	 : 355 : UN 1987 : ALCOHOLS, N.O.S. (Ethanol, Propan-2-ol) : 3 : III : 3 : F-E, S-D : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR



Version	Revision Date:	MSDS Number:	Date of last issue: 02/10/2015	
1.2	03/18/2015	36799-00003	Date of first issue: 12/12/2014	
UN/ID/NA number		: UN 1987		
Proper shipping name		: ALCOHOLS, N.O.S.		
Class Packing group Labels ERG Code Marine pollutant		: 3 : III : FLAMMABLE LIC : 127 : no	QUID	

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312	Hazards :	Fire Hazard Acute Health Hazard			
SARA 302	:	No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.			
SARA 313	:	The following components are subject to reporting levels established by SARA Title III, Section 313:			
		Propan-2-ol	67-63-0	3.4086 %	
US State Regulations					
Pennsylvania Right To Know					
	Ethanol		64-17-5	50 - 70 %	
	Water		7732-18-5	30 - 50 %	
	Propan-2-ol		67-63-0	1 - 5 %	
New Jersey Ri	ght To Know				
	Ethanol		64-17-5	50 - 70 %	
	Water		7732-18-5	30 - 50 %	
	Propan-2-ol		67-63-0	1 - 5 %	
California Proj	o 65	This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.			
The ingredients of this product are reported in the following inventories:					
AICS	:	All ingredients listed or exe	mpt.		

Inventories




Version	Revision Date:	MSDS Number:	Date of last issue: 02/10/2015
1.2	03/18/2015	36799-00003	Date of first issue: 12/12/2014

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION





Full text of other abbreviations

ACGIH ACGIH BEI NIOSH REL OSHA Z-1	:	USA. ACGIH Threshold Limit Values (TLV) ACGIH - Biological Exposure Indices (BEI) USA. NIOSH Recommended Exposure Limits USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL		Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	:	8-hour time weighted average
Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen- cy, http://echa.europa.eu/
Revision Date	:	03/18/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, in-



VersionRevision Date:MSDS Number:Date of last issue: 02/10/20151.203/18/201536799-00003Date of first issue: 12/12/2014

cluding an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8