



Page 1 / 14 Pages

# SAFETY DATA SHEET

According to 2012 OSHA Hazard Communication Standard

(29 CFR 1910.1200)

Sample name: Lithium polymer battery

Sample model:

883759P

**Shenzhen On Real Innovation Electronics** 

**Applicant**:

Technology Limited



Address: B/1,4, NO.2 Jinlong Road, Longgang District, Shenzhen, China Web: www.tiansu.org E-mail: tsjc@tiansu.org Tel: 0755-89457984





Page 2 / 14 Pages

\* The SDS is prepared based on the information provided by client. The contents and formats of this SDS are revised as per client's request.

Section 1- Identification				
(a) Product identifier				
Product name	Lithium polymer battery			
(b) Other means of iden	tification			
	Model: 883759P			
	Nominal Voltage: 3.7V			
Product description	Nominal capacity: 2000mAh			
	Watt-hour: 7.4Wh			
	Weight: 37.1g			
(c) Recommended use of	of the chemical and restrictions on use			
Recommended use	LITHIUM ION BATTERIES			
Uses advised against	No information available.			
(d) Details of the supplie	er of the safety data sheet			
Supplier Name	Shenzhen On Real Innovation Electronics Technology Limited			
Supplier Address	2nd Floor, Building B, Huafeng International Robot Industrial Park, Hangcheng Avenue,			
Supplier Address	Xixiang, Baoan District, Shenzhen China			
Manufacture Company	ShenZhen EPT Battery Co.,Ltd.			
Monufactura Address	Building 3, Huancheng Industrial Park, No.41 Dalang north road, Dalang, Longhua			
Manufacture Address	District, Shenzhen, 518109 Guangdong, P.R. China			
Supplier Phone Number	0755-28078063			
(e) Emergency telephon	e number			

0755-28078063

### **Section 2- Hazards identification**

#### (a) Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.





Page 3 / 14 Pages

Report No.: TSZ23010306-P02-R02

	Page 37 14 Pages				
Reproductive toxicity		Category 2			
Acute toxicity-Oral	Acute toxicity-Oral Category 3				
Skin corrosion/ irritation Category 1					
Specific target organ tox	cicity-repeated exposure	Category 1			
(b) GHS Label elements, including precautionary statements					
Emergency Overview					
Signal word	Danger				
Suspected of damaging fertility or the unborn child Toxic if swallowed Causes severe skin burns and eye damage Cause damage to organs through prolonged or repeated exposure.					
Appearance: No inform	mation available Physical State	Solid <b>Odor</b> : No information available			
P101	If medical advice is needed,,have product	containet or label at hand			
P201	Obtain special instructions before use.				
P202	Do not handle until all safety precautions have been read and understood.				
P260	Do not breathe dust/fume/gas/mist/vapou	s/spray.			
P264	Wash thoroughly after handling.				
P270	dust/fume/gas/mist/vapours/spray				
P280					
D000					





Page 4 / 14 Pages

Report No.: TSZ23010306-P02-R02

		Page 4 / 14 Pa	ages	
	IF expo	osed or concerned: Get medic	al advice/ attention.	
P308+P313	IF SWA	ALLOWED: Immediately call a	POISON CENTER/doctor/\u	2026.
P301+P310	Specifi	Specific treatment (see on this label).		
P321	Rinse r	Rinse mouth.		
P330	IF SWA	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.		
P301+P330+P331	IF ON	SKIN (or hair): Take off immed wer].	iately all contaminated clothi	ng. Rinse skin with water
P303+P361+P353	Wash o	contaminated clothing before r	euse.	
P363	IF INH	ALED: Remove person to fres	n air and keep comfortable fo	or breathing.
P304+P340	Immed	iately call a POISON		
P310	CENTE	ER/doctor/\u2026		
P305+P351+P338	IF IN E	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if		
P314	presen	present and easy to do. Continue rinsing.		
	Get me	Get medical advice/attention if you feel unwell.		
P405	Store le	Store locked up.		
P501	Dispos	Dispose of contents/container to		
(c) Hazards not otherwise classified (HNOC)				
Not applicable	Not applicable			
(d) Unknown Toxicity				
32% of the mixture consists of ingredient(s) of unknown toxicity				
(e) Other information				
Very toxic to aquatic life	e with lon	g lasting effects		
(f) Interactions with O	(f) Interactions with Other Chemicals			
No information availabl	e.			
Section 3- Composition/information on ingredients				
Chemical Name		CAS Number	Weight (%)	Trade Secret
Lithium Cobalt Oxide (L	Lithium Cobalt Oxide (LiCoO <sub>2</sub> ) 12190-79-3 38.33 *			
Copper		7440-50-8	6.64	*

7782-42-5

Graphite



\*

37.85



Page 5 / 14 Pages Phosphate(1-), hexafluoro-, \* 21324-40-3 4.64 lithium \* Aluminum foil 7429-90-5 12.54 "\*" The exact percentage (concentration) of composition has been withheld as a trade secret. Section 4- First-aid measures **Description of first aid measures** • After inhalation: Supply fresh air; consult doctor in case of complaints. · After skin contact: Immediately rinse with water. • After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor. • After swallowing: If symptoms persist consult doctor. • Most important symptoms and effects, both acute and delayed No further relevant information available. · Indication of any immediate medical attention and special treatment needed No further relevant information available. Section 5- Fire-fighting measures (a) Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. (b) Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient. (c) Specific Hazards Arising from the Chemical The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. (d) Hazardous Combustion Products Carbon oxides. (e) Protective equipment and precautions for firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Section 6- Accidental release measures (a) Personal precautions, protective equipment and emergency procedures If the battery is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. The preferred response is to leave the area and allow the vapors to dissipate. Avoid skin and eyes contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerated. If leakage of the battery happens, liquid could be absorbed with sand, earth or other inert substance and contaminated area should be ventilated meantime. (b) Environment precautions Do not allow product to reach sewage system or any water source. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers surface or ground water. (c) Methods and material for containment and cleaning up If battery casing is dismantled, small amounts of electrolyte may leak. Collect all released material in a plastic lined container. Dispose off according to the local law and rules. Avoid leached substances to get into the earth, canalization or waters.



TS(SZ)-YR-B-068-A01



Page 6 / 14 Pages

### Section 7- Handling and storage

#### (a) Precautions for safe handling

#### Handling

Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

(b) Conditions for safe storage, including any incompatibilities

#### Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

#### **Incompatible Products**

Strong acids. Strong oxidizing agents. Strong bases

### Section 8- Exposure controls/personal protection

#### (a) Control parameters

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Graphite	TWA: 3 mg/m <sup>3</sup> inhalable fraction	TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup>
7782-42-5		(vacated) TWA: 3.5 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup>
			TWA: 0.1 mg/m <sup>3</sup>
			Graphite in
			presence of Polycyclic
			aromatic
			hydrocarbons PAH
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	TWA: 0.02 mg/m³	-	-
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA:2.5mg/m³ F	TWA:2.5mg/m <sup>3</sup> F TWA:2.5mg/m <sup>3</sup> dust (vacated)TWA:2.5mg/m <sup>3</sup>	
Copper 7440-50-8	TWA:0.2mg/m <sup>3</sup> fume TWA:1mg/m <sup>3</sup> Cu dust and mist	TWA:0.1mg/m <sup>3</sup> fume TWA:1mg/m <sup>3</sup> dust and mist (vacated) TWA:0.1mg/m <sup>3</sup> Cu dust,fume,mist	IDLH:100mg/m <sup>3</sup> dust ,fume and mist TWA:1mg/m <sup>3</sup> dust and mist TWA:0.1mg/m <sup>3</sup> fume
Aluminum foil 7429-90-5	TWA:1mg/m <sup>3</sup> respirable fraction	TWA:15mg/m <sup>3</sup> total dust TWA:5mg/m <sup>3</sup> respirable fraction (vacated) TWA:15mg/m <sup>3</sup> total dust (vacated) TWA:5mg/m <sup>3</sup>	TWA:10mg/m <sup>3</sup> total dust TWA:5mg/m <sup>3</sup> respirable dust





Ican Su		Page 7 / 14 Pages		
		respirable fraction(vacated)		
		TWA:5mg/m <sup>3</sup> AL Aluminum		
ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value				
OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health				
Other Exposure Guidelines		its revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d ir., 1992) See section 15 for national exposure control parameters		
(b) Appropriate engine	eering contro	ols		
Engineering Measures	Engineering Measures Eyewash stations Ventilation systems			
(c) Individual protection	on measures	s, such as personal protective equipment		
Eye/Face Protection	None require Face protec	ed for consumer use. If there is a risk of contact:. Tight sealing safety goggles. tion shield.		
Skin and body	None required for consumer use. If there is a risk of contact:. Wear protective gloves and			
Protection	protective clothing.			
Respiratory Protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.			
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face			
Section 9- Physical and chemical properties				
Form		Solid		
Color		Black		
Odor		Not Available		
рН		Not Available		
Melting point/freezing p	point	Not Available		
Boiling Point and Boilir	ng range	Not Available		
Flash Point		Not Available		





Page 8 / 14 Pages

Report No.: TSZ23010306-P02-R02

Upper/lower flammability or explosive limits	Not Available		
Vapor Pressure	Not Available		
Vapor Density	Not Available		
Relative density	Not Available		
Solubility in Water	Not Available		
Auto-ignition temperature	Not Available		
Decomposition temperature	Not Available		
Evaporation rate	Not Available		
Flammability (soil, gas)	Not Available		
Viscosity	Not Available		
Section 10- Stability and reactivity			
Reactivity	No information available.		
Chemical stability	Stable under normal conditions.		
Possibility of Hazardous Reactions	None under normal processing.		
Hazardous Polymerization	Hazardous polymerization does not occur.		
Conditions to avoid	Exposure to air or moisture over prolonged periods. Excessive heat.		
Incompatible materials	Acids. Bases. Oxidizing agent.		
Hazardous Decomposition Products	Carbon oxides.		
Section 11 – Toxicological information			
Product Information	Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:		
Eye contact	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause		



TS(SZ)-YR-B-068-A01



Ican Su	Page 9 / 14 Pages
	irreversible damage to eyes.
Skin contact	Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns.
Ingestion	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways.
Component Information	

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Graphite 7782-42-5	> 10000 mg/kg(Rat)	> 3 g/kg(Rabbit)	-

Information on toxicological effects				
	_		_	

Symptoms	kin redness). May cause rec	Erythema (skin redness). May cause redness and tearing	of the	eyes.
Itching. Rasnes. Hives.	nes. Hives.	Itching. Rashes. Hives.		

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization:		May cause sensitization of susceptible persons. May cause sensitization by skin contact.			
Mutagenic Effects:		No informatio	n available.		
Carcinogenicity:		The table belo a carcinogen.		each agency has lis	sted any ingredient as
Chemical Name	ACGIH		IARC	NTP	OSHA
Lithium Cobalt Oxide (CoLiO <sub>2</sub> )	A3		Group 2B		Х

Group 2B

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

12190-79-3 Graphite

7782-42-5

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

A3

X - Present

Reproductive Toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause



Х

TS(SZ)-YR-B-068-A01



Page 10 / 14 Pages

	systemic target organ toxicity from chronic or repeated exposure. (STOT RE).
Chronic Toxicity	Contains a known or suspected carcinogen. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse liver effects.
Target Organ Effects	Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Central Vascular System (CVS).Kidney. Liver. Liver. Cardiovascular system. Systemic Toxicity.
Aspiration Hazard	No information available.

Numerical measures of toxicity Product Information

chapter 3.1 of the GHS document	ATEmix (oral):	12,905.00 mg/kg
	ATEmix (dermal):	10,200.00 mg/kg (ATE)

# Section 12- Ecological information

Ecological Toxicity		Very toxic to aquatic life with long lasting effects.				
Chemical name	Toxicity to Algae	Toxicity to Fish Microorganism		Daphnia Magna (Water Flea)		
Copper 7440-50-8	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: $0.0068 - 0.0156$ mg/L (Pimephales promelas) 96h LC50: = $0.112$ mg/L (Poecilia reticulata) 96h LC50: = $0.3$ mg/L (Cyprinus carpio) 96h LC50: = $0.8$ mg/L (Cyprinus carpio) 96h LC50: = $1.25$ mg/L (Lepomis macrochirus) 96h LC50: = $0.052$ mg/L (Oncorhynchus mykiss) 96h LC50: = $0.2$ mg/L (Pimephales promelas) 96h LC50: < $0.3$ mg/L (Pimephales promelas)		48h EC50: = 0.03 mg/L		
Graphite 7782-42-5				24h EC50: > 5600 mg/L		
Persistence and Degradability		No information available.				
Bioaccumula	tion	No information available.				





Page 11 / 14 Pages

Other adverse effects

No information available.

### **Section 13- Disposal considerations**

#### Waste treatment methods

Disposal methods	This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.
Contaminated Packaging	Disposal should be in accordance with applicable regional, national and local laws and regulations.

#### California Hazardous Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO <sub>2</sub> ) 12190-79-3	Toxic
Copper 7440-50-8	Toxic
Aluminum foil 7429-90-5	Ignitable powder

## Section 14 – Transport information

UN Number -DOT, IMDG, IATA	UN 3480 & UN 3481
UN Proper shipping name -DOT, IMDG, IATA	Lithium ion Batteries (Including lithium ion polymer batteries) or ; Lithium ion Batteries contained in equipments (Including lithium ion polymer batteries) or; Lithium ion Batteries packed with equipment (Including lithium ion polymer batteries)
Transport information	Lithium polymer battery (Sample Model: 883759P) is tested and has passed in accordance with UN manual of Tests and Criteria, Part III, subsection 38.3. The transportation of lithium cells and batteries is regulated by the International Air Transport Association (According to Section IB of PACKING INSTRUCTION 965, or to Section II of PACKING INSTRUCTION 966~967 of IATA DGR 62nd Edition for transportation), International Civil Aviation Organization, International Maritime Dangerous Goods Code and the US Department of Transportation listed in 49 CFR 173.185. Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment",or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45





Page 12 / 14 Pages

	<u>.</u>	T age 12	/ 14 Pages			
Transport hazard clas -DOT, IMDG, IATA	s <b>s(es)</b> 9					
Environmental hazaro	<b>ls</b> Ye	(DOT)				
Marine pollutant	Sy	mbol (fish and tree)	)			
Special precautions f		-	us dangerous substances an	d articles		
EMS Number	F-/	A,S-N				
Transport in bulk acc to Annex II of MARPO and the IBC Code	-	t applicable				
DOT Remarks:	Sp	ecial marking with t	the symbol (fish and tree)			
IMDG Limited quantities (LC Excepted quantities (		de: E0 t permitted as Excepted Quantity				
	Sect	ion 15- Regu	latory information	1		
(a) International Inve	entories					
TSCA	Complies.	Complies.				
DSL	All components are listed either on the DSL or NDSL.					
(b) US Federal Regu	lations					
	Section 313	3 of Title III of the Superfund Amendments and Reauthorization Act of 1986				
SARA 313	(SARA). This product contains a chemical or chemicals which are subject to the reporting					
	requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.					
Chemical Name	C	AS No	Weight-%	SARA 313 – Threshold Values %		
Lithium Cobalt Oxide (CoLiO <sub>2</sub> )	12	190-79-3	15-40	0.1		
Copper	74	40-50-8	3-7	1.0		
Aluminum foil	74	29-90-5	7-13	1.0		
SARA 311/312 Hazard	I Categories					
Acute Health Hazard		No				
Chronic Health Hazard		No				
Fire Hazard		No				
Sudden release of pres	sure hazard	No				
Reactive Hazard		No				
CWA (Clean Water Act)		This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR				





Page 13 / 14 Pages

				122.42)						
Chemical Name	C/	•						/A - Priority	C	WA - Hazardous
		Quantities F		Pollu	Pollutants		Pollutants		Substances	
Copper 7440-50-8					>	X		x		
This ma					aterial, as supplied, contains one or more substances regulated as					
CEF	RCLA			hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)						
Chemical N	lamo		Laz	ardous Su			Extremely F	, ,	FR 302	, RQ
Chemical N	ane		naz	RQs	DStatice	5	Substanc			NQ
Coppe	r			5000	lb				RQ	5000 lb final RQ
7440-50	-8								RQ	2270 kg final RQ
(c) US State Reg	ulatio	ons								
California Propos	ition	65			Thi	s produc	t contains t	ne following P	ropositi	on 65 chemicals.
C	hemic	cal name	)				Cali	fornia Proposi	tion 65	
Gra	phite –	- 7782-4	2-5					Carcinogen		
U.S. State Right-t	o-Knc	ow Regu	latior	IS						
Chemical Name		New Je	rsey	sey Massachuse		Pen	nsylvania	Rhode Island		Illinois
Graphite 7782-42-5		х		X			Х			х
Lithium Cobalt Ox (CoLiO <sub>2</sub> ) 12190-79-3	ide	х					x			x
Aluminum 7429-90-5		х		x			х	x		
Copper 7440-50-8		х		х			Х	Х		Х
(d) International	Regu	lations								
Mexico										
National occupati	ional e	exposur	re limi	ts						
Comp	onent			C	Carcino	gen Stat	us	E	xposur	e Limits
Grap 7782-42-5		40)						Mexico: TWA=3.5 mg/m <sup>3</sup>		
Alum 7429-90-5		13)				Mexico: TV			o: TWA	a= 10 mg/m³
Copper 7440-50-8(3 - 7)			Mexico: TWA= 1 mg/m <sup>3</sup> Mexico: TWA= 0.2 mg/m <sup>3</sup> Mexico: STEL= 2 mg/m <sup>3</sup>			= 0.2 mg/m <sup>3</sup>				
Mexico - Occupational	Exposu	re Limits -	Carcino	ogens						
Canada										
WHMIS Hazard CI	ass			Not deterr	mined					
			Se	ection 1	16- 0	ther i	nformat	ion		





Page 14 / 14 Pages

NFPA	Health Hazards	1	Flammability	0	Instability	0	Physical and Chemical Hazards	-		
HMIS	Health Hazards	2*	Flammability	0	Physical Hazard	0	Personal Protection	Х		
Disclaim The infor the date storage, informati	Chronic Hazard Star Legend * = Chronic Health Hazard  Disclaimer  The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.									

--- End of Report ---

