

A07698 ZEP COM S STL ZUSSTL14A 20N14 STK

Version 2.1 Revision Date 02/09/2017 Print Date 02/15/2017

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : A07698 ZEP COM S STL ZUSSTL14A 20N14 STK

Material number : 0000000001046517

Manufacturer or supplier's details

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW

Atlanta, GA 30318

Telephone : 404-352-1680

For SDS Information : Compliance Services 1-877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Cleaner

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a compressed gas
Colour	amber
Odour	characteristic

GHS Classification

Flammable aerosols : Category 1
Gases under pressure : Compressed gas
Skin irritation : Category 2
Eye irritation : Category 2A
Skin sensitisation : Category 1

GHS label elements

Hazard pictograms







Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

Precautionary statements : **Prevention**:



Version 2.1 Revision Date 02/09/2017 Print Date 02/15/2017

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear eye protection/ face protection.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 50 - < 70
Distillates (petroleum), hydrotreated light	64742-47-8	>= 10 - < 20
Solvent naphtha (petroleum), light aliph.	64742-89-8	>= 5 - < 10
(R)-p-mentha-1,8-diene	5989-27-5	>= 1 - < 5
carbon dioxide	124-38-9	>= 1 - < 5
Solvent naphtha (petroleum), heavy aliph.	64742-96-7	>= 1 - < 5
propan-2-ol	67-63-0	>= 1 - < 5
citral	5392-40-5	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious place in recovery position and seek medical

advice.

If symptoms persist, call a physician.



A07698 ZEP COM S STL ZUSSTL14A 20N14 STK

Version 2.1 Revision Date 02/09/2017 Print Date 02/15/2017

In case of skin contact : If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

If on clothes, remove clothes.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Rinse immediately with plenty of water for at least 15 minutes.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Most important symptoms and effects, both acute and

delayed

Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash. Effects are dependent on exposure (dose, concentration,

contact time).

Causes skin irritation.

Causes serious eye irritation. May cause an allergic skin reaction.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical Water spray jet

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2)

Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored $\frac{1}{2}$

separately in closed containments.

Use a water spray to cool fully closed containers.



Version 2.1 Revision Date 02/09/2017 Print Date 02/15/2017

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Always replace cap after use.

Do not breathe vapours or spray mist.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 $^{\circ}\text{C}.$ Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Keep in a dry, cool and well-ventilated place.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Strong oxidizing agents



 Version 2.1
 Revision Date 02/09/2017
 Print Date 02/15/2017

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CFORT of exposure Permissible concentration Permissi	Components	CAS-No.	Value type	Control	Basis
Exposure Permissible concentration Permissible Permissible concentration Per	Components	CAS-NO.			Dasis
Distillates (petroleum), hydrotreated heavy naphthenic TWA (Mist) 5 mg/m3 OSHA Z-1					
Distillates (petroleum), hydrotreated heavy naphthenic Nydrotreated heavy naphthenic TWA (Inhalable fraction) TWA (Inhalable fraction) TWA (Inhalable fraction) TWA S00 ppm 2,000 mg/m3 OSHA Z-1 TWA Mist) S mg/m3 OSHA Z-1 TWA Mist) S mg/m3 OSHA P0 1,600 mg/m3 OSHA P0 TWA (Mist) S mg/m3 OSHA P0 TWA (Mist) TWA (Mist) S mg/m3 OSHA P0 TWA (Mist) TWA (Mis			(Apodulo)		
Nydrotreated heavy naphthenic	Distillates (petroleum).	64742-52-5	TWA (Mist)		OSHA Z-1
Cinhalable fraction			()	i i i i gi i i i	
Distillates (petroleum), hydrotreated light STEL Steel			TWA	5 mg/m3	ACGIH
Distillates (petroleum), hydrotreated light S4742-47-8 TWA 500 ppm 2,000 mg/m3 CSHA Z-1 2,000 mg/m3 CSHA P0 TWA 400 ppm 1,600 mg/m3 CSHA P0 TWA (Mist) 5 mg/m3 NIOSH REL ST (Mist) 10 mg/m3 NIOSH REL PEL (particulate) (particulate) STEL 30,000 ppm ACGIH TWA 5,000 ppm ACGIH TWA 5,000 ppm NIOSH REL TWA 5,000 ppm NIOSH REL TWA 5,000 ppm NIOSH REL STEL 30,000 ppm NIOSH REL STEL 30,000 ppm OSHA Z-1 STEL 30,000 ppm OSHA Z-1 STEL 30,000 ppm OSHA Z-1 STEL 30,000 ppm OSHA P0 STEL 30,000 ppm OSHA P0 STEL 30,000 ppm CAL PEL STEL 30,000 ppm ACGIH STEL 30,000 ppm CAL PEL STEL 30,000 ppm ACGIH TWA 400 ppm ACGIH STEL 400 ppm ACGIH NIOSH REL STEL 30,000 ppm ACGIH STEL 400 ppm ACGIH NIOSH REL STEL 30,000 ppm ACGIH NIOSH REL 30,000 ppm			(Inhalable		
Nydrotreated light					
TWA		64742-47-8	TWA		OSHA Z-1
1,600 mg/m3	hydrotreated light	ļ			
TWA (Mist)			TWA		OSHA P0
TWA (Mist) 5 mg/m3 OSHA PO				•	
TWA (Mist) 5 mg/m3 NIOSH REL ST (Mist) 10 mg/m3 NIOSH REL PEL (particulate) 5 mg/m3 CAL PEL Carbon dioxide 124-38-9 TWA 5,000 ppm ACGIH TWA 5,000 ppm NIOSH REL STEL 30,000 ppm NIOSH REL ST 30,000 ppm NIOSH REL ST 30,000 ppm OSHA Z-1 TWA 5,000 mg/m3 STEL 30,000 ppm OSHA PO 18,000 mg/m3 STEL 30,000 ppm CAL PEL STEL 30,000 ppm CAL PEL STEL 30,000 ppm CAL PEL STEL 400 ppm ACGIH TWA 400 ppm NIOSH REL TWA 400 ppm NIOSH REL STEL 400 ppm NIOSH REL TWA 400 ppm NIOSH REL STEL 400 ppm NIOSH REL TWA 400 ppm NIOSH REL STEL 500 ppm OSHA Z-1 TWA 400 ppm OSHA Z-1 TWA 400 ppm OSHA Z-1 STEL 500 ppm OSHA Z-1 STEL 500 ppm OSHA Z-1 STEL 500 ppm OSHA PO 1,225 mg/m3 TWA 400 ppm OSHA PO 1,225 mg/m3 CAL PEL CA					
ST (Mist)					
PEL (particulate) 5 mg/m3 CAL PEL			` '		
Carbon dioxide 124-38-9 TWA 5,000 ppm ACGIH STEL 30,000 ppm ACGIH TWA 5,000 ppm NIOSH REL 9,000 mg/m3 NIOSH REL 9,000 mg/m3 NIOSH REL 54,000 mg/m3 NIOSH REL 1WA 5,000 ppm OSHA Z-1 9,000 mg/m3 OSHA PO 18,000 mg/m3 OSHA PO 54,000 mg/m3 OSHA PO 54,000 mg/m3 OSHA PO 54,000 mg/m3 CAL PEL 9,000 mg/m3 CAL PEL 5,000 ppm CAL PEL 5,000 mg/m3 CAL PEL 54,000 mg/m3 CAL PEL 54,000 mg/m3 CAL PEL 54,000 mg/m3 CAL PEL 54,000 mg/m3 CAL PEL 17WA 400 ppm ACGIH 17WA 400 ppm NIOSH REL 1,225 mg/m3 NIOSH REL 1,225 mg/m3 OSHA PO 1,225 mg/m3 OSHA PO 1,225 mg/m3 OSHA PO 1,225 mg/m3<		<u> </u>			
STEL 30,000 ppm ACGIH				5 mg/m3	CAL PEL
TWA 5,000 ppm 9,000 mg/m3 NIOSH REL 9,000 mg/m3 NIOSH REL 54,000 mg/m3 NIOSH REL 54,000 mg/m3 OSHA Z-1 9,000 mg/m3 OSHA Z-1 9,000 mg/m3 OSHA P0 18,000 mg/m3 OSHA P0 18,000 mg/m3 OSHA P0 54,000 mg/m3 OSHA P0 54,000 mg/m3 OSHA P0 54,000 mg/m3 OSHA P0 54,000 mg/m3 OSHA P0 STEL 30,000 ppm CAL PEL 9,000 mg/m3 OSHA P0 54,000 mg/m3 OSHA P0 STEL 30,000 ppm ACGIH STEL 400 ppm ACGIH TWA 200 ppm ACGIH TWA 400 ppm NIOSH REL 980 mg/m3 OSHA Z-1 980 mg/m3 OSHA Z-1 980 mg/m3 OSHA Z-1 STEL 500 ppm OSHA Z-1 STEL 500 ppm OSHA Z-1 STEL 500 ppm OSHA P0 980 mg/m3 OSHA P0 1,225 mg/m3 OSHA P0 1,225 mg/m3 OSHA P0 1,225 mg/m3 OSHA P0 PEL 400 ppm 980 mg/m3	carbon dioxide	124-38-9			
9,000 mg/m3 ST 30,000 ppm NIOSH REL 54,000 mg/m3 TWA 5,000 ppm OSHA Z-1 9,000 mg/m3 TWA 10,000 ppm OSHA P0 18,000 mg/m3 STEL 30,000 ppm OSHA P0 54,000 mg/m3 PEL 5,000 ppm CAL PEL 9,000 mg/m3 STEL 30,000 ppm CAL PEL 54,000 mg/m3 STEL 400 ppm ACGIH TWA 200 ppm ACGIH TWA 400 ppm NIOSH REL 980 mg/m3 ST 500 ppm NIOSH REL 1,225 mg/m3 TWA 400 ppm OSHA Z-1 980 mg/m3 STEL 500 ppm OSHA P0 1,225 mg/m3 STEL 500 ppm OSHA P0 1,225 mg/m3 PEL 400 ppm OSHA P0 1,225 mg/m3 PEL 400 ppm OSHA P0 1,225 mg/m3 OSHA P0					
ST 30,000 ppm 54,000 mg/m3 NIOSH REL			TWA		NIOSH REL
TWA 5,000 mg/m3 OSHA Z-1					
9,000 mg/m3 10,000 ppm			ST		NIOSH REL
TWA 10,000 ppm 18,000 mg/m3 OSHA P0 18,000 mg/m3 OSHA P0 54,000 mg/m3 PEL 5,000 ppm 54,000 mg/m3 CAL PEL 9,000 mg/m3 CAL PEL 30,000 ppm 54,000 mg/m3 PTEL 30,000 ppm 54,000 mg/m3 CAL PEL 5,000 ppm CAL PEL 5,000 ppm ACGIH 54,000 mg/m3 PTEL 400 ppm ACGIH TWA 400 ppm NIOSH REL 980 mg/m3 PTWA 400 ppm NIOSH REL 1,225 mg/m3 PTWA 400 ppm OSHA Z-1 980 mg/m3 PTWA 400 ppm OSHA Z-1 980 mg/m3 PTWA 400 ppm OSHA P0 980 mg/m3 PEL 500 ppm OSHA P0 1,225 mg/m3 PEL 400 ppm OSHA P0 PEL 400 ppm OSHA PD PEL 400 ppm OSHA PD PEL 400 ppm OSHA PD PEL 400 ppm OSHA PEL PEL PEL 400 ppm OSHA PD PEL 400 ppm OSHA PD PEL 400 ppm OSHA PD PEL 400 ppm OSHA PEL			TWA		OSHA Z-1
STEL 30,000 ppm 54,000 mg/m3 CAL PEL			TWA	10,000 ppm	OSHA P0
PEL 5,000 ppm 9,000 mg/m3 STEL 30,000 ppm 54,000 mg/m3 propan-2-ol 67-63-0 TWA 200 ppm ACGIH STEL 400 ppm ACGIH TWA 400 ppm NIOSH REL 980 mg/m3 ST 500 ppm NIOSH REL 1,225 mg/m3 TWA 400 ppm OSHA Z-1 980 mg/m3 STEL 500 ppm OSHA PO 980 mg/m3 PEL 500 ppm OSHA PO 1,225 mg/m3 TWA 400 ppm OSHA PO 980 mg/m3 STEL 500 ppm OSHA PO 1,225 mg/m3 CAL PEL			STEL	30,000 ppm	OSHA P0
STEL 30,000 ppm 54,000 mg/m3			PEL		CAL PEL
propan-2-ol 67-63-0 TWA 200 ppm ACGIH STEL 400 ppm ACGIH TWA 400 ppm NIOSH REL 980 mg/m3 NIOSH REL 1,225 mg/m3 NIOSH REL 1,225 mg/m3 OSHA Z-1 980 mg/m3 OSHA PO 980 mg/m3 OSHA PO 1,225 mg/m3 OSHA PO 1,225 mg/m3 CAL PEL PEL 400 ppm CAL PEL 980 mg/m3 CAL PEL			STEL	30,000 ppm	CAL PEL
STEL 400 ppm ACGIH TWA 400 ppm NIOSH REL 980 mg/m3 NIOSH REL ST 500 ppm NIOSH REL 1,225 mg/m3 OSHA Z-1 980 mg/m3 OSHA PO TWA 400 ppm OSHA PO 980 mg/m3 OSHA PO STEL 500 ppm OSHA PO 1,225 mg/m3 OSHA PO PEL 400 ppm CAL PEL 980 mg/m3 CAL PEL	propan-2-ol	67-63-0			
980 mg/m3 ST 500 ppm NIOSH REL 1,225 mg/m3 TWA 400 ppm OSHA Z-1 980 mg/m3 TWA 400 ppm OSHA P0 980 mg/m3 STEL 500 ppm OSHA P0 1,225 mg/m3 PEL 400 ppm CAL PEL 980 mg/m3			STEL		ACGIH
980 mg/m3 ST 500 ppm NIOSH REL 1,225 mg/m3 TWA 400 ppm OSHA Z-1 980 mg/m3 TWA 400 ppm OSHA P0 980 mg/m3 STEL 500 ppm OSHA P0 1,225 mg/m3 PEL 400 ppm CAL PEL 980 mg/m3			TWA		NIOSH REL
1,225 mg/m3 TWA 400 ppm OSHA Z-1 980 mg/m3 TWA 400 ppm OSHA P0 980 mg/m3 STEL 500 ppm OSHA P0 1,225 mg/m3 PEL 400 ppm CAL PEL 980 mg/m3				980 mg/m3	
TWA 400 ppm 980 mg/m3 TWA 400 ppm 980 mg/m3 OSHA Z-1 980 mg/m3 OSHA P0 980 mg/m3 STEL 500 ppm OSHA P0 1,225 mg/m3 PEL 400 ppm CAL PEL 980 mg/m3			ST		NIOSH REL
980 mg/m3 TWA 400 ppm OSHA P0 980 mg/m3 STEL 500 ppm OSHA P0 1,225 mg/m3 PEL 400 ppm CAL PEL 980 mg/m3					
TWA 400 ppm 980 mg/m3 STEL 500 ppm OSHA P0 1,225 mg/m3 PEL 400 ppm CAL PEL 980 mg/m3			TWA		OSHA Z-1
980 mg/m3 STEL 500 ppm OSHA P0 1,225 mg/m3 PEL 400 ppm CAL PEL 980 mg/m3					
STEL 500 ppm OSHA P0 1,225 mg/m3 PEL 400 ppm CAL PEL 980 mg/m3			TWA		OSHA P0
1,225 mg/m3 PEL 400 ppm CAL PEL 980 mg/m3			STEL		OSHA P0
PEL 400 ppm CAL PEL 980 mg/m3					
· · · · · · · · · · · · · · · · · · ·			PEL	400 ppm	CAL PEL
0122 000 pp 0/12 22			STEL	500 ppm	CAL PEL



A07698 ZEP COM S STL ZUSSTL14A 20N14 STK

Version 2.1 Revision Date 02/09/2017 Print Date 02/15/2017

1				1,225 mg/m3	
	citral	5392-40-5	TWA (Inhalable fraction and vapor)	5 ppm	ACGIH

Biological occupational exposure limits

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of	40 mg/l	ACGIH BEI
				workwee k		

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Ensure that eyewash stations and safety showers are close to

the workstation location. Tightly fitting safety goggles

Eye wash bottle with pure water Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a compressed gas

Colour : amber

Odour : characteristic
Odour Threshold : No data available



A07698 ZEP COM S STL ZUSSTL14A 20N14 STK

Version 2.1 Revision Date 02/09/2017 Print Date 02/15/2017

pH : Not applicable

Melting point/freezing point : No data available

Boiling point : 82.22 °C

Flash point

No data available

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available
Density : 0.856 g/cm3

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : not determined

Thermal decomposition : No data available

Viscosity

Viscosity, kinematic : No data available

Heat of combustion : 44.04 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

: Carbon oxides



Version 2.1 Revision Date 02/09/2017 Print Date 02/15/2017

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical

: None known.

Condition

Symptoms of Overexposure

: Effects are immediate and delayed.

Symptoms may include irritation, redness, pain, and rash. Effects are dependent on exposure (dose, concentration,

contact time).

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 5 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l

Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

(R)-p-mentha-1,8-diene:



A07698 ZEP COM S STL ZUSSTL14A 20N14 STK

Version 2.1 Revision Date 02/09/2017 Print Date 02/15/2017

Acute oral toxicity : LD50 Oral Rat: 4,400 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: > 5,000 mg/kg

propan-2-ol:

Acute oral toxicity : LD50 Oral Rat: 4,396 mg/kg
Method: Calculation method

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Irritating to eyes.

Respiratory or skin sensitisation

Product:

Remarks: Causes sensitisation.

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Distillates (petroleum), hydrotreated heavy naphthenic:

Distillates (petroleum), hydrotreated light:

Solvent naphtha (petroleum), light aliph.:

(R)-p-mentha-1,8-diene:

carbon dioxide:

Solvent naphtha (petroleum), heavy aliph.:

propan-2-ol:

citral:

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:



A07698 ZEP COM S STL ZUSSTL14A 20N14 STK

Version 2.1 Revision Date 02/09/2017 Print Date 02/15/2017

Remarks: No data available

Components:

Distillates (petroleum), hydrotreated light:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-

octanol/water Components:

citral:

Partition coefficient: n-

octanol/water

: Pow: 2.76

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

: Remarks: No data available

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to

aquatic life.

Components:

Distillates (petroleum), hydrotreated light:

Additional ecological

information

: No data available



Version 2.1 Revision Date 02/09/2017 Print Date 02/15/2017

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification

requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.



A07698 ZEP COM S STL ZUSSTL14A 20N14 STK

Version 2.1 Revision Date 02/09/2017 Print Date 02/15/2017

SARA 311/312 Hazards : Sudden Release of Pressure Hazard

Acute Health Hazard

Fire Hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65 This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

TSCA On TSCA Inventory

DSL This product contains the following components that are not on the

Canadian DSL nor NDSL.

For information on the country notification status for other regions please contact the manufacturer's regulatory group.


Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Further information





Special hazard.

HMIS III:

HEALTH	2
FLAMMABILITY	4
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

OSHA - GHS Label Information:



Revision Date 02/09/2017 Version 2.1 Print Date 02/15/2017

Hazard pictograms







Signal word

Danger:

Hazard statements

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Precautionary statements

Prevention: Keep aw ay from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash skin thoroughly after handling. Contaminated work clothing should not be allow ed

out of the w orkplace. Wear eye protection/face protection. Wear protective gloves. Response: IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and

wash before reuse.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	2.1
Revision Date:	02/09/2017
Print Date:	02/15/2017

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.